

Parts & Accessories

Wire & Cable

14 Ga. Direct Burial Speaker Wire

For outdoor speakers, low voltage lighting, and many other outdoor or direct burial applications. The cable features a specially formulated black polyethylene jacket that is U/V resistant and provides protection against water damage. The audiophile grade wire contains 41 strands of 99.9% pure copper conductors, totaling 14 ga. The high strand count provides improved skin effect. Available in 100, 500, and 1,000 ft. lengths.



Part #	Description	Price (1-3)	Price (4-UP)
100-780	100 ft.	\$34.90	\$32.50
100-782	500 ft.	155.10	146.85
100-784	1,000 ft.	293.22	275.14

Low Voltage Direct Burial Wire



Carol's direct burial wire was primarily designed for low voltage landscape and security lighting. It is also well suited for outdoor speakers and other direct burial applications. These cables feature a specially formulated black PVC jacket that is U/V resistant and provides protection against water damage. The jacket utilizes a duplex parallel design that allows easy separation of conductors and quicker terminations during installation. A polarity ridge on one leg make for circuit identification easy. The wire features high strand count, bare copper conductors and is available in 12, 14 and 16 ga. They are UL listed for up to 150V and UL rated for direct burial and outdoor applications. OSHA accepted. Available in 100 and 500 ft. lengths.



Part #	AWG	Length	Price (1-3)	Price (4-UP)
100-844	16	500 ft.	\$146.82	\$135.54
100-845	16	100 ft.	29.71	26.84
100-846	14	500 ft.	223.04	207.09
100-847	14	100 ft.	66.53	50.11
100-848	12	500 ft.	311.64	289.37
100-849	12	100 ft.	82.97	70.22

Belden Audiophile Grade Power Cable



This high quality power cable has become the leading wire for custom designed power cables. The 12 AWG cable features (7x20) tinned copper conductors, Teflon® insulation, 100% Beldfoil® shield with 85% tinned copper braid shield and a Teflon® jacket. UL approved CMP and rated for plenum use. Sold by the foot.

#100-790 \$9.99 LIST **\$7.98** (1-9) **\$7.52** (10-UP)

Automotive Zip Cord Speaker Wire

Bare copper conductors with red and black PVC insulation. Can also be used as car audio power cable. Voltage rating: 300V. Temperature range: -20°C to +60°C. Made in the USA. Please order a minimum of 10 ft.



Part #	AWG	Color	Length	Price
100-050	18	Red/Black	1 ft.	\$.31
100-052	18	Red/Black	500 ft.	76.27
100-051	18	Red/Black	1,000 ft.	143.07
100-055	16	Red/Black	1 ft.	.47
100-056	16	Red/Black	1,000 ft.	210.34
100-060	14	Red/Black	1 ft.	.62
100-061	14	Red/Black	1,000 ft.	319.89
100-065	12	Red/Black	1 ft.	.98
100-066	12	Red/Black	1,000 ft.	504.57

Heavy Duty SJOOW Power Cable



Heavy duty 3 conductor power cable is perfect for use on professional sound stages and other high current applications. It features 99.9% pure stranded copper for maximum conductivity. The premium grade black rubber jacket provides excellent resistance to abrasion, water, oil and is highly flexible, even in low temperatures. UL listed and CSA certified for indoor and outdoor use. Temperature range: -40°C to +90°C. Voltage rating: 300 volts, type SJOOW. UL #62. CSA #C22.2-49 where applicable. 3 conductor colors: black, white and green. Made in the USA.



Part #	AWG	Construction	Nominal O.D.	Current Rating	Length	Price
100-574	14	41 x 30 ga.	0.365	18 A	25 ft.	\$26.14
100-575	14	41 x 30 ga.	0.365	18 A	50 ft.	48.33
100-576	14	41 x 30 ga.	0.365	18 A	250 ft.	181.34
100-577	12	65 x 30 ga.	0.430	25 A	25 ft.	33.90
100-578	12	65 x 30 ga.	0.430	25 A	50 ft.	64.01
100-579	12	65 x 30 ga.	0.430	25 A	250 ft.	246.41
100-580	10	104 x 30 ga.	0.570	30 A	25 ft.	48.18
100-581	10	104 x 30 ga.	0.570	30 A	50 ft.	92.50
100-582	10	104 x 30 ga.	0.570	30 A	250 ft.	362.38

Heavy Duty SJ Cable



This heavy duty cable is very flexible, making it suitable for a variety of uses. From speaker cables on a professional sound stage, to replacing the cords on small appliances, the applications for this wire are unlimited. Premium grade black rubber jacket allows good flexibility even in low temperatures. Temperature range: -40°C to +60°C. Voltage rating: 300 volts, type SJ. UL #62. CSA #C22.2-49 where applicable. Not suitable for use where subject to acid, grease, oil, or solvents. 2 conductor colors: black and white. 4 conductor colors: black, white, green and red. Made in the USA.



Part #	AWG	# Cond.	Construction	Nominal O.D.	Current Rating	Length	Price
100-553	16	2	26 x 30 ga.	0.320"	13 A	25 ft.	\$14.77
100-551	16	2	26 x 30 ga.	0.320"	13 A	50 ft.	25.59
100-552	16	2	26 x 30 ga.	0.320"	13 A	250 ft.	95.61
100-561	14	2	41 x 30 ga.	0.350"	18 A	25 ft.	18.79
100-559	14	2	41 x 30 ga.	0.350"	18 A	50 ft.	33.74
100-560	14	2	41 x 30 ga.	0.350"	18 A	250 ft.	131.47
100-587	14	4	41 x 30 ga.	0.395"	15 A	50 ft.	61.94
100-588	14	4	41 x 30 ga.	0.395"	15 A	250 ft.	256.91
100-569	12	2	65 x 30 ga.	0.425"	25 A	25 ft.	21.57
100-567	12	2	65 x 30 ga.	0.425"	25 A	50 ft.	44.39
100-568	12	2	65 x 30 ga.	0.425"	25 A	250 ft.	179.46
100-590	12	4	65 x 30 ga.	0.470"	20 A	50 ft.	72.84
100-591	12	4	65 x 30 ga.	0.470"	20 A	250 ft.	305.46

Taperwire Flat Adhesive Backed Wire

Flat, adhesive backed, 16 ga., 2 conductor wire tape with a waterproof surface. Available in 16 ft. lengths. Can be run under carpets and up walls. Invisible under paint, spackle, or wall covering. Perfect for use with speakers, intercoms, and security alarms. For indoor and outdoor applications. Includes terminal blocks and installation instructions. 1.25" W x .025" H.



#100-015 \$38.44 (1-9) **\$34.60** (10-UP)

High Current Power Cable



Large gauge cable for running power and ground lines to high power car amplifiers. Copper rope lay construction with extra flexible PVC insulation. Made in the USA. Please order a minimum of 5 ft.



Part #	AWG	Color	Construction	Price Per Ft. (5-99 Ft.)	(100 Ft. -UP)
100-160	10	Red	413 x 36 ga.	\$.60	\$.45
100-162	10	Black	413 x 36 ga.	.60	.45
100-178	8	Red	665 x 36 ga.	.95	.71
100-174	8	Black	665 x 36 ga.	.95	.71
100-194	4	Red	1050 x 34 ga.	1.95	1.65
100-196	4	Black	1050 x 34 ga.	1.95	1.65
100-180	2	Red	2641 x 36 ga.	3.50	2.90
100-182	2	Black	2641 x 36 ga.	3.50	2.90