

### Galaxy Audio Check Mate SPL Meters

- Compact size: 9.1" x 2.1" x 1.3"
- Easy-to-read LCD screen
- Low cost, high performance
- MAX function (CM-130) or MIN/MAX (CM-140)
- Level range display
- Resolution 0.5 dB (CM-130) or 0.1 dB (CM-140)
- "A" and "C" weighting modes
- Windscreens and 9V battery included



Compact, affordable, and professional sound pressure level meters. Multi-range scales for testing a wide variety of audio sources. Great for nightclubs, DJs, festivals, and even industrial noise compliance testing. CM-130 frequency range 125 to 8,000 Hz, CM-140 frequency range 31.5 to 8,000 Hz.

Part #	Description	List Price	Price Each
<b>245-262</b>	Check Mate CM-130 SPL Meter	\$ 74.99	<b>\$49.99</b>
<b>245-263</b>	Check Mate CM-140 SPL Meter	149.99	<b>99.99</b>
<b>245-264</b>	Check Mate Carrying Holster		<b>9.99</b>

### Galaxy Audio Cricket Polarity Test Set

- Checks system and component polarity
- High level, low level; balanced or unbalanced
- Can drive speakers directly
- Determines microphone XLR pin polarity
- Operates on two 9 volt batteries (included)



**#245-261** ..... \$149.99 LIST **\$99.99** EACH

### Computer Monitor/TV Tester

- Quickly and easily troubleshoot, test, and align computer monitors and TVs. Tests VGA, SVGA, 8514A, VESA and MAC monitors • Generates the following video test patterns: color bars, cross hatch, dots, color raster (white, red, green, blue), and windows • It includes a circle and true NTSC color pattern • Powered by either a 9V battery or an external AC adapter (not included, use #120-1055).



**#390-764** ..... \$269.99 LIST **\$189.95** EACH

### Video Monitor/TV Tester

- Quickly and easily troubleshoot, test, and align video monitors and TVs • Generates the following video test patterns: True NTSC color bars, cross hatch, dots, color raster (white, red, green, blue), black burst raster, staircase, circle and windows • Provides a composite and S-video (Y/C) output as well as an audio (1 kHz) output for testing audio circuits • Powered by either a 9V battery or an external AC adapter (not included, use #120-1055)



**#390-760** ..... \$239.99 LIST **\$169.95** EACH

### HDTV Pattern Generator

Designed for testing, calibration, and service of High Definition TV and NTSC analog television

- 4 selectable modes including 1080i, 720p, 480p, and NTSC
- 9 commonly used video test patterns including Color Bars, cross hatch, staircase, multiburst, overscan-bounce, plunge, needle, checker, raster (choose from white, yellow, cyan, green, magenta, red, blue, and black)
- AC adapter power source or standard 9V battery operation (Batteries not included, use #140-116)



**#390-766** ..... \$399.99 LIST **\$348.76** EACH

### Sound Pressure Level Meter

- Measure ambient noise up to 120 dB
- Two ranges increase accuracy (40-80 dB, 80-120 dB)
- "A" weighted (ANSI) frequency measurements
- Includes internal battery and calibration tests
- Operates on a 9V battery
- Dimensions: 3" x 6" x 2".



**#390-750** ..... **\$39.80** EACH



*Gold Line offers the professional sound contractor and the music industry a line of instrument quality products designed to facilitate the installation, use, and maintenance of any sound system. Gold Line products are proudly made in the USA and are covered by a one year limited warranty.*



### DSP-30 Real Time Analyzer

- 85 dB display window
- Microphone measurement range is 31 dB to 123 dB
- 30 one-third octave bands
- Triple tuned filters
- Time averaging of frequency response
- 3 decay times provided
- Printer port
- Pink noise generator input



**#390-805** ..... \$1,991.00 LIST **\$1,368.97** EACH

### ASA-10B Hand Held 10-Band Audio Spectrum Analyzer

- Octave bands (10 bands) from 32 Hz to 16 kHz on ISO centers
- Includes a built-in microphone
- Fast/slow decay times
- Short duration hold mode
- Step attenuator to read broadband SPL with a measurement range of 40-122 dB



**#390-815** ..... \$412.20 LIST **\$299.29** EACH

### APT-2 Absolute Phase Tester/Pulse Generator Set

- State of the art signal processing to accurately determine absolute polarity
- Works with tweeters, midranges, and woofers, subwoofer speakers and cabinets, plus equalizers, amplifiers, and crossovers
- 1/4" phone jacks for either line level output signal or a signal capable of driving speakers without amplification
- Powered by their own 9V batteries (Batteries not included, use #140-116)



**#390-820** ..... \$390.00 LIST **\$278.39** EACH

### SPL-162 Sound Pressure Level Meter

- Measures sound levels from 89 dB to 162 dB and can be set to flat, C, or A-weighting
- Temporary hold mode
- Power is supplied by 8 AA batteries or by 12VDC power supply
- Includes belt-attachable carrying case large enough to carry the power supply (Batteries not included, use #140-102)



**#390-870** ..... \$641.56 LIST **\$519.72** EACH

### PN-3 Pink Noise Generator

- A gated pink noise source pink noise or bursts plus short pulses
- Output level is 245 mV
- Powered by a 9V battery (Batteries not included, use #140-116)
- Works well in conjunction with the DSP-30 (#390-805) and the ASA10-B (#390-815)



**#390-855** ..... **\$167.00** EACH

### ZM-1 Impedance Meter with Calculated Watts

- Portable, battery operated meter
- Makes measurements on 25, 50, 70, or 100 volt line systems
- Sine waves are generated at 100 Hz, 330 Hz, 1 kHz, or 10 kHz to read impedance or calculated watts
- 200, 2k, or 20k ohm range for better accuracy
- #390-827 includes a protection relay



**#390-825** ..... \$469.00 LIST **\$339.94** EACH

**#390-827** ..... \$569.00 LIST **\$419.29** EACH