

HT625W 6-1/2" and HT825W 8" 2-Way In-Wall Speaker Pairs

HT625W: • Woofer: 6-1/2" glass fiber cone • Tweeter: pivoting 30 mm cloth dome • Power handling: 60 watts RMS/120 watts max • Impedance: 8 ohms • Frequency response: 45-20,000 Hz • SPL: 86 dB 1W/1m • Dimensions: 10-3/4" W x 14-3/4" H x 3-9/32" D • Cutout size: 8-7/8" W x 12-7/8" H • Sold in pairs.



HT825W: • Woofer: 8" glass fiber cone • Tweeter: pivoting 30 mm cloth dome • Power handling: 80 watts RMS/160 watts max • Impedance: 8 ohms • Frequency response: 40-20,000 Hz • SPL: 87 dB 1W/1m • Dimensions: 12-7/16" W x 16-11/16" H x 3-3/4" D • Cutout size: 10-1/2" W x 14-3/4" H • Sold in pairs.

#302-086 (HT625W) **\$379.95** PAIR
#302-090 (HT825W) **\$419.95** PAIR

HT6253W 6-1/2" and HT8253W 8" 3-Way In-Wall Speaker Pairs

HT6253W: • Woofer: 6-1/2" glass fiber cone • Tweeter: pivoting 20 mm cloth dome • Power handling: 100 watts RMS/200 watts max • Impedance: 8 ohms • Frequency response: 45-20,000 Hz • SPL: 87 dB 1W/1m • Dimensions: 12-7/16" W x 16-11/16" H x 3-5/8" D • Cutout size: 10-1/2" W x 14-3/4" H • Sold in pairs.



HT8253W: • Woofer: 8" glass fiber cone • Tweeter: pivoting 20 mm cloth dome • Power handling: 125 watts RMS/250 watts max • Impedance: 8 ohms • Frequency response: 40-20,000 Hz • SPL: 88 dB 1W/1m • Dimensions: 12-7/16" W x 18" H x 3-3/4" D • Cutout size: 10-1/2" W x 16-1/8" H • Sold in pairs.

#302-088 (HT6253W) **\$599.95** PAIR
#302-092 (HT8253W) **\$749.95** PAIR

HT625C 6-1/2" and HT825C 8" Coaxial Ceiling Speaker Pairs

HT625C: • Woofer: 6-1/2" glass fiber cone • Tweeter: pivoting 30 mm cloth dome • Power handling: 60 watts RMS/120 watts max • Impedance: 8 ohms • Frequency response: 45-20,000 Hz • SPL: 86 dB 1W/1m • Dimensions: 10-3/4" dia. x 4" D • Cutout size: 9-1/2" dia. • Sold in pairs.



HT825C: • Woofer: 8" glass fiber cone • Tweeter: pivoting 30 mm cloth dome • Power handling: 80 watts RMS/160 watts max • Impedance: 8 ohms • Frequency response: 40-20,000 Hz • SPL: 87 dB 1W/1m • Dimensions: 12-1/4" dia. x 4-5/8" D • Cutout size: 11" dia. • Sold in pairs.

#302-078 (HT625C) **\$299.95** PAIR
#302-080 (HT825C) **\$379.95** PAIR

HT622BDP 6-1/2" and HT822BDP 8" Ceiling Bi/Di-Pole Speaker Pairs

HT622BDP: • Woofer: 8" glass fiber cone • Tweeter: two 20 mm cloth dome • Power handling: 80 watts RMS/160 watts max • Impedance: 8 ohms • Frequency response: 40-20,000 Hz • SPL: 87 dB 1W/1m • Dimensions: 12-1/4" dia. x 4-3/8" D • Cutout size: 11" dia. • Sold in pairs.



HT822BDP: • Woofer: 6-1/2" glass fiber cone • Tweeter: two 20 mm cloth dome • Power handling: 60 watts RMS/120 watts max • Impedance: 8 ohms • Frequency response: 50-20,000 Hz • SPL: 86 dB 1W/1m • Dimensions: 10-3/4" dia. x 4" D • Cutout size: 9-1/2" dia. • Sold in pairs.

#302-098 (HT622BDP) **\$399.95** PAIR
#302-099 (HT822BDP) **\$479.95** PAIR

MTX Home Theater Series



Features of the Home Theater Series include real-world-tuning for critical listening, glass fiber woofers, cloth dome tweeters, UV resistant baffles, paintable aluminum grills, Chem1 PC boards with mylar capacitors, and air core inductors. Expect nothing but a long life of absolute clarity, backed by a 10-year warranty.

HT625AC 6-1/2" and HT825AC 8" Angled Coaxial Ceiling Speaker Pairs

The MTX Home Theater Series angled in-ceiling speakers are engineered for use in rear/surround speaker applications. Install-ready, pre-assembly, and push-pin terminals save time and trouble when installing. White aluminum mesh grills can be painted to match room decor.



HT625AC: • Woofer: 6-1/2" glass fiber • Tweeter: 30 mm cloth • Power handling: 60 watts RMS/120 watts max • Impedance: 8 ohms • Frequency response: 45-20,000 Hz • SPL: 86 dB • Dimensions: 10-3/4" dia. x 5" D • Cutout size: 9-1/2" dia. • Sold in pairs.

HT825AC: • Woofer: 8" glass fiber • Tweeter: 30 mm cloth • Power handling: 80 watts RMS/160 watts max • Impedance: 8 ohms • Frequency response: 40-20,000 Hz • SPL: 86 dB • Dimensions: 12-1/4" dia. x 5-3/4" D • Cutout size: 11" dia. • Sold in pairs.

#302-082 (HT625AC) **\$379.95** PAIR
#302-084 (HT825AC) **\$449.95** PAIR

HT2625W 6-1/2" In-Wall MTM Center Channel Speaker

Model HT2625W shielded speaker is specifically designed for the center channel of your home theater system. Two woofers in a linear design provides a much smaller footprint, while the pivoting tweeter offers superb sonic imaging.



Specifications: • Woofer: Two 6-1/2" glass fiber cones • Tweeter: pivoting 30 mm cloth dome • Power handling: 100 watts RMS/200 watts max • Impedance: 8 ohms • Frequency response: 45-20,000 Hz • SPL: 89 dB 1W/1m • Dimensions: 16-1/4" W x 10-1/2" H x 3-5/8" D • Cutout size: 14-3/8" W x 8-5/8" H • Sold in individually.

#302-096 **\$299.95** EACH

HT520BDP 5-1/4" In-Wall Bi/Di-Pole Surround Speaker Pair

MTX's HT520BDP is the finishing touch for any home theater. It offers an innovative design without the sacrifice of quality, by providing true Bi/Di-pole surround with its dual 5-1/4" woofers and 20 mm tweeters.



Specifications: • Woofer: Two 5-1/4" glass fiber cones • Tweeter: Two 20 mm cloth dome • Power handling: 125 watts RMS/250 watts max • Impedance: 8 ohms • Frequency response: 60-20,000 Hz • SPL: 89 dB 1W/1m • Dimensions: 16-1/4" W x 12-1/2" H x 3-7/8" D • Cutout size: 14-3/8" W x 10-5/8" H • Sold in pairs.

#302-094 **\$599.95** PAIR

HTS28W Dual 8" In-Wall Subwoofer

HTS28W energizes your home theater experience with the sub-bass of conventional subwoofers—without sacrificing valuable floor space. It features a dual driver design and offers adjustable crossover points of 80 or 100 Hz, while accurately reproducing audio frequencies down to 30 Hz. The two heavy-duty 8" woofers are mounted in a single enclosure, fitting easily into a standard 2 x 4 stud wall for fast installation.



Specifications: • Woofer: (2 x) 8" glass fiber cone • Power handling: 200 watts RMS/400 watts max • Impedance: 8 ohms per driver • Frequency response: 30-100 Hz • SPL: 90 dB 1W/1m • Dimensions: 12-15/16" W x 21" H x 3-5/8" D • Cutout size: 10-1/2" W x 18-1/2" H • Sold individually.

#302-097 **\$499.95** EACH