

Parts & Accessories

Wire Management

NTE 2-to-1 Assorted Size Box

- Resistant to common fluids and solvents
- 2:1 shrink ratio
- Flame retardant
- UL listed



NTE assorted heat shrink boxes offer installers and DIY enthusiasts a simple and convenient way to buy heat shrink. The assortment packs offer 158 2-1/2" long pieces of heat shrink in six diameter sizes: 1/16" (60 pieces), 1/8" (40 pieces), 3/16" (20 pieces), 1/4" (18 pieces), 3/8" (10 pieces), and 1/2" (10 pieces). NTE heat shrink is resistant to common fluids and solvents, flame retardant, and meets UL standards. Shrink temperature is 194°F/90°C with an operating temperature range of -67°F/-55°C to 275°F/135°C. UL listed.

Part #	Description	Price (1-3)	Price (4-UP)
080-722	Black 158 pcs.	\$10.00	\$8.95
080-724	Red 158 pcs.	10.00	8.95

NTE 2-to-1 Assorted Black Heat Shrink Pack

- 2:1 shrink ratio
- Resistant to common fluids and solvents
- Flame retardant
- Seals and protects
- UL listed




The NTE assorted black heat shrink pack offer installers and DIY enthusiasts a simple and convenient way to buy heat shrink. Offers 28 4" long pieces of heat shrink in seven sizes (1/16, 3/32, 1/8, 3/16, 1/4, 3/8, and 1/2). The shrink temperature is 194°F/90°C with an operating temperature range of -67°F/-55°C to 275°F/135°C. UL listed.

#080-726 \$2.98 (1-3) \$2.75 (4-UP)

Split Loom Tubing

Helps dress up any custom installation. Split loom design allows entry and exit of wire at any location. Please order in multiples of 10 ft. Made in Canada.



Part #	Description	Price (10-40 Ft.)	Price (50 Ft.-UP)
080-523	1/4" black	.18	.12
080-525	1/2" black	.22	.16
080-526	3/4" black	.34	.26
080-527	1" black	.39	.35

Speaker Cable Pants

These cable pants are ideal when building your own speaker cables. They keep the conductors separated when terminating and connecting to your components. These black pants will add a professional look and provide the finishing touch to your custom cables. Black color. Sold in packs of 10.



Part #	# Cond.	A	Dimensions B	C	Price (1-3)	Price (4-UP)
082-772	2	6 mm	3.5 mm	98 mm	\$5.78	\$4.73
082-774	2	7 mm	3.5 mm	98 mm	5.78	4.73
082-776	2	8 mm	3.5 mm	108 mm	5.50	4.50
082-778	2	9 mm	4 mm	78 mm	5.50	4.50
082-780	2	10 mm	4 mm	98 mm	5.50	4.50
082-782	2	11 mm	4.8 mm	90 mm	5.50	4.50
082-784	2	14 mm	4.8 mm	98 mm	5.50	4.50
082-786	4	8 mm	3 mm	160 mm	8.50	7.50
082-788	4	9.5 mm	4 mm	160 mm	8.50	7.50
082-790	4	11 mm	4 mm	145 mm	8.92	7.87

Monster® XLN Speaker Cable Pants

The finishing touch to your cable connection. Duraflex® Jacket for maximum flexibility and easy installation. Holds conductors in place for easy terminations. Available in 2 channel and 4 channel.



#185-212 \$2.00 EACH MONSTER®

Clean Cut™ Fray Resistant Sleeving

- Dense braid structure provides fuller coverage
- Fray resistant when cut with scissors
- Cut & abrasion resistant
- Chemically inert
- UV resistant
- Easy to install
- Maintains properties across wide temperature range



By manipulating the mechanical specifications of Polyethylene Terephthalate filaments, the engineers at Techflex have produced a product with the same characteristics as the Flexo Pet with the added advantage of being able to cut with ordinary scissors and yet maintain a fray-resistant end. Flexo Clean Cut™ fray-resistant properties allows frequent expansion at the cut end without unraveling. Clean Cut™ is ideal for field installers and other situations where access to a hot knife is not possible. The black expandable sleeve is designed for quick and easy bundling of wires and cables. It not only provides a professional look to wire bundles but also protects from abrasion and cuts. Clean Cut™ can withstand temperature extremes from -103° F to 255° F.

Part #	Nominal Diameter	Length	Price (1-3)	Price (4-UP)
082-440	1/2"	25 ft.	\$12.67	\$11.29
082-430	1/2"	100 ft.	48.98	43.64
082-442	3/4"	25 ft.	15.59	13.89
082-432	3/4"	75 ft.	46.94	41.82
082-444	1"	25 ft.	17.27	15.38
082-434	1"	50 ft.	37.76	33.64
082-446	1-1/4"	25 ft.	20.39	18.16
082-436	1-1/4"	50 ft.	44.90	40.22
082-448	1-1/2"	25 ft.	25.31	22.55
082-438	1-1/2"	50 ft.	54.08	48.18

Chrome XC Mylar Sleeving



- UV resistant
- Lightweight and flexible
- Cuts easily with hot knife
- Chemically inert
- High abrasion resistance
- Operating temperature: -103°F to 302°F



Flexo Chrome XC is so much more than just a hot looking wire and hose covering. Engineered by braiding heavy gauge 5 mil metallized polyester film (Mylar) in combination with our clear polyethylene terephthalate (PET), Techflex has produced a tough, durable and attractive solution for a wide range of applications. Chrome XC provides a tighter weave design that eliminates transparent elements; the result is a continuous, smooth, metallic shine perfect for any application.

Part #	Nominal Diameter	Length	Price (1-3)	Price (4-UP)
082-472	5/16"	25 ft.	\$12.82	\$11.42
082-466	1/2"	25 ft.	19.50	18.25
082-468	3/4"	25 ft.	26.82	24.65
082-470	1-1/2"	25 ft.	42.16	37.56

Mylar Braided Sleeving



- Adds "Chrome" look to wires and hoses
- Provides electrical shielding to wire bundles
- Easy to install, lightweight and flexible
- Operating temperature up to 255°F



Flexo Chrome is so much more than just a hot looking wire and hose covering. This strong and attractive product is practical in both electronic and decorative applications. Braiding must be cut with a hot knife to prevent unraveling. Sold in 25 ft. lengths.

Part #	Size I.D.	Size Range (Min-Max)	Price (1-3)	Price (4-UP)
082-424	1/4"	1/8"-7/16"	\$12.00	\$10.80
082-426	3/8"	3/16"-5/8"	13.51	12.16
082-428	1/2"	1/4"-3/4"	15.18	13.66

Deluxe 30 Watt Hot Knife



This deluxe 30 watt hot knife is perfect for cutting nylon sleeve braiding without the worry of fraying. Can also be used for wood burning and other hobby projects. It features a sharp brass knife tip that easily cuts through nylon. The long-life heating element provides fast warm-up and years of trouble free use. Also features a comfortable cushion grip, blue plastic handle and a 4 ft. power cord. UL approved, 120 VAC. Replacement tip #370-362.



#370-360 \$9.68 (1-3) \$8.97 (4-UP)