

Mylar Tweeter with Acoustic Lens

- Available shielded or non-shielded
- Ferrofluid cooled

Specifications: • Power handling: 30 watts RMS/45 watts max • VC_{DIA}: 1/2" • Fs: 2,600 Hz • SPL: 90 dB 1W/1m • Dimensions: A: 2-3/8" x 2-3/8", B: 1-15/16", C: 7/8".

#270-170 (4 ohm GT302) **\$2.60** (1-3) **\$2.40** (4-UP)
#270-175 (8 ohm GT302/S) **\$2.85** (1-3) **\$2.40** (4-UP)



4" Cone Tweeter

This tweeter blends well with the cone midrange #280-012. It features a hard paper cone, treated paper surround, and black aluminum dust cap. Flat high frequency response to 20,000 Hz.

Specifications: • Power handling: 35 watts RMS/50 watts max • Impedance: 8 ohms • Fs: 1,500 Hz • Frequency response: 3,000-20,000 Hz • SPL: 90 dB 1W/1m • Dimensions: A: 4", B: 3", C: 1-1/16" • Mfg. #GT-25.

#270-018 **\$5.26** (1-3) **\$4.72** (4-UP)



5" Cone Midrange

Great general-purpose 5" sealed back midrange driver. Features a paper cone, treated paper surround, and black aluminum dust cap. Offers a smooth and extended response, and mates well with cone tweeter #270-018.

Specifications: • Power handling: 35 watts RMS/50 watts max • Impedance: 8 ohms • Fs: 800 Hz • Frequency response: 1,500-10,000 Hz • SPL: 90 dB 1W/1m • Dimensions: A: 5-1/8", B: 4-1/16", C: 1-5/8" • Mfg. #GM-35.

#280-012 **\$5.79** (1-3) **\$4.95** (4-UP)



4" Rubber Surround Shielded Woofer

Specifications: • Power handling: 40 watts RMS/70 watts max • VC_{DIA}: 1" • L_e: .23 mH • Impedance: 8 ohms • Re: 7.1 ohms • Frequency range: 80-6,000 Hz • Fs: 83 Hz • SPL: 84 dB 2.83V/1m • V_{AS}: .07 cu. ft. • X_{MAX}: 1.5 mm • Q_{MS}: 2.40 • Q_{ES}: .97 • Q_{TS}: .69 • Dimensions: A: 4-3/8", B: 3-3/4", C: 2-3/4" • Mfg. #GW-4028/S.

#290-373 **\$10.37** (1-3) **\$9.76** (4-UP)



5-1/4" Rubber Surround Shielded Woofer

Specifications: • Power handling: 70 watts RMS/100 watts max • VC_{DIA}: 1" • L_e: .25 mH • Impedance: 8 ohms • Re: 7.0 ohms • Frequency range: 80-4,000 Hz • Fs: 80 Hz • SPL: 85 dB 2.83V/1m • V_{AS}: .15 cu. ft. • X_{MAX}: 2.0 mm • Q_{MS}: 3.90 • Q_{ES}: 1.17 • Q_{TS}: .90 • Dimensions: A: 5-3/8", B: 4-1/2", C: 2-3/4" • Mfg. #GW-5028/S.

#290-377 **\$13.34** (1-3) **\$12.55** (4-UP)



5" Sealed Back Midrange

Sealed back midrange eliminates need for a separate midrange enclosure. Features treated paper cone, paper surround, and steel mesh grill. Available in 4 and 8 ohm impedance.

Specifications: • Power handling: 40 watts RMS/55 watts max • VC_{DIA}: 1" • Frequency response: 800-8,000 Hz • Fs: 470 Hz • SPL: 89 dB 1W/1m • Dimensions: A: 5-1/8", B: 4-1/8", C: 2-1/2".

#280-100 (4 ohm GM-65/4) **\$7.24** (1-3) **\$6.29** (4-UP)
#280-105 (8 ohm GM-65/8) **\$7.24** (1-3) **\$6.29** (4-UP)



5" Sealed Back Midrange

Sealed back midrange eliminates need for a separate midrange enclosure. Features poly-mica cone, treated foam surround, and aluminum voice coil for higher power handling. Available in 4 and 8 ohm varieties.

Specifications: • Power handling: 40 watts RMS/55 watts max • VC_{DIA}: 1" • Frequency response: 800-8,000 Hz • Fs: 470 Hz • SPL: 89 dB 1W/1m • Dimensions: A: 5-1/8", B: 4-1/8", C: 2-1/2".

#280-110 (4 ohm GM-85/4) **\$9.33** (1-3) **\$8.37** (4-UP)
#280-115 (8 ohm GM-85/8) **\$9.33** (1-3) **\$8.37** (4-UP)




Goldwood Sound has been a key player in the U.S. speaker industry for many years. Their expertise in importing speaker components allows them to find great overseas products and bring them to the U.S. at very affordable prices. There are many "hidden gems" in the Goldwood line that can fit many unique price and performance criterion.

1" Titanium Dome Tweeters




#270-150



#270-160



#270-155



#270-165

Choose the faceplate design that best suits your application. All of these tweeters feature a 1" pure titanium dome with a phase shield to provide a controlled high frequency roll off.

Specifications: • Power handling: 45 watts RMS/65 watts max • VC_{DIA}: 1" • Impedance: 8 ohms • Re: 6.8 ohms • Frequency response: 3,500-20,000 Hz • Fs: 1,500 Hz • SPL: 90 dB 1W/1m

Part #	Faceplate Dimensions	Cutout Dimensions	Price (1-3)	Price (4-UP)
270-150	3-3/4" x 3-3/4"	3-1/8"	\$9.17	\$8.39
270-155	3-7/8" round	3-1/8"	9.85	9.00
270-160	4-1/2" x 3-1/2"	3-1/8"	9.44	8.59
270-165	5-1/2" x 3-1/2"	3-1/8"	9.90	9.13

1" Soft Dome Tweeters

- Silk dome
- High power handling

Specifications: • Power handling: 50 watts RMS/100 watts max • VC_{DIA}: 1" • Impedance: 8 ohms • Fs: 1,300 Hz • Frequency response: 3,000-20,000 Hz • SPL: 90 dB 1W/1m • Dimensions: A: 4", B: 2-7/8", C: 1-1/4" GT510, 1-3/4" GT510/S.



#270-176



#270-178

#270-176 (GT510) **\$10.48** (1-3) **\$9.30** (4-UP)
#270-178 (GT510/S Shielded) **\$11.00** (1-3) **\$10.25** (4-UP)

1" Soft Dome Tweeter

- Silk dome
- High power handling
- Efficient horn loaded design

Specifications: • Power handling: 50 watts RMS/100 watts max • VC_{DIA}: 1" • Impedance: 8 ohms • Fs: 1,000 Hz • Frequency response: 2,000-20,000 Hz • SPL: 92 dB 1W/1m • Dimensions: A: 4", B: 2-7/8", C: 1-1/8" Mfg. #GT-525.



#270-182 **\$11.00** (1-3) **\$10.25** (4-UP)

1" Soft Dome Horn Tweeter

- Silk dome
- High power handling
- Efficient horn loaded design

Specifications: • Power handling: 50 watts RMS/100 watts max • VC_{DIA}: 1" • Impedance: 8 ohms • Fs: 1,000 Hz • Frequency response: 2,000-20,000 Hz • SPL: 92 dB 1W/1m • Dimensions: A: 4-1/2", B: 3-1/4", C: 2" Mfg. #GT-520.



#270-180 **\$11.00** (1-3) **\$10.25** (4-UP)