

W3-1053SC 3" Full Range Driver

Made by Tang Band but available exclusively from Parts Express! The W3-1053SC has an attractive pincushion style frame, edge-damped paper cone, flat spider, and rubber surround. Underhung 7/8" voice coil provides linear travel and wide range. Extremely smooth, extended frequency response.



Specifications: • Power handling: 15 watts RMS/30 watts max • VCDIA: 7/8" • Le: 0.44 mH • Impedance: 8 ohms • Re: 5.98 ohms • Frequency range: 100-18,000 Hz • Fs: 100 Hz • SPL: 85 dB 1W/1m • VAS: 0.04 cu. ft. • QMS: 4.77 • QES: 0.72 • QTS: 0.62 • XMAX: 1.5 mm • Dimensions: A: 3-3/16"; 3-13/16" diagonally, B: 3", C: 2".

#264-880 \$24.99 LIST **\$11.60** (1-3) **\$9.67** (4-UP)

W3-315E 3" Driver

3" driver with an aluminum/magnesium cone, rubber surround, and cast aluminum frame. The rigid cone offers a very clean and clear midrange with a strong midbass.



Specifications: • Power handling: 10 watts RMS/20 watts max • VCDIA: 3/4" • Impedance: 8 ohms • Re: 6.6 ohms • Frequency range: 100-20,000 Hz • Fs: 100 Hz • SPL: 85 dB 1W/1m • VAS: .06 cu. ft. • QMS: 5.51 • QES: .57 • QTS: .52 • XMAX: 1 mm • Dimensions: A: 3-5/8", B: 3", C: 1-5/8".

#264-811 \$26.99 LIST **\$23.72** (1-3) **\$21.57** (4-UP)

W3-1335SB 3" Titanium Driver

One of the few drivers to use a true titanium cone, the W3-1335S offers excellent linearity and detail throughout the critical midbass and midrange regions.



Specifications: • Power handling: 12 watts RMS/25 watts max • VCDIA: 1" • Impedance: 8 ohms • Re: 6.6 ohms • Frequency range: 110-20,000 Hz • Fs: 110 Hz • SPL: 86 dB 1W/1m • VAS: .04 cu. ft. • QMS: 1.31 • QES: .46 • QTS: .34 • XMAX: .5 mm • Dimensions: A: 3-5/8", B: 3", C: 2".

#264-842 \$49.99 LIST **\$39.92** (1-3) **\$36.29** (4-UP)

W3-1364S 3" Bamboo Driver

A blend of paper and Bamboo fibers provides a perfect combination of light weight and self-dampening. Neodymium motors with copper rings reduce distortion even further.



Specifications: • Power handling: 12 watts RMS/25 watts max • VCDIA: 3/4" • Impedance: 8 ohms • Re: 6.6 ohms • Frequency range: 105-20,000 Hz • Fs: 105 Hz • SPL: 86 dB 1W/1m • VAS: .07 cu. ft. • QMS: 2.48 • QES: .77 • QTS: .59 • XMAX: .5 mm • Dimensions: A: 3-5/8", B: 3", C: 2".

#264-844 (3" - W3-1364SA) \$34.99 LIST **\$26.49** (1-3) **\$24.37** (4-UP)

W3-1797S 3" Aluminum Cone Driver 4 Ohm

The W3-1797S features a self-shielding neodymium magnet system, flat aluminum sandwich cone, integrated protective screen, and extremely low second and third order distortion.

NEW



Specifications: • Power handling: 25 watts RMS/50 watts max • VCDIA: 1-1/4" • Impedance: 4 ohms • Re: 3.6 ohms • Frequency range: 90-20,000 Hz • Fs: 90 Hz • SPL: 85 dB 1W/1m • VAS: 0.04 cu. ft. • QMS: 1.66 • QES: 0.36 • QTS: 0.29 • XMAX: 1 mm • Dimensions: A: 3.66", B: 2.9", C: 1.93".

#264-888 \$67.99 LIST **\$57.42** (1-3) **\$52.20** (4-UP)

W4-1757SB 4" Aluminum Cone Driver 6 Ohm

Aluminum honeycomb sandwich cone, durable foam half-roll surround, shielded neodymium magnet, and extremely wide off-axis frequency response.

NEW



Specifications: Power handling: 30 watts RMS/60 watts max • VCDIA: 1-1/2" • Impedance: 6 ohms • Re: 5.6 ohms • Frequency range: 75-20,000 Hz • Fs: 75 Hz • SPL: 86 dB 1W/1m • VAS: 0.05 cu. ft. • QMS: 1.55 • QES: 0.65 • QTS: 0.46 • XMAX: 3 mm • Dimensions: A: 4.25", B: 3.76", C: 1.75".

#264-881 \$77.99 LIST **\$61.79** (1-3) **\$55.58** (4-UP)

W2-1767S 2" Neodymium Woofer

NEW



Intended for micro-compact bass applications, the high power handling W2-1767S features a paper cone with Santoprene surround, aluminum dust cap, and neodymium magnet. The very long-throw design (3 mm XMAX) complements the driver's smooth response extending to 10 kHz.

Specifications: • Power handling: 20 watts RMS/30 watts max • VCDIA: 1" • Impedance: 8 ohms • Re: 6.6 ohms • Frequency range: 110-10,000 Hz • Fs: 110 Hz • SPL: 80 dB 1W/1m • VAS: 0.008 cu. ft. • QMS: 2.85 • QES: 0.41 • QTS: 0.36 • XMAX: 3 mm • Dimensions: A: 2.25", B: 2", C: 1.5".

#264-884 \$29.99 LIST **\$24.75** (1-3) **\$22.50** (4-UP)

W3-881SJ and W4-656SC 3" and 4" Shielded Drivers

The heart of these drivers is a textured PPM cone, which combined with a rubber surround gives them great versatility. The 3" version utilizes an underhung neodymium motor, while the 4" uses a more traditional shielded ceramic motor.



W3-881SJ Specifications: • Power handling: 15 watts RMS/30 watts max • VCDIA: 3/4" • Impedance: 8 ohms • Re: 6.6 ohms • Frequency range: 100-20,000 Hz • Fs: 100 Hz • SPL: 86 dB 1W/1m • VAS: .08 cu. ft. • QMS: 3.07 • QES: .80 • QTS: .63 • XMAX .5 mm • Dimensions: A: 3-5/8", B: 3", C: 1-7/8".

W4-656SC Specifications: • Power handling: 25 watts RMS/50 watts max • VCDIA: 1" • Impedance: 8 ohms • Re: 6.0 ohms • Frequency range: 65-12,000 Hz • Fs: 65 Hz • SPL: 88 dB 1W/1m • VAS: .18 cu. ft. • QMS: 2.39 • QES: .39 • QTS: .33 • XMAX 3 mm • Dimensions: A: 4-15/16", B: 3-3/4", C: 3-3/16".

#264-812 (3" - W3-881SJ) \$22.99 LIST **\$18.35** (1-3) **\$16.69** (4-UP)

#264-820 (4" - W4-656SC) \$33.99 LIST **\$26.85** (1-3) **\$24.41** (4-UP)

W4-1337SA 4" Titanium Cone Driver

This high-quality full range 4" driver utilizes a titanium cone, solid aluminum phase plug, santoprene rubber surround, underhung coil, and large shielded motor structure. Great for home theater or hi-fi midbass applications.



Specifications: • Power handling: 25 watts RMS/50 watts max • VCDIA: 1" • Impedance: 8 ohms • Re: 6.8 ohms • Frequency range: 70-20,000 Hz • Fs: 70 Hz • SPL: 87 dB 1W/1m • VAS: .17 cu. ft. • QMS: 1.51 • QES: .49 • QTS: .37 • XMAX: 3 mm • Dimensions: A: 4-15/16", B: 3-3/4", C: 2-7/8".

#264-848 \$61.99 LIST **\$54.64** (1-3) **\$52.11** (4-UP)

W4-1052SD 4" Driver 4 Ohm

A neodymium-powered 4" driver, this unit offers great bass extension and a smooth frequency response.



Specifications: • Power handling: 20 watts RMS/40 watts max • VCDIA: 1" • Impedance: 4 ohms • Re: 3.80 ohms • Frequency range: 60-15,000 Hz • Fs: 63 Hz • SPL: 87 dB 1W/1m • VAS: .26 cu. ft. • QMS: 4.52 • QES: .49 • QTS: .44 • XMAX: 3.4 mm • Dimensions: A: 4-9/16", B: 3-3/4", C: 2-1/4".

#264-828 \$34.99 LIST **\$27.53** (1-3) **\$25.03** (4-UP)

W5-704D 5-1/4" Woofer

This high-quality poly cone woofer has several unique features including a twin-roll rubber surround, durable aramid spider, and cast aluminum frame. Great for compact vented two-way designs.



Specifications: • Power handling: 25 watts RMS/50 watts max • VCDIA: 1" • Impedance: 8 ohms • Re: 6.0 ohms • Frequency range: 55-13,000 Hz • Fs: 55 Hz • SPL: 88 dB 2.83V/1m • VAS: .45 cu. ft. • QMS: 1.93 • QES: .46 • QTS: .37 • XMAX: 3 mm • Dimensions: A: 6-3/16", B: 4-7/8", C: 2-3/4".

#264-850 \$30.99 LIST **\$24.70** (1-3) **\$22.45** (4-UP)