

DMN-A 2" Soft Dome Midrange

Compact design soft dome midrange with hand treated fabric dome and 2" voice coil. This coil is powered by a neodymium motor and is damped via a large non-resonant rear chamber that lowers the resonance frequency and improves low-end output. Overall a very relaxed sounding dome midrange that is one of the few that can be used near CRTs.



Specifications: • Power handling: 60 watts RMS/120 watts max • VC_{DIA}: 2" • Le: .127 mH • Impedance: 5 ohms • Re: 4.6 ohms • Frequency range: 700-10,000 Hz • Fs: 350 Hz • SPL: 91 dB 1W/1m • X_{MAX}: .35 mm • Dimensions: A: 4-9/16", B: 3-1/2", C: 5".

#297-415 \$89.00 LIST **\$35.77** (1-3) **\$35.00** (4-UP)

SP10 Subwoofer

- 10" flat cone
- 15.5 mm X_{MAX}
- A true heavyweight at 28 lbs.
- Aluminum cast frame
- Full-roll neoprene surround
- Great car audio subwoofer

The SP10 is one of the most massive 10" subwoofers available today. Weighing in at over 28 lbs., it is a true heavyweight. The SP10 has been optimized for accurate low frequency reproduction in a small sealed enclosure of only .8 cu. ft. producing an f3 around 45 Hz. So, if you dare, jump into the ring with a true heavyweight.



Specifications: • Power handling: 500 watts RMS/700 watts max • VC_{DIA}: 3" • Le: 1.35 mH • Impedance: 4 ohms • Re: 3.4 ohms • Frequency range: 35-150 Hz • Fs: 34 Hz • SPL: 84 dB 2.83V/1m • V_{AS}: .60 cu. ft. • Q_{MS}: 4.83 • Q_{ES}: .65 • Q_{TS}: .57 • X_{MAX}: 15.5 mm • Dimensions: A: 10-1/4", B: 9-1/4", C: 5-11/16".

#297-460 \$187.20 LIST **\$182.80** (1-3) **\$173.45** (4-UP)



TN25 1" Fabric Dome Tweeter

• Hand treated 1" fabric dome • Large non-resonant rear acoustic chamber • Ferrofluid cooled voice coil for higher power handling • Self-shielding neodymium magnet • Small faceplate allows for closer placement to bass/midrange driver for improved imaging.



Specifications: • Power handling: 20 watts RMS/40 watts max • VC_{DIA}: 1" • Impedance: 5 ohms • Re: 4.6 ohms • Frequency range: 2,500-22,000 Hz • Fs: 1,500 Hz • SPL: 89 dB 1W/1m • Dimensions: A: 2-1/8" x 2-1/8", B: 1-11/16", C: 2-1/2".

#297-408 \$19.00 LIST **\$8.91** (1-3) **\$8.72** (4-UP)

TN28 1-1/8" Fabric Dome Tweeter

The versatile design of this tweeter minimizes diffraction while allowing front, rear, or side mounting. The ferrofluid-immersed 28 mm voice coil and flexible leads provide good power handling and stable excursion. The hand-treated fabric dome provides a very smooth frequency response while the neodymium motor and large non-resonant rear chamber provide superior low-treble performance.



Specifications: • Power handling: 40 watts RMS/100 watts max • VC_{DIA}: 1-1/8" • Impedance: 6 ohms • Re: 5.1 ohms • Frequency range: 2,000-20,000 Hz • Fs: 1,600 Hz • SPL: 88 dB 2.83V/1m • Dimensions: 1-7/8" dia. x 3-1/4" L.

#297-409 \$39.00 LIST **\$17.24** (1-3) **\$16.87** (4-UP)

HiVi "B" Series Drivers


HiVi B Series drivers are capable of covering a wide portion of the audio spectrum, and the magnetically shielded design allows them to be used in center channel and other multimedia applications.

- Bronze/aluminum alloy cone
- Cosmetic frame
- Shielded motor structure



B1S 1" Aluminum Shielded Mid/Tweeter

Specifications: • Power handling: 3 watts RMS/6 watts max • VC_{DIA}: 3/4" • Impedance: 8 ohms • Re: 6.5 ohms • Frequency range: 1,000-20,000 • Fs: 180 Hz • SPL: 79 dB 1W/1m • V_{AS}: .001 cu. ft. • Q_{MS}: 3.22 • Q_{ES}: .65 • Q_{TS}: .54 • X_{MAX}: .95 mm • Dimensions: A: 1-7/16", B: 1-3/8", C: 5/8".



#297-411 \$6.50 LIST **\$4.98** (1-3) **\$4.89** (4-UP)

B2S 2" Aluminum Shielded Mid/Bass

Specifications: • Power handling: 10 watts RMS/20 watts max • VC_{DIA}: 1" • Impedance: 8 ohms • Re: 6.5 ohms • Frequency response: 300-20,000 Hz • Fs: 152 Hz • SPL: 78 dB 1W/1m • V_{AS}: .007 cu. ft. • Q_{MS}: 5.69 • Q_{ES}: 1.53 • Q_{TS}: 1.20 • X_{MAX}: 1.5 mm • Dimensions: A: 2-1/8", B: 1-7/8", C: 1-1/4".



#297-432 \$14.99 LIST **\$11.63** (1-3) **\$11.37** (4-UP)

B3S 3" Aluminum Shielded Mid/Bass

Specifications: • Power handling: 15 watts RMS/30 watts max • VC_{DIA}: 3/4" • Impedance: 8 ohms • Re: 6.5 ohms • Frequency range: 100-15,000 • Fs: 80 Hz • SPL: 81 dB 1W/1m • V_{AS}: .06 cu. ft. • Q_{MS}: 4.29 • Q_{ES}: 1.19 • Q_{TS}: .93 • X_{MAX}: 3 mm • Dimensions: A: 3", B: 2-3/4", C: 2-1/8".



#297-427 \$19.99 LIST **\$11.87** (1-3) **\$11.61** (4-UP)

B3N 3" Aluminum Shielded Mid/Bass

Specifications: • Power handling: 15 watts RMS/30 watts max • VC_{DIA}: 3/4" • Impedance: 8 ohms • Re: 6.5 ohms • Frequency range: 100-15,000 • Fs: 77 Hz • SPL: 81 dB 1W/1m • V_{AS}: .06 cu. ft. • Q_{MS}: 4.48 • Q_{ES}: 1.07 • Q_{TS}: .86 • X_{MAX}: 3 mm • Dimensions: A: 3-1/2", B: 2-7/8", C: 2-1/8".



#297-428 \$19.99 LIST **\$11.21** (1-3) **\$11.06** (4-UP)

B4N 4" Aluminum Shielded Mid/Bass

Specifications: • Power handling: 25 watts RMS/50 watts max • VC_{DIA}: 1" • Impedance: 8 ohms • Re: 6.5 ohms • Frequency range: 50-10,000 • Fs: 56 Hz • SPL: 85 dB 1W/1m • V_{AS}: .16 cu. ft. • Q_{MS}: 3.91 • Q_{ES}: .63 • Q_{TS}: .52 • X_{MAX}: 3.2 mm • Dimensions: A: 4-5/8", B: 3-5/8", C: 2-3/4".



#297-429 \$24.99 LIST **\$17.20** (1-3) **\$16.83** (4-UP)