

# Pro Audio

## Speakers, Drivers & Horns

### Eminence Delta Pro Series

- Ferrite magnet
- Die-cast aluminum basket
- Paper cone, cloth cone edge
- Solid composition paper dust cap



**NEW**

#### Delta Pro-8 225W Midranges

- Mid/bass driver for pro audio or MI applications.
- Truncated cast aluminum heatsink-style basket is great for stacking in a line array.

**Specifications:** • Power handling: 225 watts RMS • VC<sub>DIA</sub>: 2" • Le: 0.82/0.90 mH • Impedance: 8/16 ohms • Re: 5.6/10.5 ohms • Frequency range: 100-3,000/100-5,000 Hz • Magnet weight: 59 oz. • Fs: 69/71.4 Hz • SPL: 97.8/99 dB 1W/1m • V<sub>AS</sub>: 0.65/0.65 cu. ft. • Q<sub>MS</sub>: 6.43/7.47 • Q<sub>ES</sub>: 0.20/0.27 • Q<sub>TS</sub>: 0.22/0.27 X<sub>MAX</sub>: 3 mm • Dimensions: A: 8.02", B: 7.36", C: 3.75".

**#290-507** (8A – 8 ohm) ..... \$9.99 LIST **\$84.97** EACH  
**#290-508** (8B – 16 ohm) ..... \$9.99 LIST **\$84.97** EACH

#### Delta Pro-12A 400W Driver

Recommended for professional audio in both sealed and vented enclosures. Ideal for full-range, mid/hi, and monitor wedges.

**Specifications:** • Power handling: 400 watts RMS • VC<sub>DIA</sub>: 2.5" • Le: 0.84 mH • Impedance: 8 ohms • Re: 5.71 ohms • Frequency range: 52-4,500 Hz • Magnet weight: 80 oz. • Fs: 51 Hz • SPL: 99.2 dB 1W/1m • V<sub>AS</sub>: 2.9 cu. ft. • Q<sub>MS</sub>: 7.56 • Q<sub>ES</sub>: 0.37 • Q<sub>TS</sub>: 0.35 • X<sub>MAX</sub>: 4.6 mm • Dimensions: A: 12.38", B: 11.07", C: 6.22".

**#290-510** ..... \$114.99 LIST **\$109.97** EACH

#### Delta Pro-15A 400W Driver

Recommended for professional audio in both sealed and vented enclosures. Ideal for full-range, mid/hi, and monitor wedges.

**Specifications:** • Power handling: 400 watts RMS • VC<sub>DIA</sub>: 2.5" • Le: 0.83 mH • Impedance: 8 ohms • Re: 5.71 ohms • Frequency range: 54-4,200 Hz • Magnet weight: 80 oz. • Fs: 42 Hz • SPL: 101.6 dB 1W/1m • V<sub>AS</sub>: 8.6 cu. ft. • Q<sub>MS</sub>: 4.73 • Q<sub>ES</sub>: 0.44 • Q<sub>TS</sub>: 0.40 • X<sub>MAX</sub>: 4.3 mm • Dimensions: A: 15.32", B: 14", C: 6.06".

**#290-512** ..... \$124.99 LIST **\$119.97** EACH

#### Delta Pro-18 500W Drivers

Long throw subwoofer for small vented cabinets. Oversized top plate and large pole piece vent help keep the voice coil cool. Recommended enclosure size: 3.0-10.0 cu. ft.

**Specifications:** • Power handling: 500 watts RMS • VC<sub>DIA</sub>: 2.5" • Le: 3.43/2.65 mH • Impedance: 8 or 4 ohms • Re: 5.3/3.8 ohms • Frequency range: 37-250/35-200 Hz • Magnet weight: 67 oz. • Fs: 28/27.23 Hz • SPL: 96/94.4 dB 1W/1m • V<sub>AS</sub>: 17.41/17.26 cu. ft. • Q<sub>MS</sub>: 10.38/13.24 • Q<sub>ES</sub>: 0.33/0.32 • Q<sub>TS</sub>: 0.32/0.32 X<sub>MAX</sub>: 6.7 mm • Dimensions: A: 18", B: 16.57", C: 8.13".

**#290-520** (18A – 8 ohm) ..... \$149.99 LIST **\$139.97** EACH  
**#290-521** (18C – 4 ohm) ..... \$149.99 LIST **\$139.97** EACH



**NEW**

### Eminence Gamma Series

- Ferrite magnet
- Pressed steel basket
- Paper cone, cloth cone edge
- For all high power bass applications including bass guitar

#### Gamma-15A-2 300W Driver

Recommended for vented professional audio enclosures as a mid/hi or full-range and monitor; also for bass guitar.

**Specifications:** • Power handling: 300 watts RMS • VC<sub>DIA</sub>: 2" • Le: 1.73 mH • Impedance: 8 ohms • Re: 5.98 ohms • Frequency range: 48-3,300 Hz • Magnet weight: 59 oz. • Fs: 33 Hz • SPL: 98.6 dB 1W/1m • V<sub>AS</sub>: 11.1 cu. ft. • Q<sub>MS</sub>: 5.13 • Q<sub>ES</sub>: 0.32 • Q<sub>TS</sub>: 0.30 • X<sub>MAX</sub>: 3.0 mm • Dimensions: A: 15.15", B: 13.77", C: 5.94".

**#290-454** ..... \$84.99 LIST **\$79.97** EACH



### Eminence Alpha Series

- Ferrite magnet
- Pressed steel basket
- Paper cone, cloth cone edge
- Solid composition paper dust cap



#### Alpha-6 100W Midranges

Recommended for professional audio midrange applications in a sealed cabinet, or as a mid-bass in a vented satellite enclosure. The Alpha-6C boasts a 4-ohm impedance, increased body weight, and stiffer, more aggressive water proofing treatment on the cone making it ideal for car audio use.

**Specifications:** • Power handling: 100 watts RMS • VC<sub>DIA</sub>: 1.5" • Le: 0.19/0.28 mH • Impedance: 8/4 ohms • Re: 7.2/3.2 ohms • Frequency range: 85-6,000/107-6,000 Hz • Magnet weight: 20 oz. • Fs: 118/107 Hz • SPL: 93.6 dB 1W/1m • V<sub>AS</sub>: 0.2 cu. ft. • Q<sub>MS</sub>: 5.68/6.12 • Q<sub>ES</sub>: 0.60/0.49 • Q<sub>TS</sub>: 0.54/0.45 • Dimensions: A: 6.59", B: 5.69", C: 2.8".

**#290-400** (6A – 8 ohm) ..... \$44.99 LIST **\$39.97** EACH  
**#290-399** (6C – 4 ohm) ..... \$44.99 LIST **\$39.97** EACH

#### Alpha-8A 125W Midrange

Ideal for small P.A. systems, keyboards and guitar combos.

**Specifications:** • Power handling: 125 watts RMS • VC<sub>DIA</sub>: 1.5" • Le: 0.44 mH • Impedance: 8 ohms • Re: 5.3 ohms • Frequency range: 58-5,000 Hz • Magnet weight: 20 oz. • Fs: 73 Hz • SPL: 94 dB 1W/1m • V<sub>AS</sub>: 0.6 cu. ft. • Q<sub>MS</sub>: 4.60 • Q<sub>ES</sub>: 0.68 • Q<sub>TS</sub>: 0.59 • X<sub>MAX</sub>: 3.2 mm • Dimensions: A: 8.24", B: 7.13", C: 3.58".

**#290-401** ..... \$49.99 LIST **\$44.97** EACH



#### Alpha-8MRA 125W Midrange

Ideal for building into bass enclosures to extend the range or creating an economical 2-way system. The closed back does not need a separate enclosure.

**Specifications:** • Power handling: 125 watts RMS • VC<sub>DIA</sub>: 1.5" • Le: 0.34 mH • Impedance: 8 ohms • Re: 7.32 ohms • Frequency range: 400-4,800 Hz • Magnet weight: 20 oz. • Fs: 514 Hz • SPL: 100.9 dB 1W/1m • V<sub>AS</sub>: 0.03 cu. ft. • Q<sub>MS</sub>: 4.48 • Q<sub>ES</sub>: 2.08 • Q<sub>TS</sub>: 1.42 • Dimensions: A: 8.22", B: 7.19", C: 3.25".

**#290-402** ..... \$49.99 LIST **\$44.97** EACH



#### Alpha-10A 150W Guitar/PA Driver

Ideal for 2-way sound reinforcement systems, keyboard, and guitar combos.

**Specifications:** • Power handling: 150 watts RMS • VC<sub>DIA</sub>: 1.5" • Le: 0.66 mH • Impedance: 8 ohms • Re: 5.31 ohms • Frequency range: 57-4,500 Hz • Magnet weight: 20 oz. • Fs: 50 Hz • SPL: 95.6 dB 1W/1m • V<sub>AS</sub>: 2.9 cu. ft. • Q<sub>MS</sub>: 5.21 • Q<sub>ES</sub>: 0.66 • Q<sub>TS</sub>: 0.59 • X<sub>MAX</sub>: 3.2 mm • Dimensions: A: 10.11", B: 9.13", C: 3.9".

**#290-403** ..... \$49.99 LIST **\$44.97** EACH

#### Alpha-12A 150W Guitar/PA Driver

Ideal for 2-way sound reinforcement systems, keyboard and guitar combos.

**Specifications:** • Power handling: 150 watts RMS • VC<sub>DIA</sub>: 1.5" • Le: 0.79 mH • Impedance: 8 ohms • Re: 6.3 ohms • Frequency range: 51-4,300 Hz • Magnet weight: 20 oz. • Fs: 49 Hz • SPL: 95.6 dB 1W/1m • V<sub>AS</sub>: 4.3 cu. ft. • Q<sub>MS</sub>: 6.53 • Q<sub>ES</sub>: 0.88 • Q<sub>TS</sub>: 0.77 • X<sub>MAX</sub>: 2.4 mm • Dimensions: A: 12.26", B: 11", C: 4.73".

**#290-405** ..... \$59.99 LIST **\$52.97** EACH

#### Alpha-15A 200W Driver

Ideal for 2-way sound reinforcement systems, keyboard, and guitar combos. For all bass applications.

**Specifications:** • Power handling: 200 watts RMS • VC<sub>DIA</sub>: 1.5" • Le: 0.84 mH • Impedance: 8 ohms • Re: 5.88 ohms • Frequency range: 46-3,500 Hz • Magnet weight: 25 oz. • Fs: 41 Hz • SPL: 97 dB 1W/1m • V<sub>AS</sub>: 9.2 cu. ft. • Q<sub>MS</sub>: 7.23 • Q<sub>ES</sub>: 1.53 • Q<sub>TS</sub>: 1.26 • X<sub>MAX</sub>: 3.8 mm • Dimensions: A: 15.15", B: 13.77", C: 5.83".

**#290-407** ..... \$64.99 LIST **\$59.97** EACH

