

Pro Audio

Speakers, Drivers & Horns

Eminence Delta Pro Series

- Ferrite magnet
- Die-cast aluminum basket
- Paper cone, cloth cone edge
- Solid composition paper dust cap



NEW

Delta Pro-8 225W Midranges

- Mid/bass driver for pro audio or MI applications. Truncated cast aluminum heatsink-style basket is great for stacking in a line array.

Specifications: • Power handling: 225 watts RMS • VC_{DIA}: 2" • Le: 0.82/0.90 mH • Impedance: 8/16 ohms • Re: 5.6/10.5 ohms • Frequency range: 100-3,000/100-5,000 Hz • Magnet weight: 59 oz. • Fs: 69/71.4 Hz • SPL: 97.8/99 dB 1W/1m • V_{AS}: 0.65/0.65 cu. ft. • Q_{MS}: 6.43/7.47 • Q_{ES}: 0.20/0.27 • Q_{TS}: 0.22/0.27 X_{MAX}: 3 mm • Dimensions: A: 8.02", B: 7.36", C: 3.75".

#290-507 (8A – 8 ohm) \$89.99 LIST **\$84.97** EACH
#290-508 (8B – 16 ohm) \$89.99 LIST **\$84.97** EACH

Delta Pro-12A 400W Driver

Recommended for professional audio in both sealed and vented enclosures. Ideal for full-range, mid/hi, and monitor wedges.

Specifications: • Power handling: 400 watts RMS • VC_{DIA}: 2.5" • Le: 0.84 mH • Impedance: 8 ohms • Re: 5.71 ohms • Frequency range: 52-4,500 Hz • Magnet weight: 80 oz. • Fs: 51 Hz • SPL: 99.2 dB 1W/1m • V_{AS}: 2.9 cu. ft. • Q_{MS}: 7.56 • Q_{ES}: 0.37 • Q_{TS}: 0.35 • X_{MAX}: 4.6 mm • Dimensions: A: 12.38", B: 11.07", C: 6.22".

#290-510 \$114.99 LIST **\$109.97** EACH



Delta Pro-15A 400W Driver

Recommended for professional audio in both sealed and vented enclosures. Ideal for full-range, mid/hi, and monitor wedges.

Specifications: • Power handling: 400 watts RMS • VC_{DIA}: 2.5" • Le: 0.83 mH • Impedance: 8 ohms • Re: 5.71 ohms • Frequency range: 54-4,200 Hz • Magnet weight: 80 oz. • Fs: 42 Hz • SPL: 101.6 dB 1W/1m • V_{AS}: 8.6 cu. ft. • Q_{MS}: 4.73 • Q_{ES}: 0.44 • Q_{TS}: 0.40 • X_{MAX}: 4.3 mm • Dimensions: A: 15.32", B: 14", C: 6.06".

#290-512 \$124.99 LIST **\$119.97** EACH

Delta Pro-18 500W Drivers

Long throw subwoofer for small vented cabinets. Oversized top plate and large pole piece vent help keep the voice coil cool. Recommended enclosure size: 3.0-10.0 cu. ft.

Specifications: • Power handling: 500 watts RMS • VC_{DIA}: 2.5" • Le: 3.43/2.65 mH • Impedance: 8 or 4 ohms • Re: 5.3/3.8 ohms • Frequency range: 37-250/35-200 Hz • Magnet weight: 67 oz. • Fs: 28/27.23 Hz • SPL: 96/94.4 dB 1W/1m • V_{AS}: 17.41/17.26 cu. ft. • Q_{MS}: 10.38/13.24 • Q_{ES}: 0.33/0.32 • Q_{TS}: 0.32/0.32 X_{MAX}: 6.7 mm • Dimensions: A: 18", B: 16.57", C: 8.13".

#290-520 (18A – 8 ohm) \$149.99 LIST **\$139.97** EACH
#290-521 (18C – 4 ohm) \$149.99 LIST **\$139.97** EACH



NEW

Eminence Gamma Series

- Ferrite magnet
- Pressed steel basket
- Paper cone, cloth cone edge
- For all high power bass applications including bass guitar

Gamma-15A-2 300W Driver

Recommended for vented professional audio enclosures as a mid/hi or full-range and monitor; also for bass guitar.

Specifications: • Power handling: 300 watts RMS • VC_{DIA}: 2" • Le: 1.73 mH • Impedance: 8 ohms • Re: 5.98 ohms • Frequency range: 48-3,300 Hz • Magnet weight: 59 oz. • Fs: 33 Hz • SPL: 98.6 dB 1W/1m • V_{AS}: 11.1 cu. ft. • Q_{MS}: 5.13 • Q_{ES}: 0.32 • Q_{TS}: 0.30 • X_{MAX}: 3.0 mm • Dimensions: A: 15.15", B: 13.77", C: 5.94".

#290-454 \$84.99 LIST **\$79.97** EACH



Eminence Alpha Series

- Ferrite magnet
- Pressed steel basket
- Paper cone, cloth cone edge
- Solid composition paper dust cap



Alpha-6 100W Midranges

Recommended for professional audio midrange applications in a sealed cabinet, or as a mid-bass in a vented satellite enclosure. The Alpha-6C boasts a 4-ohm impedance, increased body weight, and stiffer, more aggressive water proofing treatment on the cone making it ideal for car audio use.

Specifications: • Power handling: 100 watts RMS • VC_{DIA}: 1.5" • Le: 0.19/0.28 mH • Impedance: 8/4 ohms • Re: 7.2/3.2 ohms • Frequency range: 85-6,000/107-6,000 Hz • Magnet weight: 20 oz. • Fs: 118/107 Hz • SPL: 93.6 dB 1W/1m • V_{AS}: 0.2 cu. ft. • Q_{MS}: 5.68/6.12 • Q_{ES}: 0.60/0.49 • Q_{TS}: 0.54/0.45 • Dimensions: A: 6.59", B: 5.69", C: 2.8".

#290-400 (6A – 8 ohm) \$44.99 LIST **\$39.97** EACH
#290-399 (6C – 4 ohm) \$44.99 LIST **\$39.97** EACH

Alpha-8A 125W Midrange

Ideal for small P.A. systems, keyboards and guitar combos.

Specifications: • Power handling: 125 watts RMS • VC_{DIA}: 1.5" • Le: 0.44 mH • Impedance: 8 ohms • Re: 5.3 ohms • Frequency range: 58-5,000 Hz • Magnet weight: 20 oz. • Fs: 73 Hz • SPL: 94 dB 1W/1m • V_{AS}: 0.6 cu. ft. • Q_{MS}: 4.60 • Q_{ES}: 0.68 • Q_{TS}: 0.59 • X_{MAX}: 3.2 mm • Dimensions: A: 8.24", B: 7.13", C: 3.58".

#290-401 \$49.99 LIST **\$44.97** EACH



Alpha-8MRA 125W Midrange

Ideal for building into bass enclosures to extend the range or creating an economical 2-way system. The closed back does not need a separate enclosure.

Specifications: • Power handling: 125 watts RMS • VC_{DIA}: 1.5" • Le: 0.34 mH • Impedance: 8 ohms • Re: 7.32 ohms • Frequency range: 400-4,800 Hz • Magnet weight: 20 oz. • Fs: 514 Hz • SPL: 100.9 dB 1W/1m • V_{AS}: 0.03 cu. ft. • Q_{MS}: 4.48 • Q_{ES}: 2.08 • Q_{TS}: 1.42 • Dimensions: A: 8.22", B: 7.19", C: 3.25".

#290-402 \$49.99 LIST **\$44.97** EACH



Alpha-10A 150W Guitar/PA Driver

Ideal for 2-way sound reinforcement systems, keyboard, and guitar combos.

Specifications: • Power handling: 150 watts RMS • VC_{DIA}: 1.5" • Le: 0.66 mH • Impedance: 8 ohms • Re: 5.31 ohms • Frequency range: 57-4,500 Hz • Magnet weight: 20 oz. • Fs: 50 Hz • SPL: 95.6 dB 1W/1m • V_{AS}: 2.9 cu. ft. • Q_{MS}: 5.21 • Q_{ES}: 0.66 • Q_{TS}: 0.59 • X_{MAX}: 3.2 mm • Dimensions: A: 10.11", B: 9.13", C: 3.9".

#290-403 \$49.99 LIST **\$44.97** EACH

Alpha-12A 150W Guitar/PA Driver

Ideal for 2-way sound reinforcement systems, keyboard and guitar combos.

Specifications: • Power handling: 150 watts RMS • VC_{DIA}: 1.5" • Le: 0.79 mH • Impedance: 8 ohms • Re: 6.3 ohms • Frequency range: 51-4,300 Hz • Magnet weight: 20 oz. • Fs: 49 Hz • SPL: 95.6 dB 1W/1m • V_{AS}: 4.3 cu. ft. • Q_{MS}: 6.53 • Q_{ES}: 0.88 • Q_{TS}: 0.77 • X_{MAX}: 2.4 mm • Dimensions: A: 12.26", B: 11", C: 4.73".

#290-405 \$59.99 LIST **\$52.97** EACH

Alpha-15A 200W Driver

Ideal for 2-way sound reinforcement systems, keyboard, and guitar combos. For all bass applications.

Specifications: • Power handling: 200 watts RMS • VC_{DIA}: 1.5" • Le: 0.84 mH • Impedance: 8 ohms • Re: 5.88 ohms • Frequency range: 46-3,500 Hz • Magnet weight: 25 oz. • Fs: 41 Hz • SPL: 97 dB 1W/1m • V_{AS}: 9.2 cu. ft. • Q_{MS}: 7.23 • Q_{ES}: 1.53 • Q_{TS}: 1.26 • X_{MAX}: 3.8 mm • Dimensions: A: 15.15", B: 13.77", C: 5.83".

#290-407 \$64.99 LIST **\$59.97** EACH

