

Pro Audio

Speakers, Drivers & Horns

Eminence Kappa Series

- Ferrite magnet
- Pressed steel basket
- Paper cone, cloth cone edge
- Solid composition paper dust cap



Kappa-12A 450W Driver

Recommended for professional audio as a mid/hi or full-range in a vented enclosure.

- Specifications:** • Power handling: 450 watts RMS • VC_{DIA}: 3" • Le: 0.77 mH • Impedance: 8 ohms • Re: 5.41 ohms • Frequency range: 62-4,200 Hz • Magnet weight: 80 oz. • Fs: 45 Hz • SPL: 99.3 dB 1W/1m • V_{AS}: 4.0 cu. ft. • Q_{MS}: 7.76 • Q_{ES}: 0.28 • Q_{TS}: 0.27 • X_{MAX}: 3.2 mm • Dimensions: A: 12.26", B: 11", C: 5.63"



#290-456 \$109.99 LIST **\$99.97** EACH

Kappa-15 450W Drivers

Recommended for professional audio in a vented mid-bass or bass enclosure; also suitable for bass guitar.

- Specifications:** • Power handling: 450 watts RMS • VC_{DIA}: 3" • Le: 0.88/1.05 mH • Impedance: 4/8 ohms • Re: 3.68/5.22 ohms • Frequency range: 63-2,800/52-2,300 Hz • Magnet weight: 80 oz. • Fs: 31/33 Hz • SPL: 98.1/100.5 dB 1W/1m • V_{AS}: 11.7/11.35 cu. ft. • Q_{MS}: 10.14/8.90 • Q_{ES}: 0.25/0.33 • Q_{TS}: 0.25/0.32 • X_{MAX}: 2.4/4.0 mm • Dimensions: A: 15.16", B: 13.77", C: 6.13"



#290-459 (15C-4 ohm) \$129.99 LIST **\$119.97** EACH

#290-458 (15A-8 ohm) \$129.99 LIST **\$119.97** EACH

Kappa-15LFA 600W Driver

Recommended for professional audio in a vented mid-bass or bass enclosure; also suitable for bass guitar.

- Specifications:** • Power handling: 600 watts RMS • VC_{DIA}: 3" • Le: 1.27 mH • Impedance: 8 ohms • Re: 5.4 ohms • Frequency range: 38-2,700 Hz • Magnet weight: 95 oz. • Fs: 39 Hz • SPL: 99 dB 1W/1m • V_{AS}: 5.6 cu. ft. • Q_{MS}: 6.08 • Q_{ES}: 0.41 • Q_{TS}: 0.38 • X_{MAX}: 5.5 mm • Dimensions: A: 15.16", B: 13.77", C: 6.38"



#290-460 \$139.99 LIST **\$129.97** EACH

Eminence Sigma Pro 18A-2 650W Driver

- Copper voice coil on Polyimide former
- Die-cast aluminum basket
- Vented and extended core
- Paper cone with cloth cone edge

Recommended for professional audio as a woofer in vented enclosures.

- Specifications:** • Power handling: 650 watts RMS/1,300 watts max • VC_{DIA}: 3" • Le: 1.90 mH • Impedance: 8 ohms • Re: 6.29 ohms • Frequency range: 41-2,400 Hz • Magnet weight: 120 oz. • Fs: 28 Hz • SPL: 99 dB 1W/1m • V_{AS}: 15.6 cu. ft. • Q_{MS}: 8.28 • Q_{ES}: 0.30 • Q_{TS}: 0.29 • X_{MAX}: 6.1 mm • Dimensions: A: 18", B: 16.56", C: 8.15"



#290-427 \$169.99 LIST **\$159.97** EACH

Eminence Delta Series

- Ferrite magnet
- Pressed steel basket
- Paper cone, cloth cone edge
- Solid composition paper dust cap



Delta-10 350W Drivers

Performance optimized for midrange in 3-way systems and mid-bass in 2-way systems. Also suitable for bass guitar, keyboards, club music systems, and stage monitors.

- Specifications:** • Power handling: 350 watts RMS • VC_{DIA}: 2.5" • Le: 0.74/0.79 mH • Impedance: 8/16 ohms • Re: 5.42/11.6 ohms • Frequency range: 63-3,700/71-3,700 Hz • Magnet weight: 56 oz. • Fs: 66/65 Hz • SPL: 98.8/98 dB 1W/1m • V_{AS}: 1.1/1.27 cu. ft. • Q_{MS}: 6.53/8.34 • Q_{ES}: 0.35 • Q_{TS}: 0.33 • X_{MAX}: 3.5/1.8 mm • Dimensions: A: 10.09", B: 9.05", C: 4.25"



#290-412 (10A-8 ohm) \$79.99 LIST **\$74.97** EACH

#290-413 (10B-16 ohm) \$79.99 LIST **\$74.97** EACH

Delta-12 400W Drivers

Recommended for professional audio as a mid-bass or woofer (with high-pass filter) in vented enclosures.

- Specifications:** • Power handling: 400 watts RMS • VC_{DIA}: 2.5" • Le: 0.74/0.77 mH • Impedance: 8/16 ohms • Re: 6.3/11.4 ohms • Frequency range: 54-5,000/65-5,000 Hz • Magnet weight: 56 oz. • Fs: 55/58 Hz • SPL: 98.3 dB 1W/1m • V_{AS}: 2.9/3.1 cu. ft. • Q_{MS}: 5.27/7.04 • Q_{ES}: 0.46/0.52 • Q_{TS}: 0.43/0.48 • X_{MAX}: 2.4/2.7 mm • Dimensions: A: 12.03", B: 10.95", C: 5.35"



#290-414 (12A-8 ohm) \$84.99 LIST **\$79.97** EACH

#290-415 (12B-16 ohm) \$84.99 LIST **\$79.97** EACH

Delta-12LFA 500W Driver

Performance optimized for high power bass in sound reinforcement systems, bass guitar combos, club music systems, and stage monitors. Eminence LF models are specifically designed with extended X_{max} to deliver more bass than standard models and provide "a true woofer" for 3-way applications.

- Specifications:** • Power handling: 500 watts RMS • VC_{DIA}: 2.5" • Le: 1.45 mH • Impedance: 8 ohms • Re: 6.06 ohms • Frequency range: 44-3,000 Hz • Magnet weight: 56 oz. • Fs: 51 Hz • SPL: 94.6 dB 1W/1m • V_{AS}: 2.4 cu. ft. • Q_{MS}: 7.28 • Q_{ES}: 0.51 • Q_{TS}: 0.47 • X_{MAX}: 4.8 mm • Dimensions: A: 12.03", B: 10.95", C: 5.35"



#290-416 \$99.99 LIST **\$94.97** EACH

Delta-15 400W Drivers

Recommended for professional audio as a mid-bass or vocal wedge in a sealed enclosure. Also suitable as a mid-bass or woofer in vented enclosures.

- Specifications:** • Power handling: 400 watts RMS • VC_{DIA}: 2.5" • Le: 0.64/1.35 mH • Impedance: 8/16 ohms • Frequency range: 40-4,000/64-4,000 Hz • Magnet weight: 56 oz. • Fs: 40/45 Hz • SPL: 100 dB 1W/1m • V_{AS}: 9.6/7.2 cu. ft. • Q_{MS}: 8.05/6.54 • Q_{ES}: 0.57/0.67 • Q_{TS}: 0.53/0.61 • X_{MAX}: 2.7/1.6 mm • Dimensions: A: 15.15", B: 13.77", C: 6.05"



#290-418 (15A-8 ohm) \$94.99 LIST **\$89.97** EACH

#290-419 (15B-16 ohm) \$94.99 LIST **\$89.97** EACH

Delta-15LFA 500W Driver

Performance optimized for high power bass in sound reinforcement systems, bass guitar combos, club music systems, and stage monitors. Eminence LF models are specifically designed with extended X_{max} to deliver more bass than standard models and provide "a true woofer" for 3-way applications.

- Specifications:** • Power handling: 500 watts RMS • VC_{DIA}: 2.5" • Le: 1.49 mH • Impedance: 8 ohms • Re: 6.3 ohms • Frequency range: 42-3,200 Hz • Magnet weight: 56 oz. • Fs: 41 Hz • SPL: 96 dB 1W/1m • V_{AS}: 6.6 cu. ft. • Q_{MS}: 6.65 • Q_{ES}: 0.64 • Q_{TS}: 0.58 • X_{MAX}: 4.8 mm • Dimensions: A: 15.15", B: 13.77", C: 6.3"



#290-417 \$104.99 LIST **\$99.97** EACH