

Pro Audio

Speakers, Drivers & Horns

Selenium SWS1100 Series High-Power Subwoofers

- Bumped backplate and extended pole piece for maximum excursion
- Multi-cooling system directly cools the gap and the air trapped between the two spiders
- 4" diameter flat wire voice coil on a fiberglass-composite former
- Non-pressed long fiber pulp cone for linear response and strength
- Two counter-balancing, distortion canceling, polyester-cotton-fiber spiders
- Highly reinforced cast aluminum frame also acts as a heatsink

Selenium's SWS1100 series has broken the 1,000 watt RMS power handling barrier. Capable of handling up to 2,200 watts of continuous music power, these subs are perfect for those who want premium performance; whether building a custom box, or upgrading an existing enclosure, the SWS1100 series is the choice!

15SWS1100 15" High-Power Subwoofer

Specifications: • Power handling: 1,100 watts RMS/2,200 watts max • VC_{DIA}: 4" • Le: 2.22 mH • Nominal impedance: 8 ohms • Re: 5.6 ohms • Frequency response: 35-3,000 Hz • Magnet weight: 120 oz. • Fs: 37 Hz • SPL: 95 dB 1W/1m • V_{AS}: 4.94 cu. ft. • Q_{MS}: 13.2 • Q_{ES}: 0.42 • Q_{TS}: 0.41 • X_{MAX}: 9.3 mm • Dimensions: A: 15.31", B: 13.74", C: 7.68".

#264-395 \$347.00 LIST **\$297.03** (1-3) **\$277.60** (4-UP)

18SWS1100 18" High-Power Subwoofer

Specifications: • Power handling: 1,100 watts RMS/2,200 watts max • VC_{DIA}: 4" • Le: 2.6 mH • Nominal impedance: 8 ohms • Re: 7.2 ohms • Frequency response: 30-2,500 Hz • Magnet weight: 120 oz. • Fs: 39 Hz • SPL: 97 dB 1W/1m • V_{AS}: 7.48 cu. ft. • Q_{MS}: 13.82 • Q_{ES}: 0.50 • Q_{TS}: 0.48 • X_{MAX}: 9.3 mm • Dimensions: A: 18", B: 16.55", C: 8.7".

#264-396 \$365.00 LIST **\$312.44** (1-3) **\$292.00** (4-UP)

SELENIUM
LOUDSPEAKERS



Selenium PW3 Series

- PA and musical instrument woofers
- Reinforced stamped steel frame
- Four roll, treated cloth surround
- Vented pole piece



8PW3-SLF 8" PA Woofer

Specifications: • Power handling: 125 watts RMS/250 watts max • VC_{DIA}: 1-1/4" • Le: .32 mH • Nominal impedance: 8 ohms • Re: 6.48 ohms • Frequency response: 70-8,000 Hz • Magnet weight: 20 oz. • Fs: 72 Hz • SPL: 92 dB 1W/1m • V_{AS}: 1.02 cu. ft. • Q_{MS}: 9.64 • Q_{ES}: 0.88 • Q_{TS}: 0.81 • X_{MAX}: 2.35 mm • Dimensions: A: 8-1/8", B: 7-1/8", C: 3-3/8".

#264-330 \$39.00 LIST **\$33.38** (1-3) **\$31.20** (4-UP)

10PW3-SLF 10" PA Woofer

Specifications: • Power handling: 150 watts RMS/300 watts max • VC_{DIA}: 1-3/4" • Le: .45 mH • Nominal impedance: 8 ohms • Re: 6.1 ohms • Frequency response: 60-6,000 Hz • Magnet weight: 44 oz. • Fs: 73 Hz • SPL: 98 dB 1W/1m • V_{AS}: 1.02 cu. ft. • Q_{MS}: 6.32 • Q_{ES}: 0.73 • Q_{TS}: 0.66 • X_{MAX}: 1.25 mm • Dimensions: A: 10", B: 9", C: 4-1/2".

#264-332 \$56.00 LIST **\$47.94** (1-3) **\$44.80** (4-UP)

12PW3-SLF 12" PA Woofer

Specifications: • Power handling: 200 watts RMS/400 watts max • VC_{DIA}: 1-3/4" • Le: .45 mH • Nominal impedance: 8 ohms • Re: 6.3 ohms • Frequency response: 55-5,000 Hz • Magnet weight: 44 oz. • Fs: 50 Hz • SPL: 97 dB 1W/1m • V_{AS}: 3.42 cu. ft. • Q_{MS}: 7.95 • Q_{ES}: 0.75 • Q_{TS}: 0.69 • X_{MAX}: 1.29 mm • Dimensions: A: 12-1/16", B: 11", C: 4-3/4".

#264-334 \$59.00 LIST **\$50.50** (1-3) **\$47.20** (4-UP)

15PW3-SLF 15" PA Woofer

Specifications: • Power handling: 250 watts RMS/500 watts max • VC_{DIA}: 2-1/2" • Le: .70 mH • Nominal impedance: 8 ohms • Re: 5.8 ohms • Frequency response: 40-4,000 Hz • Magnet weight: 56 oz. • Fs: 37 Hz • SPL: 98 dB 1W/1m • V_{AS}: 9.67 cu. ft. • Q_{MS}: 5.81 • Q_{ES}: 0.68 • Q_{TS}: 0.61 • X_{MAX}: 3.0 mm • Dimensions: A: 15", B: 13-3/4", C: 6".

#264-338 \$82.00 LIST **\$70.19** (1-3) **\$65.60** (4-UP)

Selenium SWS800 Series Subwoofers

- 4" diameter, 4-layer voice coil wound on a fiberglass former
- Non-pressed long fiber pulp cone has the necessary stiffness for a linear response
- Bumped and undercut T-yoke assures maximum displacement
- Triple cooling system directly cools the gap and the air trapped between the two spiders

The SWS800 high-power professional subwoofers were specially designed to reproduce sound at the very low end of the audio spectrum.

15SWS800 15" Subwoofer

Specifications: • Power handling: 800 watts RMS/1,600 watts max • VC_{DIA}: 4" • Le: 4.12 mH • Nominal impedance: 8 ohms • Re: 5.6 ohms • Frequency response: 35-1,500 Hz • Magnet weight: 120 oz. • Fs: 37 Hz • SPL: 93 dB 1W/1m • V_{AS}: 3.44 cu. ft. • Q_{MS}: 13.78 • Q_{ES}: 0.38 • Q_{TS}: 0.37 • X_{MAX}: 6.5 mm • Dimensions: A: 15.28", B: 13.74", C: 7.48".

#264-388 \$212.00 LIST **\$181.47** (1-3) **\$169.60** (4-UP)



18SWS800 18" Subwoofer

Specifications: • Power handling: 800 watts RMS/1,600 watts max • VC_{DIA}: 4" • Le: 3.87 mH • Nominal impedance: 8 ohms • Re: 5.8 ohms • Frequency response: 30-1,500 Hz • Magnet weight: 120 oz. • Fs: 32 Hz • SPL: 96 dB 1W/1m • V_{AS}: 8.09 cu. ft. • Q_{MS}: 13.7 • Q_{ES}: 0.42 • Q_{TS}: 0.41 • X_{MAX}: 6.5 mm • Dimensions: A: 18", B: 16.54", C: 8.46".

#264-387 \$228.00 LIST **\$195.17** (1-3) **\$182.40** (4-UP)



Selenium W10P-Nd Series Neodymium Woofers

- Light weight—each driver weighs less than 10 lbs.
- 3" flatwound copper voice coil
- Rugged integrated frame/heatsink
- Smooth, low-distortion output



12W10P-Nd 12" Neodymium Woofer

Specifications: • Power handling: 350 watts RMS • VC_{DIA}: 3" • Le: 1.28 mH • Impedance: 8 ohms • Re: 6.2 ohms • Frequency range (-10 dB): 50 to 4,000 Hz • Magnet weight: 12.34 oz. • Fs: 62.5 Hz • SPL: 96 dB 1W/1m • V_{AS}: 1.35 cu. ft. • Q_{MS}: 14.41 • Q_{ES}: 0.48 • Q_{TS}: 0.47 • X_{MAX}: 3.75 mm • Dimensions: A: 12.25", B: 11.06", C: 5.75".

#264-442 \$168.00 LIST **\$143.81** (1-3) **\$134.40** (4-UP)

15W10P-Nd 15" Neodymium Woofer

Specifications: • Power handling: 350 watts RMS • VC_{DIA}: 3" • Le: 1.235 mH • Impedance: 8 ohms • Re: 6.1 ohms • Frequency range (-10 dB): 45 to 4,500 Hz • Magnet weight: 12.34 oz. • Fs: 43.6 Hz • SPL: 98 dB 1W/1m • V_{AS}: 5.82 cu. ft. • Q_{MS}: 18.90 • Q_{ES}: 0.46 • Q_{TS}: 0.45 • X_{MAX}: 3.75 mm • Dimensions: A: 15.2", B: 14", C: 6.75".

#264-443 \$191.00 LIST **\$163.50** (1-3) **\$152.80** (4-UP)

Selenium 10MB1P 10" 300W Mid-Bass Driver

- Cast aluminum frame
- Cloth surround with stiff paper cone
- Vented pole piece for reducing long term heat build-up



Specifications: • Power handling: 300 watts RMS/600 watts max • VC_{DIA}: 3" • Le: .83 mH • Nominal impedance: 8 ohms • Re: 6.1 ohms • Frequency response: 200-6,000 Hz • Magnet weight: 86 oz. • Fs: 75 Hz • SPL: 101 dB 1W/1m • V_{AS}: .95 cu. ft. • Q_{MS}: 10.26 • Q_{ES}: .35 • Q_{TS}: .34 • X_{MAX}: 2 mm • Dimensions: A: 10-1/4", B: 9", C: 4-1/2".

#264-432 \$173.00 LIST **\$148.09** (1-3) **\$138.40** (4-UP)