

Selenium ST350 Super Tweeter

- ABS housing
- Durable phenolic diaphragm
- Well-controlled 50° conical dispersion
- High temperature adhesives and materials for increased power handling

Very efficient super tweeter designed to be used in high-frequency sound reinforcement. Recommended for large rooms, clubs, auditorium, theaters, and any other environment requiring smooth, well-controlled high frequency response.



Specifications: • Power handling: 75 watts RMS/150 watts program (above 5,000 Hz) • Dispersion: 50° H x 50° V • VC_{DIA}: 1.6" • Impedance: 8 ohms • Frequency response: 2,500-20,000 Hz • SPL: 111 dB 1W/1m • Magnet weight: 16.5 oz. • Dimensions: 5.12" H x 4.76" W x 3.86" D.

#264-362 \$46.00 LIST **\$39.38** (1-3) **\$36.80** (4-UP)

#264-363 (RPST350 diaphragm) ... \$13.00 LIST **\$11.13** (1-3) **\$10.40** (4-UP)

Pyle Pro Horn Tweeters

When demands for widely dispersed, high frequency sounds are great, these horn tweeters are a superb solution. All models feature excellent transient response and are capable of handling very high SPL levels.



PH25 3" x 3" Horn Tweeter

Specifications: • Power handling: 60 watts RMS/120 watts max • VC_{DIA}: 1" • Impedance: 8 ohms • Frequency response: 1,000-15,000 Hz • Magnet weight: 15 oz. • SPL: 100 dB 1W/1m.



#272-104 \$12.00 LIST **\$6.93** (1-3) **\$6.42** (4-UP)

PH44 4" x 4" Horn Tweeter

Specifications: • Power handling: 100 watts RMS/200 watts max • VC_{DIA}: 1" • Impedance: 8 ohms • Frequency response: 1,000-18,000 Hz • Magnet weight: 15 oz. • SPL: 105 dB 1W/1m.



#272-102 ... \$14.00 LIST **\$10.50** (1-3) **\$9.81** (4-UP)

PDBT18 1" Bullet Horn Tweeter Pair

Pyle Pro high-dispersion bullet type speakers provide clear imaging of audio program material over a wide range of frequencies and dynamic ranges. All models feature a die-cast aluminum frame, high-temperature ferrofluid cooled voice coil and include crossover capacitor.



Specifications: • Power handling: 60 watts RMS/120 watts max • VC_{DIA}: 1" • Impedance: 4 ohms • Frequency response: 2,000-25,000 Hz • Magnet weight: 20 oz. • SPL: 93 dB 1W/1m.

#272-110 \$33.00 LIST **\$21.93** (1-3 PRS) **\$19.94** (4 PRS-UP)

PSN165 Wide Dispersion Horn Tweeter Pair

Features an excellent transient response and low distortion.

Specifications: • Power handling: 75 watts RMS/150 watts max • Impedance: 4-8 ohms • Frequency response: 4,000-20,000 Hz • SPL: 94 dB 1W/1m • Dimensions: 4.35" square.



#272-100 \$16.00 LIST **\$8.49** (1-3 PRS) **\$7.54** (4 PRS-UP)

Pro Audio Speakers, Drivers & Horns

SELENIUM

LOUDSPEAKERS

Selenium Super Tweeters

Selenium has been designing and manufacturing products for the sound reinforcement and musical instrument industry since 1958. These professional super tweeters are engineered for performance, longevity, and compact size.

NEW

ST200 Super Tweeter

Selenium's ST200 super tweeter offers outstanding detail and clarity at the highest frequencies, without harshness. Thanks to its bullet-shaped horn design, the ST200 offers a longer throw 40° conical dispersion, and the plastic injected housing is stable and durable. The phenolic annular diaphragm is long-lasting, cost-effective, and more natural-sounding than metallic diaphragms.



Specifications: • Power handling: 70 watts RMS/140 watts program (above 5,000 Hz) • Dispersion: 40° H x 40° V • VC_{DIA}: 1.75" • Impedance: 8 ohms • Frequency response: 2,000-20,000 Hz • SPL: 105 dB 1W/1m • Magnet weight: 7.72 oz. • Dimensions: 4.88" H x 4.53" W x 2.4" D.

#264-348 \$20.54 LIST **\$17.46** (1-3) **\$16.43** (4-UP)

DT150 Super Tweeter with 4" x 4" Horn

This high power bullet tweeter is ideal for 2-way and 3-way monitor applications. It features a compact 4" x 4" ABS horn lens and durable phenolic diaphragm.



Specifications: • Power handling: 75 watts RMS/105 watts max (conservative, with recommended crossover at 4,000 Hz) • VC_{DIA}: 1" • Impedance: 8 ohms • Frequency response: 1,500-18,000 Hz • SPL: 107 dB 1W/1m • Dimensions: 4" W x 4" H x 4-3/4" D.

#264-240 \$38.00 LIST **\$32.53** (1-3) **\$30.40** (4-UP)

ST304 Super Tweeter

• ABS housing
Specifications: • Power handling: 40 watts RMS/55 watts max • Dispersion: 40° H x 40° V • VC_{DIA}: 1-3/4" • Impedance: 8 ohms • Frequency response: 3,500-18,000 Hz • SPL: 106 dB 1W/1m • Magnet weight: 11 oz. • Dimensions: Diameter: 4-1/16", depth: 2-3/8".



#264-350 \$32.00 LIST **\$27.39** (1-3) **\$25.60** (4-UP)

#264-382 (RPST304 diaphragm) \$8.00 LIST **\$6.85** (1-3) **\$6.40** (4-UP)

ST300 Super Tweeter

• Aluminum housing
Specifications: • Power handling: 50 watts RMS/75 watts max • Dispersion: 40° H x 40° V • VC_{DIA}: 1-3/4" • Impedance: 8 ohms • Frequency response: 3,500-20,000 Hz • SPL: 108 dB 1W/1m • Magnet weight: 15 oz. • Dimensions: Diameter: 4-1/4", depth: 3-9/16".



#264-355 \$52.00 LIST **\$44.51** (1-3) **\$41.60** (4-UP)

#264-380 (RPST300 diaphragm) \$9.00 LIST **\$7.70** (1-3) **\$7.20** (4-UP)

ST324 Super Tweeter

• ABS housing
Specifications: • Power handling: 40 watts RMS/55 watts max • Dispersion: 120° H x 40° V • VC_{DIA}: 1-3/4" • Impedance: 8 ohms • Frequency response: 3,500-18,000 Hz • SPL: 103 dB 1W/1m • Magnet weight: 11 oz. • Dimensions: Diameter: 4", depth: 2-3/8".



#264-360 \$32.00 LIST **\$27.39** (1-3) **\$25.60** (4-UP)

#264-382 (RPST304 diaphragm) \$8.00 LIST **\$6.85** (1-3) **\$6.40** (4-UP)