

Pro Audio

Speakers, Drivers & Horns

Pyle Pro Bullet Tweeters

PDBT28 1" Heavy Duty Titanium Tweeter



Specifications: • Power handling: 75 watts RMS/150 watts max • VC_{DIA}: 1" • Impedance: 4 ohms • Frequency response: 2,000-20,000 Hz • Magnet weight: 20 oz. • SPL: 104 dB 1W/1m • Sold individually.

#272-115 \$25.00 LIST **\$19.95** (1-3) **\$18.45** (4-UP)

PDBT38 2" Heavy Duty Titanium Super Tweeter

Specifications: • Power handling: 125 watts RMS/250 watts max • Voice coil diameter: 2" • Impedance: 8 ohms • Frequency response: 2,000-25,000 Hz • Magnet weight: 60 oz. • SPL: 106 dB 1W/1m • Sold individually.



#272-120 \$60.00 LIST **\$43.84** (1-3) **\$40.56** (4-UP)

PDBT58 3" Extra Heavy Duty Titanium Super Tweeter

Specifications: • Power handling: 200 watts RMS/400 watts max • VC_{DIA}: 3" • Impedance: 8 ohms • Frequency response: 2,000-25,000 Hz • Magnet weight: 100 oz. • SPL: 109 dB 1W/1m • Sold individually.



#272-125 \$126.00 LIST **\$69.58** (1-3) **\$63.96** (4-UP)

Eminence PSD:3006-8 2" Titanium Horn Driver

- 2" exit, 4-bolt mounting pattern
- 3" high-temperature voice coil
- Titanium diaphragm with polyimide VC former

The Eminence PSD:3006-8 driver is an 8 ohm titanium-diaphragm driver with a geodesic dome design for increased strength and stiffness. Ideal for high-power, high-output professional sound reinforcement applications. Replacement diaphragm available.



Specifications: • Power handling: 80 watts RMS (AES500 specification with x-over > 500 Hz, exc. 24 dB/octave), 115 watts RMS (AES800 specification with 800 Hz x-over @ 12 dB/octave) • Impedance: 8 ohms • Frequency range: 500-18,000 Hz • Sensitivity: 111.4 dB (1W/1m across 500 Hz-18 kHz). Magnet weight: 80 oz. • Dimensions: 7.9" diameter x 3.1" depth.

#290-440 \$229.99 LIST **\$199.97** EACH

#290-438 (PSD:3006-8DIA diaphragm) **\$94.97** EACH

Eminence NSD:2005 1" Neodymium Horn Drivers

- Neodymium magnet for lightweight performance
- Polyimide former with titanium diaphragm
- Recommended crossover: 1.5 kHz, 12 dB/octave
- Available in 2-bolt and 1-3/8"-18 TPI screw-on versions

Specifications: • Power handling: 50 watts RMS (AES Specification, 1.5 kHz @ 12 dB) • Impedance: 8 or 16 ohms • VC_{DIA}: 2" • Fs: 580 Hz • Usable frequency range: 1.5-16 kHz • Sensitivity: 111 dB 1W/1m • Magnet weight: 4.16 oz. • Dimensions: 3.87" dia. x 1.75" depth.



| Part # | Mfg. # | Description | List Price | Price Each |
|---------|----------------|-------------------|------------|----------------|
| 290-526 | NSD:2005-8 | Bolt-on, 8 ohm | \$99.99 | \$94.97 |
| 290-527 | NSD:2005-16 | Bolt-on, 16 ohm | 99.99 | 94.97 |
| 290-528 | NSD:2005S-8 | Screw-on, 8 ohm | 99.99 | 94.97 |
| 290-529 | NSD:2005S-16 | Screw-on, 16 ohm | 99.99 | 94.97 |
| 290-564 | NSD:2005-8DIA | Diaphragm, 8 Ohm | 56.99 | 54.97 |
| 290-565 | NSD:2005-16DIA | Diaphragm, 16 Ohm | 56.99 | 54.97 |

Pyramid Bullet Tweeters



TW44 Heavy Duty 1" Titanium Super Tweeter

- Die-cast aluminum housing
- Ferro-fluid cooled
- Kapton voice coil
- Includes crossover capacitor



Specifications: • Power handling: 150 watts RMS/300 watts peak power • VC_{DIA}: 1" • Impedance: 6-8 ohms • Re: 3.5 ohms • Frequency response: 2,000-20,000 Hz • SPL: 104 dB 1W/1m • Magnet weight: 30 oz. • Dimensions: Face: 3-1/8" square, depth: 2-1/8".

#270-125 **\$16.75** (1-3) **\$15.25** (4-UP)

#270-126 (Replacement diaphragm) **\$9.50** (1-3) **\$8.98** (4-UP)

TW47 2" High-Power Titanium Super Tweeter

- Die-cast aluminum housing
- Low-profile, rear-mount design
- Kapton voice coil
- Ferro-fluid cooled
- Includes mylar crossover capacitor



Specifications: • Power handling: 125 watts RMS/250 watts peak power • VC_{DIA}: 2" • Impedance: 8 ohms • Re: 6 ohms • Frequency response: 2,000-25,000 Hz • SPL: 106 dB 1W/1m • Magnet weight: 60 oz.


• Overall dimensions: face: 4-1/4" square, depth: 3-1/8" • Rear-mount hole dimensions: 3-1/8" diameter, 1" depth.

#270-135 **\$34.90** (1-3) **\$29.95** (4-UP)

#270-136 (Replacement diaphragm) **\$13.60** (1-3) **\$10.90** (4-UP)

TW18 Bullet Horn Super Tweeter Pair

- Specifications:** • 3-3/4" aluminum bullet horn with 1" super tweeter • Ferrofluid cooled voice coil • Includes crossover capacitor • Power handling: 60 watts RMS/120 watts peak • VC_{DIA}: 1" • Impedance: 4 ohms • Frequency response: 2,000-25,000 Hz • SPL: 93 dB 1W/1m • Magnet weight: 20 oz. • Dimensions: 3-3/4" diameter x 1-1/2" depth • Available in natural aluminum or black color • Sold in pairs.



#270-100 (Natural)

#270-102 (Black) \$24.99 LIST **\$19.85** (1-3) **\$18.74** (4-UP)



Eminence PSD:2002 1" Titanium Horn Drivers

Features polyimide former and titanium diaphragm. Available in 2-bolt/3-bolt and standard 1-3/8"-18 TPI screw-on versions, in 8 or 16 ohms.

Specifications: • Power handling: 80 watts RMS • VC_{DIA}: 2" • Impedance: 8 or 16 ohms • Frequency range: 1,200-20,000 Hz • Magnet weight: 34 oz. • Fs: 550 Hz • Sensitivity: 105 dB (1 mW in plane wave tube) • PSD2002 bolt-on mounting (hole size and pattern): 2 x 1/4"-20, 3" o.c. and 3 x M6, 2.25" o.c. • PSD2002S screw-on mounting: 1-3/8"-18 ext. thread • Dimensions: 5.25" dia, x 2.2" depth.



| Part # | Mfg. # | Description | List Price | Price Each |
|---------|----------------|------------------------------|------------|----------------|
| 290-442 | PSD:2002-8 | Bolt-on, 8 ohm | \$59.99 | \$54.97 |
| 290-444 | PSD:2002-16 | Bolt-on, 16 ohm | 59.99 | 54.97 |
| 290-446 | PSD:2002S-8 | Screw-on, 8 ohm | 64.99 | 58.97 |
| 290-448 | PSD:2002S-16 | Screw-on, 16 ohm | 64.99 | 58.97 |
| 290-445 | PSD:2002-8DIA | 8 ohm replacement diaphragm | 44.99 | 39.97 |
| 290-449 | PSD:2002-16DIA | 16 ohm replacement diaphragm | 44.99 | 39.97 |