

**Eminence High Frequency Horns**



All Eminence horns are constructed of a high-density, heavy-duty, injection molded ABS. The TI2000 was designed to support even the largest 4-bolt horn driver without the need for extra support brackets.



Part #	Mfg. #	Horn Type	Min Freq	Nominal Dispersion	Throat Dia.	Mounting Type	Dimensions (W x H x D)	List Price	Price Each
<b>290-558</b>	LT250	Constant Directivity	1 kHz	80° H x 60° V	1"	2 bolt/3 bolt	6.7" x 6.4" x 3.8"	\$34.99	<b>\$29.97</b>
<b>290-556</b>	SST1	Constant Directivity	1 kHz	90° H x 40° V	1"	2 bolt/3 bolt	9.8" x 7.7" x 5.2"	49.99	<b>44.97</b>
<b>290-550</b>	H295	Constant Directivity	1 kHz	90° H x 40° V	1"	2 bolt/3 bolt	12.1" x 6" x 4"	39.99	<b>34.97</b>
<b>290-555</b>	H290S	Constant Directivity	1 kHz	90° H x 40° V	1"	1-3/8"-18 TPI	12.1" x 6" x 4"	44.99	<b>38.97</b>
<b>290-552</b>	H395	Constant Directivity	1 kHz	90° H x 40° V	1"	2 bolt/3 bolt	15.6" x 7.3" x 6.1"	39.99	<b>36.97</b>
<b>290-554</b>	H290	Bi-radial	1 kHz	90° H x 40° V	1"	2 bolt/3 bolt	11.4" x 6.5" x 5.9"	49.99	<b>44.97</b>
<b>290-560</b>	TI2000	Directivity, Radial	500 Hz	60° H x 40° V	2"	4 bolt	11.1" x 9.6" x 10"	84.99	<b>79.97</b>

Mounting type notes: 2 hole- For 2 x 1/4"-20; 3" o.c. mount drivers, 3 hole- For 3 x M6, 2.25" o.c. mount drivers; 4 hole- For 4 x 1/4"-20, 4" o.c. mount drivers.

**Selenium High Frequency Horns**



Selenium manufactures a variety of professional horns to complement their range of drivers. Each horn is crafted of high quality molded fiberglass, diecast aluminum, or ABS and provides different angles of dispersion to allow for maximum and optimal sound coverage to suit the particular application.



Part #	Mfg. #	Horn Type	Min Freq.	Nominal Dispersion	Throat Dia.	Mounting Type	Dimensions (W x H x D)	List Price	Price (1-3)	Price (4-UP)	
<b>264-306</b>	HM11-25	Exponential	1,200 Hz	60° H x 60° V	1.0"	1-3/8"-18 TPI	4.52" x 4.52" x 2.95"	\$8.00	<b>\$6.85</b>	<b>\$6.40</b>	
<i>This exponential horn features a low cutoff frequency, compact size and is perfect for stage monitors, side fill and P.A. applications.</i>											
<b>264-315</b>	HL14-25	Exponential	600 Hz	45° H x 45° V	1.0"	1-3/8"-18 TPI	6.1" x 6.1" x 10.2"	7.00	<b>5.99</b>	<b>5.60</b>	
<i>Conical, narrow dispersion exponential horn for long throw monitor and P.A. enclosures. Polypropylene construction.</i>											
<b>264-316</b>	HL14-50	Exponential	700 Hz	45° H x 45° V	2.0"	4 hole	6.1" x 6.1" x 5.1"	27.00	<b>23.11</b>	<b>21.60</b>	
<i>Conical, narrow dispersion exponential horn for long throw monitor and P.A. enclosures. Aluminum construction.</i>											
<b>264-328</b>	HM4750-SLF	Bi-radial	400 Hz	90° H x 40° V	2.0"	4 hole	17.52" x 11.42" x 8.27"	121.00	<b>103.58</b>	<b>96.80</b>	
<i>Larger format horn is ideal for stage monitors, side-fill and most P.A. applications. Reinforced fiberglass construction.</i>											
<b>264-329</b>	HL4750-SLF	Bi-radial	400 Hz	40° H x 20° V	2.0"	4 hole	17.52" x 11.02" x 13.86"	140.00	<b>119.84</b>	<b>112.00</b>	
<i>Larger format horn is ideal for side-fill and most P.A. applications. Reinforced fiberglass construction.</i>											
<b>264-308</b>	HM17-25	Bi-radial	1,500 Hz	60° H x 40° V	1.0"	1-3/8"-18 TPI	6.34" x 5.16" x 4.16"	7.00	<b>5.99</b>	<b>5.60</b>	
<i>This horn exhibits outstanding off axis uniformity, extremely low throat distortion and smooth detailed high frequency reproduction.</i>											
<b>264-312</b>	HM25-25	Exponential	1,200 Hz	90° H x 60° V	1.0"	1-3/8"-18 TPI	10.79" x 6.46" x 5.94"	27.00	<b>23.11</b>	<b>21.60</b>	
<i>Constructed of an epoxy coated, rigid injected aluminum and is dedicated to reproduce a wide frequency response with high performance.</i>											
<b>264-318</b>	HC23-25	Exponential	600 Hz	100° H x 40° V	1.0"	1-3/8"-18 TPI	10.0" x 5.0" x 5.7"	12.00	<b>10.27</b>	<b>9.60</b>	
<i>Wide dispersion diffraction horn used in compact P.A. and monitor enclosures. ABS construction.</i>											
<b>264-322</b>	ADF25-25	Adapts a 1-3/8"-18 TPI driver to be used with a 1" dia. throat 3-bolt horn							5.99	<b>3.76</b>	<b>3.51</b>
<b>264-323</b>	ADM25-25	Adapts a 2-bolt or 3-bolt 1" throat driver to a 1-3/8"-18 TPI horn							10.99	<b>6.35</b>	<b>5.93</b>