


Fourjay Paging Horns



32 Watt 25/70.7V Re-Entrant Horn Speaker

Designed for noise penetration and clear speech intelligibility, the 132-TD is used in high-noise areas and outdoor locations where you need exceptionally high output and long-thru coverage. It also boasts excellent sensitivity as a microphone in talk-back systems. It is conservatively rated at 32 watts continuous duty while the diffuser suppresses on-axis hot spots and improves dispersion. Includes 18-2, black jacketed, 30" cable for fast "hard wiring" and good weatherability. Mfg. #132-TD. Made in the USA.



Specifications: • Input: 25V or 70.7V line
• Power taps: 32, 16, 8, 4 & 2 watts
• Frequency range: 600-4,500 Hz (±3 dB)
• SPL: 110 dB 1W/1m • Dimensions: 12-1/4" W x 7-11/16" H x 11-5/8" D (excluding mounting base).

#300-069 **\$103.20** (1-5) **\$94.58** (6-UP)

Thundering Mini Horn Speaker

Designed for good speech intelligibility, the 440-8 Thundering Mini is ideal for 2-way communications on trucks, heavy equipment, boats, helicopters, etc. and provides excellent sensitivity as a microphone in talk-back systems. The 440-8 comes with a 30" black jacketed cable for fast "hard wiring" and good weatherability. Mfg. #440-8. Made in the USA.



Specifications: • Rated input: 8 ohms • Power handling: 40 watts continuous duty • Frequency range: 700-6,500 Hz • Sensitivity: 107 dB
• Dimensions: 5-1/2" W x 5-1/2" H x 4-13/16" D (excluding mounting base).

#300-066 **\$55.57** (1-5) **\$49.93** (6-UP)

The Little Big Horn

Designed for paging and music in moderately noisy environments, the Little Big Horn provides pleasing voice projection and high speech intelligibility. Constructed of impact & UV resistant ABS and stainless steel fasteners, it is weather and corrosion resistant while the reflex driver uses a moisture resistant diaphragm. Available in 8 ohm and 70.7V versions. Dimensions: 5-1/2" W x 5-1/2" H x 4-1/2" D (excluding mounting base). Made in the USA.



8 Ohm Horn Speaker—Specifications: • Rated input: 8 ohms • Power tap: 6 watts • Frequency range: 400-5,000 Hz • Sensitivity: 97 dB • Mfg. #306-8.

#300-067 **\$44.62** (1-5) **\$40.92** (6-UP)

70.7V Horn Speaker—Specifications: • Rated input: 70.7V line • Power taps: 6, 3, 1 & 1/2 watts • Frequency range: 400-5,000 Hz • Sensitivity: 97 dB
• Mfg. #306/70-T.

#300-064 **\$55.51** (1-5) **\$52.31** (6-UP)

Atlas Sound Universal Platform Mount



Universal platform adapter for use with tripod speakers stands that use a 1-3/8" diameter center support tube. Multiple mounting holes will meet a variety of support applications, while the metal construction offers a maximum load capacity of 100 lbs. Dimensions: 8-1/4" L x 4-5/8" W x 2-1/4" H. Mfg. #SSA7.



#242-179 **\$38.00** LIST **\$26.90** (1-5) **\$24.13** (6-UP)

ULTIMATE®

Ultimate Tripod Speaker Stands

Ultimate is well-known industry-wide for high quality speaker stands. Glass-reinforced polycarbonate fittings and anodized, drawn aluminum tubing make for durable, dependable and lightweight tripods. Design advancements include tight secure locking knobs and metal clamps surrounding plastic fittings, resulting in a hefty load capacity of 150 lbs.! Also new to these models is a unique telescoping connector tube that accommodates both 1-3/8" and 1-1/2" speaker "top hat" sockets. The TS-80 series adjusts from 3 ft. 8" to 6 ft. 7", weighs 6-1/4 lbs. and has a base diameter of 47". The larger TS-88 series adjusts from 5 ft. 2" to 9 ft. 2", weighs 8 lbs. and has a base diameter of 62". Lifetime manufacturer's limited warranty.



Part #	Mfg. #	Description	List Price	Price Each
242-720	TS-80S	Silver, 6'7" max height	\$129.99	\$79.99
242-725	TS-80B	Black, 6'7" max height	129.99	79.99
242-735	TS-88B	Black, 9'2" max height	169.99	119.26

Ultimate Telelock® Tripod Speaker Stand

The TS-90 stand with Telelock® is sturdier, smarter and no sweat for one person to use. Telelock® is a patented locking mechanism that makes these stands slip resistant with internal friction preventing speakers lowering too hard or too quickly. Easy "raise" or "lower" settings make setups and take downs a snap. Large tube diameter allows for a huge load capacity of 150 lbs.! Also new to this model is a unique telescoping connector tube that accommodates both 1-3/8" and 1-1/2" speaker "top hat" sockets. Adjusts from 3/8" to 6'7", weighs 6-1/4 lbs. and has a base diameter of 47". Lifetime manufacturer's limited warranty. Made in the USA.



#242-745 (TS-90B Black) **\$149.99** LIST **\$119.99** EACH

P. A. Horns

11" x 6-1/2" Horn Speaker

This high output horn was designed for small auditoriums and warehouse applications. Built-in matching transformer with 2,500, 1,250, 625, 312, 156, 83 and 42 ohm impedance taps. 2, 4, 8, 16, and 32 watt (70V) and 1, 2, 4, 8, and 16 watt (25V) wattage taps. Power handling capability: 32 watts. Frequency response: 300-14,000 Hz. Sound pressure level: 125 dB 32W/4 ft.



#300-063 **\$44.90** (1-3) **\$39.90** (4-19) **\$37.70** (20-UP)

5" Horn Speaker

Made of high impact white ABS plastic. Completely weatherproof, ideal for indoor or outdoor use. Frequency response: 400-15,000 Hz. 8 ohm impedance. 12 watt maximum input power.



#300-050 .. **\$7.25** (1-3) **\$5.90** (4-19) **\$5.42** (20-UP)

5" x 8" Horn Speaker

This is a high quality, heavy duty horn ideal for indoor or outdoor use. It is capable of handling up to 30 watts RMS, 40 watts max. Frequency response from 450 Hz to 10,000 Hz. 8 ohm impedance.



#300-060 **\$15.50** (1-3) **\$14.25** (4-19) **\$12.80** (20-UP)