

Atlas Sound Strategy Series two-way, surface-mount loudspeaker systems are ideal for indoor and outdoor installation in conference rooms & classrooms, boutiques/shops, restaurants/cafes, decks/patios, recreation/sports centers, amusement/theme parks, and houses of worship.



Atlas Sound Strategy Series II Ceiling Speaker Systems (UL 1480)

- Easy installation in drop tile or sheetrock ceilings via C-ring/V-rail tile bridge (included) and "dog leg" mounting system
- Front mounted tap selector switch for easy system tuning adjustments includes transformer bypass setting for 8 ohm direct coupled operation
- Extended low frequency response from the optimally tuned and ported enclosure
- Enhanced quality 70.7V/100V internal transformers minimize insertion loss and maintain low frequency response



FAP42T 4" Coaxial Tuned & Ported System

A low profile enclosure and wide coverage make the FAP42T a perfect choice for low ceilings.

- Specifications:** • Power rating: 16 watts (transformer limited) • 70.7V taps: 1, 2, 4, 8, 16 watts • Frequency response: 75 Hz-20 kHz • Dispersion: 130° • Dimensions: Overall: 10-1/2" dia. x 8-7/8" H; Cutout: 9" dia.



FAP42TC Compact 4" Coaxial Speaker Pair

With an overall depth of 4" (102 mm) the FAP42TC is the perfect choice when high fidelity audio and wide, even coverage is required but space above the plenum is limited. For wall mount applications (tanning salons or surround sound) the short 4" depth will even work in most stud wall installations.

- Specifications:** • Power rating: 16 watts (transformer limited) • 70.7V taps: 1, 2, 4, 8, 16 watts • Frequency response: 75 Hz-20 kHz • Dispersion: 130° • Dimensions: Overall: 10-1/2" dia. x 4-1/4" H • Cutout: 9" dia.



FAP62T 6" Coaxial Speaker Pair

Compact profile enclosure and wide dispersion make the FAP62T a perfect choice for low ceilings.

- Specifications:** • Power rating: 50 watts (transformer limited) • 70.7V taps: 2, 4, 8, 16, 32 watts • Frequency response: 63 Hz-20 kHz • Dispersion: 110° • Dimensions: Overall: 12-1/2" dia. x 8-1/2" H • Cutout: 11" dia.



FAP82T 8" Coaxial Speaker Pair

The FAP82T is perfect where high ceilings require loudspeakers with increased efficiency and tighter pattern control. Tight pattern control (not exceeding 100°) is important for high ceiling applications.

- Specifications:** • Power rating: 70 watts (at 8 ohms) • 70.7V taps: 1.9, 3.8, 7.5, 15, 30, 60 watts • Frequency response: 65 Hz-20 kHz • Dispersion: 100° • Dimensions: Overall: 15-3/4" dia. x 12-3/4" H • Cutout: 14" dia.



FAPSUB 8" Subwoofer Speaker Pair

The FAPSUB adds impressive low frequency response to any full range distributed system.

- Specifications:** • Power rating: 100 watts/200 watts max (transformer limited) • 70.7V taps: 1.9, 3.8, 7.5, 15, 30, 60 watts • Frequency response: 45-120 Hz (±10 dB) • Low pass filter: 120 Hz (18 dB/octave) • Dimensions: Overall: 15-3/4" dia. x 12-3/4" H • Cutout: 14" dia.



Atlas Sound Strategy Series® II Surface Mount Speaker Systems

- Weather resistant construction for year-round indoor or outdoor use
- UV-resistant, talc impregnated, polypropylene injection molded enclosures
- Powder coated aluminum grilles
- Conforms to stringent 100HR salt spray test per the ASTM B117 standard
- Color matched heavy-duty C-shaped mounting bracket is included
- TRX Control WaveGuide high frequency director for vocal and music accuracy and clarity
- SAE 1/4"-20 brass inserts allow easy integration of "off-the-shelf" security hardware
- Available in black or white, in 70.7V and 8 ohm versions
- Five-year manufacturer's warranty

SM42T 4" 8 Ohm/70.7V 2-Way Pair

Includes a 70.7V/100V transformer with screwdriver adjustable tap settings from 2-16 watts for distributed sound applications and a transformer bypass setting for direct coupled 8 ohm applications.



- Specifications:** • Power rating: 30 watts RMS • Impedance: 8 ohms (xfmr. bypassed) • 70.7V taps: 2, 4, 8, 16 watts • Frequency response: 110 Hz-20 kHz • Dimensions (less bracket): 7" H x 5" W x 5-15/16" D • Sold in pairs.

#242-810 (Black - SM42T-B)

#242-812 (White - SM42T-W) .. \$144.00 LIST **\$129.00** (1-5 PRS) **\$123.59** (6 PRS-UP)

SM52 5-1/4" 8 Ohm 2-Way Pair

- Specifications:** • Power rating: 100 watts RMS • Impedance: 8 ohms • Frequency response: 85 Hz-20 kHz • Dimensions (less bracket): 10-3/16" H x 6-7/8" W x 5-7/8" D • Sold in pairs.



#242-814 (Black - SM52-B)

#242-816 (White - SM52-W) .. \$290.00 LIST **\$261.84** (1-5 PRS) **\$248.75** (6 PRS-UP)

SM52T 5-1/4" 70.7V/100V 2-Way Pair

- Specifications:** • Power rating: 30 watts (xfmr. limited) • 70.7V taps: 0.94, 1.9, 3.7, 7.5, 15, 30 watts • Frequency response: 85 Hz-20 kHz • Dimensions (less bracket): 10-3/16" H x 6-7/8" W x 5-7/8" D • Sold in pairs.

#242-818 (Black - SM52T-B)

#242-820 (White - SM52T-W) .. \$324.00 LIST **\$290.90** (1-5 PRS) **\$276.35** (6 PRS-UP)

Atlas Sound SM82 8" 2-Way Surface Mount Speakers

For surface mount applications where increased output and tighter pattern control in an environment-resistant, contemporarily styled enclosure is required, the SM82 series is the perfect choice. System components consist of a highly efficient 8" HYCONE™ treated woofer and 1" exit titanium compression driver. Sold individually.

SM82 8 Ohm Speaker

- Specifications:** • Power rating: 150 watts RMS/225 watts max • Impedance: 8 ohms • Frequency response: 65 Hz-20 kHz • Sensitivity: 92 dB 1W/1m • Dispersion 65° H x 65° V • Dimensions: 16-1/2" H x 9-1/16" W x 8-7/16" D.

#242-822 (Black - SM82-B)

#242-824 (White - SM82-W) \$281.00 LIST **\$252.00** (1-5) **\$239.40** (6-UP)

SM82T 70.7V/100V Speaker

- Specifications:** • Power rating: 60 watts (xfmr. limited) • 70.7V taps: 1.9, 3.8, 7.5, 15, 30, 60 watts • Frequency response: 65 Hz-20 kHz • Sensitivity: 92 dB 1W/1m • Dispersion 65° H x 65° V • Dimensions (less bracket): 16-1/2" H x 9-1/16" W x 8-7/16" D.

#242-826 (Black - SM82T-B)

#242-828 (White - SM82T-W) \$304.00 LIST **\$264.32** (1-5) **\$251.10** (6-UP)

