



Designed specifically for sound contractors, the versatile loading options and a comprehensive feature set make the ISA Series a rugged, cost-effective power solution for any permanently installed sound system. • 25, 70, 100V, and low impedance outputs available simultaneously, allowing a limited number of distributed speakers to be attached to the same amp that is powering the main sound system • XLR and detachable Euro style input connectors • Independent defeatable clip limiters for reduced distortion • Selectable 30 Hz or 70 Hz high-pass filters • Covered barrier strip output connectors for safety agency compliance • Automatic variable-speed rear-to-front fan cooling • Stereo, Bridge, or Parallel operating modes • Complete amplifier and load protection.

Part #	Mfg. #	Watts x 2 @ 8/4/2 ohms	Weight (lbs.)	List Price	Price Each
245-696	ISA 300Ti	185/280/430	44	\$770.00	\$615.00
245-697	ISA 500Ti	260/425/700	49	885.00	710.00
245-698	ISA 800Ti	450/650/1200	57	1,155.00	925.00

QSC PLX2 Series



- Patented PowerLight power supply technology with other patents pending
- Very light weight ("02" models, 21 lbs.; "04" models 13 lbs.)
- Cooling design exhausts hot air out the front, keeping the rack cool
- Front panel LED power, clip, -10 dB, and signal present indicators
- Speakon® NL-4 output connectors provide a positive-locking speaker connection
- 21-position front-panel gain controls for precise, repeatable amplifier adjustment
- Balanced XLR inputs with parallel TRS connectors

Built on the third generation of QSC PowerLight® technology, PLX2 amplifiers combine light weight, superlative audio quality, and proven QSC reliability. With power ratings up to 3,600 watts, PLX2 amplifiers are capable of providing plenty of clean, undistorted output to the most power hungry speaker systems.

Part #	Mfg. #	Watts x 2 @ 8/4/2 ohms	Bridge Mono @ 8/4 ohms	List Price	Price Each
245-632	PLX1104	325/550/ -	-/-	\$899.00	\$699.00
245-634	PLX1804	600/900/ -	-/-	1049.00	799.00
245-636	PLX1802	330/575/900	1,200/1,800	1,199.00	899.00
245-638	PLX2502	450/750/1,250	1,500/2,500	1,329.00	1,029.00
245-640	PLX3102	600/1,000/1,550	2,100/3,100	1,469.00	1,129.00
245-642	PLX3602	775/1,250/1,800	2,600/3,600	1,749.00	1,349.00

QSC GX Series



- Optimized for maximum real-world headroom into 4 ohm and 8 ohm speaker systems
- Inputs: XLR, 1/4" TRS, and phono input connectors
- Outputs: Speakon® combo accepts 1/4" (TS) plugs or Speakon 2-pole and 4-pole plugs (connects 2 poles only); binding posts support all other speaker wiring systems
- Detented gain controls for precise setting and matching of sensitivity
- GuardRail™ automatically protects the amplifier and loudspeakers
- Front panel LEDs monitor Power, Signal, and Clipping

GX Series amplifiers are ideal for professional entertainers who require maximum performance and portability on a limited budget. QSC designers, headed by Pat Quilter, have optimized output and appearance while reducing raw material cost and weight. Dimensions: 3.5" H (2RU) x 19" W x 10.1" D.

Part #	Mfg. #	Watts x 2 @ 8/4 ohms	Weight (lbs.)	List Price	Price Each
245-650	GX3	300/425	25	\$399.00	\$299.00
245-652	GX5	500/700	26	499.00	399.00

QSC RMX Series



The RMX Series amplifiers from QSC offer true professional quality performance at an affordable price. Models range in power from 430 watts to 1200 watts per channel at 2 ohms, all in a compact chassis only 2 rack spaces high and less than 16" deep. All RMX Series amplifiers feature: • 1/4" (6.3 mm) TRS, XLR, and barrier strip balance inputs • Binding post and Neutrik Speakon® outputs • Independent, user-defeatable clip limiters reduce distortion • Selectable low-frequency filters (30 Hz or 50 Hz) protect speakers and increase headroom • Independent DC and thermal overload protection on each channel automatically protect amplifier and speakers • Variable-speed fan cooling with rear-to-front cooling.

Part #	Mfg. #	Watts x 2 @ 8/4/2 ohms	Weight (lbs.)	List Price	Price Each
245-690	RMX850	200/300/430	35	\$465.00	\$369.00
245-692	RMX1450	280/450/700	40	625.00	499.00
245-695	RMX1850HD	360/600/900	45	750.00	599.00
245-694	RMX2450	500/750/1200	45	875.00	699.00

Peavey PV Series



- 2 rack space stereo power amps featuring DDT™ clip protection
- Variable speed fan
- XLR, 1/4", and barrier strip inputs
- Binding post and Speakon® outputs
- Separate Speakon® mono bridge output



All the features and proven reliability. The PV® Series power amplifiers feature Peavey's patented DDT™ distortion detection technique virtually eliminating distortion. They also feature Peavey's patented Turbo-V Cooling™ design, which cools the power transistors more evenly than traditional heatsink designs. Dimensions: 3.5" H x 19" W x 15.5" D.

Part #	Mfg. #	Watts x 2 @ 8/4 ohms	Weight (lbs.)	List Price	Price Each
248-809	PV 900	180/300	40	\$499.99	\$329.99
248-808	PV 1500	300/500	45	649.99	469.99
248-807	PV 2600	540/800	49	899.99	599.99

Peavey CS Series



- Massive toroidal transformer and storage capacitors
- Twin temperature-dependent variable speed fans
- Patented DDT™ soft limiter protects amp and speakers
- RampUp™ Signal Control
- DC voltage, thermal, short circuit and turn on/off protection
- Neutrik® Speakon® and 5-way binding post outputs

Since 1975 the Peavey CS series professional power amps have been delivering solid performance and unsurpassed reliability for which Peavey is famous. With a long history of reliability and now with more power than ever before, these workhorses are giving the pro audio world even more reasons to choose the CS® Series. Dimensions: 3.5" H x 19" W x 17.5" D.

Part #	Mfg. #	Watts x 2 @ 8/4/2 ohms	Weight (lbs.)	List Price	Price Each
248-790	CS 1400	330/500/700	32.7	\$719.99	\$639.99
248-791	CS 2000	490/760/1075	36.3	999.99	799.99
248-793	CS 800X4	180/300/400 (x 4)	38.3	1,099.99	899.99