

# Car Audio

## Amplifiers



### Pyle Dryver High-Performance Amplifiers

- Remote bass level control
- Electronic crossover network (low / full / high)
- Bass boost circuit
- 2 ohm stable and tri-amp capable
- RCA input and output connections
- Power and protection LED indicators
- Red lighting illumination
- Soft turn-on / turn-off
- PLAD 3300D features high efficient Class D design
- One-year manufacturer's warranty



**Specifications:** • Total harmonic distortion (THD): < 0.04% • Signal to noise ratio (S/N): > 90 dB • Input sensitivity: 100 mV~4 V • Channel separation: > 65 dB • Frequency response: 10-30,000 Hz.

Part #	Mfg. #	Power Output (Watts)			Dimensions			List Price	Price Each
		4Ω RMS	2Ω RMS	4Ω Max	Length	Width	Height		
267-750	PLAD212	100 x 2	175 x 2	400 x 2	7"	8-5/8"	2-1/4"	\$141.71	<b>\$79.00</b>
267-752	PLAD213	150 x 2	250 x 2	500 x 2	8-11/16"	8-5/8"	2-1/4"	186.93	<b>99.38</b>
267-754	PLAD214	250 x 2	400 x 2	800 x 2	9-7/8"	8-5/8"	2-1/4"	224.91	<b>128.44</b>
267-756	PLAD215	500 x 2	700 x 2	1,000 x 2	17-11/16"	8-5/8"	2-1/4"	320.37	<b>191.05</b>
267-758	PLAD412	100 x 4	150 x 4	250 x 4	11-3/8"	8-5/8"	2-1/4"	206.01	<b>117.65</b>
267-760	PLAD413	200 x 4	350 x 4	500 x 4	12-5/8"	8-5/8"	2-1/4"	251.37	<b>143.56</b>
267-764	PLAD3300D	600 x 1	1800 x 1	N/R	12-11/16"	8-5/8"	2-1/4"	432.59	<b>257.97</b>

### Pyramid Super Blue Amplifiers



- MOSFET PWM Power Supply
- Built-in bass and treble control
- LED diagnostic condition indicator
- High and low level inputs
- Bridgeable operation (except PB440X and PB442X)
- Thermal, overload, and short circuit protection
- Two-year manufacturer's warranty



**Specifications:** • Total harmonic distortion (THD): < 0.04% • Signal to noise ratio (S/N): > 90 dB, > 85 dB for 35 watt models • Frequency response: 15-30,000 Hz.

Part #	Mfg. #	Power Output (Watts)		Dimensions			List Price	Price Each
		4Ω RMS	4Ω Max	Length	Width	Height		
265-079	PB440X	35 x 2	125 x 2	4-3/4"	10-2/3"	2-1/3"	\$60.85	<b>\$32.00</b>
265-081	PB442X	35 x 4	125 x 4	9-1/16"	10-2/3"	2-1/3"	88.83	<b>46.97</b>
265-083	PB444X	60 x 2	400 x 1	9-1/16"	10-2/3"	2-1/3"	111.85	<b>60.95</b>
265-085	PB446X	70 x 2	600 x 1	12-1/8"	10-2/3"	2-1/3"	134.85	<b>74.25</b>
265-087	PB448X	60 x 4	500 x 2	15-1/3"	10-2/3"	2-1/3"	190.80	<b>102.53</b>
265-089	PB449X	125 x 2	1000 x 1	15-1/3"	10-2/3"	2-1/3"	167.78	<b>92.50</b>

### BOSS Low-Profile Amplified Subwoofers

- Includes powerful built-in amplifier
- Stereo low-level and high-level inputs
- Remote level control
- Soft delay turn-on
- Thermal, short, and overload protection circuits

Amplified subwoofer systems make it easy to get great bass. These enclosures are precision designed and matched to the subwoofer for optimum bass response. Add a powerful built-in amplifier and you have a simple solution for adding "lows" and thump to your system.

**Specifications:** • 0° / 180° phase selector switch • Adjustable input sensitivity: 0.2V ~ 6V • Variable bass boost: 0 ~ +12 dB @ 45 Hz • Subsonic filter: 20 ~ 50 Hz • Low pass filter: 20 ~ 150 Hz.



Part #	Mfg. #	Amplifier Output Power (Watts)		Woofer Diameter	Dimensions			List Price	Price Each
		RMS	Max		Length	Width	Height		
265-346	BASS600	400	600	8"	13.7"	9.8"	2.8"	\$199.00	<b>\$129.00</b>
265-348	BASS1200	800	1,200	10"	15.2"	11.9"	2.8"	239.95	<b>159.00</b>

### Battery Post Terminal Pair

High quality gold plated battery clamp pair. Perfect for upgrading from original factory clamps. Stamped with polarity symbols for easy identification.



#263-610 ..... \$19.99 LIST **\$12.50** (1-3) **\$10.50** (4-UP)

### 4 AWG-8 AWG Distribution Block

Solid brass block with connections for (1) 4 AWG wire input from battery and (4) 8 AWG wire outputs for power to the amplifiers. Recessed set screws hold the wire in place. Brass block is completely insulated with clear plastic to prevent accidental shorting.



#265-800 ..... \$9.99 LIST **\$5.98** (1-3) **\$5.22** (4-UP)