

BOSS Chaos Exxtreme Woofers

One look and you will know why they are called Chaos Exxtreme. The red metallic poly injection cone delivers clear sound while the rubber surround provides smooth response and durability. Features metallic injection cone and 1" aluminum voice coil.



CH10 Chaos 10" Woofer

- Power handling: 200 watts RMS/400 watts peak • Magnet weight: 40 oz.
- Impedance: 4 ohms • Frequency response: 30-4,500 Hz • SPL: 92 dB
- Mounting depth: 3-3/16".

#265-344 \$33.00 LIST **\$21.50 EACH**

CH12 Chaos 12" Woofer

- Power handling: 250 watts RMS/500 watts peak • Magnet weight: 60 oz.
- Impedance: 4 ohms • Frequency response: 25-3,000 Hz • SPL: 94 dB
- Mounting depth: 4-3/4".

#265-342 \$40.00 LIST **\$26.50 EACH**

BOSS Chaos Exxtreme DVC Subwoofers

One look and you will know why they are called Chaos Exxtreme. The red metallic poly injection cone delivers clear sound while the rubber surround provides smooth response and durability. Features metallic injection cone and 1.5" aluminum voice coil.



CH103DVC 10" DVC Subwoofer

- Power handling: 350 watts RMS/700 watts peak
- Magnet weight: 30 oz. • Impedance: dual 4 ohms • Frequency response: 35-2,200 Hz • SPL: 94 dB • Mounting depth: 5-15/16".

#265-340 \$53.00 LIST **\$34.50 EACH**

CH123DVC 12" DVC Subwoofer

- Power handling: 400 watts RMS/800 watts peak • Magnet weight: 40 oz. • Impedance: dual 4 ohms • Frequency response: 28-2,000 Hz
- SPL: 95 dB • Mounting depth: 6-1/8".

#265-338 \$58.00 LIST **\$38.50 EACH**

Dayton Audio Reference Series High Output Subwoofers

- 4-layer high-temperature coils for maximum power handling
- Stiffer suspensions for greater mechanical control
- Heavy-gauge aluminum cones withstand pressures of small enclosures
- Triple shorting-ring motor for ultra-low distortion



RSS265HO-4 10"

Reference HO Subwoofer

- Specifications:** • Power handling: 600 watts RMS/1,000 watts max • VC_{DIA}: 2-1/2" • Le: 1.75 mH • Impedance: 4 ohms • Re: 3.4 ohms • Frequency range: 24-600 Hz • Fs: 24 Hz • SPL: 87 dB 2.83V/1m • V_{AS}: 1.20 cu. ft. • Q_{MS}: 4.20 • Q_{ES}: .36 • Q_{TS}: .33 • X_{MAX}: 12 mm • Dimensions: A: 10-1/2", B: 9-1/4", C: 5".

#295-462 \$163.99 LIST **\$125.79 (1-3) \$119.80 (4-UP)**



RSS315HO-4 12" Reference HO Subwoofer

- Specifications:** • Power handling: 700 watts RMS/1,200 watts max • VC_{DIA}: 2-1/2" • Le: 1.75 mH • Impedance: 4 ohms • Re: 3.4 ohms • Frequency range: 26-600 Hz • Fs: 26 Hz • SPL: 88 dB 2.83V/1m • V_{AS}: 1.62 cu. ft. • Q_{MS}: 4.00 • Q_{ES}: .44 • Q_{TS}: .40 • X_{MAX}: 12 mm • Dimensions: A: 12-3/8", B: 11-1/8", C: 5-3/8".

#295-466 \$179.99 LIST **\$138.24 (1-3) \$131.66 (4-UP)**

RSS390HO-4 15" Reference HO Subwoofer

- Specifications:** • Power handling: 800 watts RMS/1,400 watts max • VC_{DIA}: 2-1/2" • Le: 1.90 mH • Impedance: 4 ohms • Re: 3.3 ohms • Frequency range: 21-600 Hz • Fs: 21 Hz • SPL: 90 dB 2.83V/1m • V_{AS}: 4.60 cu. ft. • Q_{MS}: 4.10 • Q_{ES}: .41 • Q_{TS}: .37 • X_{MAX}: 12 mm • Dimensions: A: 15-5/16", B: 14-1/8", C: 6-1/8".

#295-469 \$207.99 LIST **\$159.80 (1-3) \$151.90 (4-UP)**

Cooustic Crusher Subwoofers

Cooustic Crusher subwoofers provide the best in hard-hitting, head-turning bass. Available in 10" and 12" single voice coil models, Crusher subs handle an impressive 225W RMS power. Cooustic Crusher subs feature the hot new "tribal dragon" logo and look killer in any hardcore install. The all new Crusher subs are designed to be the perfect complement to Power Logic amplifiers.



- Poly cone
- Wide roll, dual layer urethane surround
- 4" voice coil
- Magnet cover
- Extended pole piece



US-CX10-04 10" Subwoofer

- Specifications:** • Power handling: 225 watts RMS/675 watts peak • Impedance: 4 ohms • VC_{DIA}: 4" • Frequency response: 37-150 Hz • Magnet weight: 25 oz. • Fs: 37 Hz • SPL: 87.7 dB 1W/1m • V_{AS}: 1.42 cu. ft. • Q_{TS}: 0.64 • X_{MAX}: 9.5 mm • Dimensions: A: 10.14", B: 9.17", C: 5.4".

#267-918 \$69.95 LIST **\$36.90 EACH**

US-CX12-04 12" Subwoofer

- Specifications:** • Power handling: 225 watts RMS/675 watts peak • Impedance: 4 ohms • VC_{DIA}: 4" • Frequency response: 37-150 Hz • Magnet weight: 25 oz. • Fs: 33 Hz • SPL: 89.4 dB 1W/1m • V_{AS}: 2.89 cu. ft. • Q_{TS}: 0.60 • X_{MAX}: 9.5 mm • Dimensions: A: 12.5", B: 11", C: 6".

#267-920 \$79.95 LIST **\$44.90 EACH**

Quatro™ Subwoofers

- Designed and built in the USA
- Work great in small sealed enclosures
- High sensitivity design
- Large excursion capability
- Five-year manufacturer's warranty



QT210-4 8" Subwoofer

Perfect for truck cab subwoofers!

- Specifications:** • Power handling: 150 watts RMS/300 watts max • VC_{DIA}: 1.5" • Le: 2.2 mH • Impedance: 4 ohms • Re: 3.9 ohms • Frequency range: 35-200 Hz • Fs: 36 Hz • SPL: 89 dB 2.83V/1m • V_{AS}: .82 cu. ft. • Q_{MS}: 8.2 • Q_{ES}: .42 • Q_{TS}: .40 • X_{MAX}: 9.5 mm • Dimensions: A: 8-1/4", B: 7-1/4", C: 4".

#295-545 \$83.99 LIST **\$63.88 (1-3) \$60.83 (4-UP)**



QT255-4 10" Subwoofer

- Specifications:** • Power handling: 200 watts RMS/400 watts max • VC_{DIA}: 2" • Le: 2.0 mH • Impedance: 4 ohms • Re: 3.4 ohms • Frequency range: 30-200 Hz • Fs: 30 Hz • SPL: 92 dB 2.83V/1m • V_{AS}: 1.84 cu. ft. • Q_{MS}: 8.0 • Q_{ES}: .31 • Q_{TS}: .30 • X_{MAX}: 8 mm • Dimensions: A: 10", B: 9", C: 4-3/4".

#295-550 \$123.99 LIST **\$95.23 (1-3) \$90.70 (4-UP)**

QT305-4 12" Subwoofer

- Specifications:** • Power handling: 250 watts RMS/500 watts max • VC_{DIA}: 2-1/2" • Le: 2.5 mH • Impedance: 4 ohms • Re: 3.5 ohms • Frequency range: 25-200 Hz • Fs: 27 Hz • SPL: 94 dB 2.83V/1m • V_{AS}: 4.24 cu. ft. • Q_{MS}: 10.5 • Q_{ES}: .37 • Q_{TS}: .36 • X_{MAX}: 10 mm • Dimensions: A: 12", B: 11", C: 6".

#295-555 \$142.99 LIST **\$115.89 (1-3) \$109.78 (4-UP)**

QT385-4 15" Subwoofer

- Specifications:** • Power handling: 300 watts RMS/600 watts max • VC_{DIA}: 2-1/2" • Le: 3.5 mH • Impedance: 4 ohms • Re: 3.45 ohms • Frequency range: 20-125 Hz • Fs: 21 Hz • SPL: 92 dB 2.83V/1m • V_{AS}: 6.60 cu. ft. • Q_{MS}: 14.0 • Q_{ES}: .42 • Q_{TS}: .41 • X_{MAX}: 10 mm • Dimensions: A: 15-1/8", B: 13-7/8", C: 6-5/8".

#295-560 \$166.99 LIST **\$128.45 (1-3) \$122.33 (4-UP)**