

## MTX Thunder Square DVC Subwoofers



- ALDS Asymmetrical Linear Drive System with a flat progressive spider
- Extended pole piece for smooth, linear, piston-like drive
- Exclusive Spider Plateau Venting cooling system cools at the voice coil
- Available in dual 4 ohm or dual 2 ohm configurations

Introducing the newest addition to the MTX Thunder Woofer family, Thunder Square (TS). Utilizing patented technology (U.S. Patent #7,275,620), TS subwoofers are capable of delivering volume displacement unlike any other in their class. Translated for those of you new to the audio world: these subwoofers are LOUD! With 1.75" voice coils and up to 115 oz. magnets, they are like nothing you've ever heard! TS55 subwoofers rely on a stamped basket and incorporate a painted gloss black metallic polypropylene dust cap with a raised MTX Audio gothic logo.

### TS5510-22 10" Thunder Square Dual 2 Ohm Subwoofer

- Power handling: 450 watts RMS • VC<sub>DIA</sub>: 1.75" • Impedance: 2 ohms per coil
- Re: 0.85 ohms • Magnet weight: 80 oz. • Fs: 37 Hz • Sensitivity: 94.2 dB
- 2.83V/1m • V<sub>AS</sub>: 0.992 cu. ft. • Q<sub>MS</sub>: 8.81 • Q<sub>ES</sub>: 0.81 • Q<sub>TS</sub>: 0.74 • X<sub>MAX</sub>: 15.2 mm
- Dimensions: Overall: 10-5/16", Cutout: 9-1/4", Mounting depth: 6-11/16".

**#293-380** ..... \$299.95 LIST **\$249.95** EACH

### TS5510-44 10" Thunder Square Dual 4 Ohm Subwoofer

- Power handling: 450 watts RMS • VC<sub>DIA</sub>: 1.75" • Impedance: 4 ohms per coil
- Re: 1.69 ohms • Magnet weight: 80 oz. • Fs: 35 Hz • Sensitivity: 91.5 dB
- 2.83V/1m • V<sub>AS</sub>: 1.24 cu. ft. • Q<sub>MS</sub>: 8.32 • Q<sub>ES</sub>: 0.81 • Q<sub>TS</sub>: 0.74 • X<sub>MAX</sub>: 15.2 mm
- Dimensions: Overall: 10-5/16", Cutout: 9-1/4", Mounting depth: 6-11/16".

**#293-381** ..... \$299.95 LIST **\$249.95** EACH

## MTX JackHammer Subwoofers

- FEA optimized roll geometry to maximize excursion without sacrificing cone surface area
- Rubber surround stitched cone for added durability and style
- ALDS Asymmetrical Linear Drive System with a flat progressive spider
- Industry leading thermal power handling using 428° F high-temperature voice coil wire
- Extended pole piece for smooth, linear, piston-like drive
- Spider Plateau Venting cooling system cools at the voice coil



The JackHammers are loaded with features that make them rock. The JH45 subwoofers have a silver stamped basket, rubber magnet cover, and industrial-looking "riveted" dust cap design. The JH55 subwoofer has a black stamped basket for structural strength, a stamped back panel with MTX's aggressive looking Gothic logo, and a large rubber boot creating a powerful looking package that would make even your buddy's install in his '73 Ford Pinto look cool.

### JH4510-04 10" JackHammer 4 Ohm Subwoofer

- Power handling: 200 watts RMS • VC<sub>DIA</sub>: 1.5" • Impedance: 4 ohms • Re: 3.50 ohms • Magnet weight: 48 oz. • Fs: 38.7 Hz • Sensitivity: 90 dB 2.83V/1m
- V<sub>AS</sub>: 1.06 cu. ft. • Q<sub>MS</sub>: 5.32 • Q<sub>ES</sub>: 0.64 • Q<sub>TS</sub>: 0.57 • X<sub>MAX</sub>: 9.4 mm
- Dimensions: Overall diameter: 10-5/16", Cutout diameter: 9-3/16", Mounting depth: 4-7/8".

**#293-360** ..... \$99.95 LIST **\$89.95** EACH

### JH4512-04 12" JackHammer 4 Ohm Subwoofer

- Power handling: 250 watts RMS • VC<sub>DIA</sub>: 1.5" • Impedance: 4 ohms • Re: 3.52 ohms • Magnet weight: 48 oz. • Fs: 31 Hz • Sensitivity: 90.3 dB 2.83V/1m
- V<sub>AS</sub>: 2.49 cu. ft. • Q<sub>MS</sub>: 5.74 • Q<sub>ES</sub>: 0.70 • Q<sub>TS</sub>: 0.62 • X<sub>MAX</sub>: 9.4 mm
- Dimensions: Overall diameter: 12-5/16", Cutout diameter: 11-1/16", Mounting depth: 5-1/2".

**#293-362** ..... \$119.95 LIST **\$99.95** EACH

### JH5512-04 12" JackHammer 4 Ohm Subwoofer

- Power handling: 400 watts RMS • VC<sub>DIA</sub>: 1.75" • Impedance: 4 ohms • Re: 3.45 ohms • Magnet weight: 70 oz. • Fs: 29 Hz • Sensitivity: 90.4 dB 2.83V/1m
- V<sub>AS</sub>: 2.35 cu. ft. • Q<sub>MS</sub>: 5.63 • Q<sub>ES</sub>: 0.57 • Q<sub>TS</sub>: 0.52 • X<sub>MAX</sub>: 13.5 mm
- Dimensions: Overall diameter: 12-5/8", Cutout diameter: 11-1/16", Mounting depth: 6-7/8".

**#293-364** ..... \$179.95 LIST **\$149.95** EACH

## Car Audio Subwoofers



### TS5512-22 12" Thunder Square Dual 2 Ohm Subwoofer

- Power handling: 600 watts RMS • VC<sub>DIA</sub>: 1.75" • Impedance: 2 ohms per coil
- Re: 0.80 ohms • Magnet weight: 115 oz. • Fs: 35.5 Hz • Sensitivity: 97.9 dB
- 2.83V/1m • V<sub>AS</sub>: 2.01 cu. ft. • Q<sub>MS</sub>: 9.42 • Q<sub>ES</sub>: 0.66 • Q<sub>TS</sub>: 0.62 • X<sub>MAX</sub>: 15.2 mm
- Dimensions: Overall: 12-9/16", Cutout: 11", Mounting depth: 7".

**#293-382** ..... \$349.95 LIST **\$299.95** EACH

### TS5512-44 12" Thunder Square Dual 4 Ohm Subwoofer

- Power handling: 600 watts RMS • VC<sub>DIA</sub>: 1.75" • Impedance: 4 ohms per coil
- Re: 1.65 ohms • Magnet weight: 115 oz. • Fs: 34 Hz • Sensitivity: 95 dB
- 2.83V/1m • V<sub>AS</sub>: 2.39 cu. ft. • Q<sub>MS</sub>: 5.67 • Q<sub>ES</sub>: 0.64 • Q<sub>TS</sub>: 0.58 • X<sub>MAX</sub>: 15.2 mm
- Dimensions: Overall: 12-9/16", Cutout: 11", Mounting depth: 7".

**#293-383** ..... \$349.95 LIST **\$299.95** EACH

## MTX Thunder Thin Subwoofers

Many vehicles today have limited space, and having a large enclosure to get the bass you want may not fit into your lifestyle. Introducing Thunder Thin series subwoofers, the next evolution in the MTX subwoofer lineup. Measuring only 3-3/8" deep, these subwoofers will fit anywhere, so if you want to get an extreme amount of bass from a very small space (like a door), then TT65 subwoofers are the solution for you. Available in 10" and 12" sizes, in single 2 ohm or single 4 ohm configurations.



### TT6510-02 10" Thunder Thin 2 Ohm Subwoofer

- Power handling: 300 watts RMS • VC<sub>DIA</sub>: 1.75" • Impedance: 2 ohms
- Re: 1.67 ohms • Magnet weight: 53 oz. • Fs: 28.7 Hz • Sensitivity: 89.95 dB 2.83V/1m • V<sub>AS</sub>: 1.33 cu. ft. • Q<sub>MS</sub>: 6.42 • Q<sub>ES</sub>: 0.68 • Q<sub>TS</sub>: 0.62 • X<sub>MAX</sub>: 12.7 mm
- Dimensions: Overall diameter: 10-5/16", Cutout diameter: 9-1/8", Mounting depth: 3-3/8".

**#293-385** ..... \$229.95 LIST **\$199.95** EACH

### TT6510-04 10" Thunder Thin 4 Ohm Subwoofer

- Power handling: 300 watts RMS • VC<sub>DIA</sub>: 1.75" • Impedance: 4 ohms
- Re: 3.78 ohms • Magnet weight: 53 oz. • Fs: 30.5 Hz • Sensitivity: 85.34 dB 2.83V/1m • V<sub>AS</sub>: 1.21 cu. ft. • Q<sub>MS</sub>: 6.45 • Q<sub>ES</sub>: 0.95 • Q<sub>TS</sub>: 0.83 • X<sub>MAX</sub>: 12.7 mm
- Dimensions: Overall diameter: 10-5/16", Cutout diameter: 9-1/8", Mounting depth: 3-3/8".

**#293-386** ..... \$229.95 LIST **\$199.95** EACH

### TT6512-02 12" Thunder Thin 2 Ohm Subwoofer

- Power handling: 400 watts RMS • VC<sub>DIA</sub>: 1.75" • Impedance: 2 ohms
- Re: 1.73 ohms • Magnet weight: 65 oz. • Fs: 25.53 Hz • Sensitivity: 90.5 dB 2.83V/1m • V<sub>AS</sub>: 2.74 cu. ft. • Q<sub>MS</sub>: 4.74 • Q<sub>ES</sub>: 0.84 • Q<sub>TS</sub>: 0.71 • X<sub>MAX</sub>: 12.7 mm
- Dimensions: Overall diameter: 12-5/8", Cutout diameter: 11-1/16", Mounting depth: 3-3/8".

**#293-387** ..... \$249.95 LIST **\$219.95** EACH

### TT6512-04 12" Thunder Thin 4 Ohm Subwoofer

- Power handling: 400 watts RMS • VC<sub>DIA</sub>: 1.75" • Impedance: 4 ohms
- Re: 3.33 ohms • Magnet weight: 65 oz. • Fs: 26.32 Hz • Sensitivity: 87.63 dB 2.83V/1m • V<sub>AS</sub>: 2.65 cu. ft. • Q<sub>MS</sub>: 4.64 • Q<sub>ES</sub>: 0.90 • Q<sub>TS</sub>: 0.76 • X<sub>MAX</sub>: 12.7 mm
- Dimensions: Overall diameter: 12-5/8", Cutout diameter: 11-1/16", Mounting depth: 3-3/8".

**#293-388** ..... \$249.95 LIST **\$219.95** EACH