

Pioneer TS-T15 3/4" Tweeter Pair

- Polyester fiber soft dome
- Neodymium magnet • Surface or flush mount capabilities
- Includes two in-line 6 dB crossovers • Impedance: 4 ohms • Frequency response: 2,500-30,000 Hz • SPL: 90 dB 1W/1m • Power handling: 40 watts RMS/120 watts max • Hole size: 1-3/4" dia. x 5/8" deep.

Pioneer



#267-288 \$75.00 LIST **\$42.87** PAIR

Pioneer TS-T110 7/8" Hard Dome Tweeter Pair

- Strontium magnet • Surface or flush mount capabilities
- In-line 6 dB crossover
- Impedance: 4 ohms
- Frequency response: 2,500-30,000 Hz • SPL: 90 dB 1W/1m • Power handling: 40 watts RMS/120 watts max • Hole size: 2" dia. x 3/4" deep.



#267-286 \$55.00 LIST **\$32.47** PAIR

MTX TX1000 1" Tweeter Pair

- Soft dome flush, surface, or angle mounted • Includes two 12 dB optimized high-pass filters • Impedance: 4 ohms
- Frequency response: 2,500-20,000 Hz • SPL: 90 dB 1W/1m
- Power handling: 50 watts RMS/100 watts max • Hole size: 1-7/8" dia. x 1" deep.

MTX
AUDIO



#267-650 **\$89.95** PAIR

Pyle PLST6 1/2" Tweeter Pair

- Mylar dome • Neodymium magnet
- Can be flush, swivel or surface mounted • Includes two 12 dB high-pass filters • Impedance: 4 ohms • Frequency response: 1,300-22,000 Hz • SPL: 92 dB 1W/1m • Power handling: 75 watts RMS/150 watts max • Hole size: 1-3/4" dia. x 1" deep.

PYLE



#267-748 \$24.99 LIST **\$11.29** PAIR

Pyramid TW22N 1" Tweeter Pair

PYRAMID

- Silk dome • Neodymium magnet
- 1" high temperature, ferrofluid cooled voice coil • Surface mount with adjustable firing angle • Includes two 6 dB crossovers • Impedance: 4 ohms • Frequency response: 2,000-20,000 Hz • SPL: 90 dB 1W/1m
- Power handling: 60 watts RMS/95 watts • 1-3/4" dia. x 1-1/2" deep.



#265-263 **\$14.60** (1-3 PRS) **\$12.88** (4 PRS-UP)

Goldwood GT-221 1" Tweeter Pair

goldwood

- Mylar dome • Neodymium magnet • 220° surface swivel mount included • Impedance: 4 ohm
- Frequency response: 3,000-20,000 Hz • SPL: 90 dB • Power handling: 50 watts RMS/100 watts max • 2" dia. x 3/4" H.



#270-013 **\$11.44** PAIR

Mini Extension Speaker

Mini speaker for small stereos, CBs, police scanners, or ham radios that have a 3.5 mm output jack. Includes mounting bracket and 6 ft. of cable. 8 ohm impedance. 15 watts max. Dimensions: 3-3/16" H x 3-3/16" W x 2-1/4" D.

PYRAMID



#265-242 **\$5.90** (1-3) **\$5.45** (4-UP)

XTC Waterproof Foam Baffles

The perfect solution to baffling auto door and rear deck speakers.

These units also protect door speakers from water and dust.

XTC foam is specially designed to withstand

extreme temperatures and will not rot, disintegrate, or sponge up water. Flexible construction will fit almost any application. Sold in pairs.



Part #	Description	Depth	Price (1-9)	Price (10-UP)
260-780	3" round	2-3/4"	\$6.25	\$5.65
260-782	4" round	3-7/8"	7.60	6.95
260-784	4" x 10" oval	4-1/2"	9.50	8.75
260-786	5-1/4" round	3-7/8"	7.90	7.50
260-788	6-1/2" round	4-1/2"	9.50	8.80
260-790	6" x 9" oval	4-1/2"	9.95	9.25
260-792	8" round	6"	10.75	9.50
260-794	10" round	6"	15.55	13.40
260-795	12" round	6-1/4"	16.75	14.70

2-Piece Mesh Grills

Very convenient and fast way to put grills on auto speakers and P.A.

equipment. 2-piece construction allows you to mount ring and woofer

with one set of screws and snap grill over entire assembly. Installed screws are not visible. Sold individually. Heavy duty expanded steel mesh design.



Part #	Speaker Size	Price (1-9)	Price (10-49)	Price (50-UP)
260-420	5-1/4"	\$4.50	\$3.95	\$3.15
260-418	6"	4.85	4.25	3.59
260-422	6-1/2"	4.95	4.50	4.03
260-424	8"	6.90	6.20	4.97
260-426	10"	10.25	9.26	7.53
260-428	12"	12.50	11.90	10.50
260-430	15"	17.00	15.35	14.01

Bass Stoppers™ Speaker Protectors

The Bass Stoppers are designed to prevent damaging low frequencies from reaching automotive midrange and high frequency drive units. Improves sound quality by lowering distortion levels. Just splice the Bass Stopper into speaker positive lead. For use with both 4 and 8 ohm speakers. 6 dB/octave.

BASS STOPPER™



Part #	Power Handling	Frequency Blocked 4 ohm	Frequency Blocked 8 ohm	Price (1-3)	Price (4-UP)
266-200	75 watts	0-300 Hz	0-150 Hz	\$2.95	\$2.65
266-205	150 watts	0-600 Hz	0-300 Hz	2.95	2.65
266-210	150 watts	0-800 Hz	0-400 Hz	2.95	2.65
266-215	150 watts	0-1.2 kHz	0-600 Hz	2.95	2.65
266-220	150 watts	0-2.8 kHz	0-1.4 kHz	2.95	2.65
266-225	150 watts	0-5.6 kHz	0-2.8 kHz	2.95	2.65