

Parts Express is proud to offer a new expanded range of genuine Morel Israel products. Their tweeters have long been staple products here at Parts Express, and are some of the best and most popular soft dome tweeters available. Morel strives to produce not only the highest quality, but also the best sounding products. Find more information on Morel's new products going at parts-express.com and select Morel from the "search by brand" drop down box.

NEW



The Elite tweeters and dome midrange are based on the MDT 33, MDT44 and MDM55 unique qualities. They feature IDR™ (Improved Dispersion Recess), improved magnets, and aluminum faceplates. Additionally, the tweeters feature a high quality oven coating and are available in 110 mm, 104 mm and 72 mm faceplate diameters. The Elite midrange line's newest novelty consists of a 2.1" soft dome constructed in a 130 mm faceplate.

- IDR™ (Improved Dispersion Recess)
- Large Hexatech aluminum voice coil
- High power handling
- Gold plated terminals

NEW

ET338 Hand-Coated Soft Dome Tweeters

- Replaceable Accuflex™ diaphragm
- Triple magnet system

Specifications: • Power handling: 200 watts RMS/1,000 watts max • VCDIA: 1-1/8" • Impedance: 8 ohms • Re: 5.2 ohms • Frequency range: 1,800-20,000 Hz • Fs: 700 Hz • SPL: 92.5 dB 1W/1m • Dimensions: A: 4-1/3" (4-1/8" for ET338-104), B: 3", C: 2-5/8" • Replacement diaphragm #277-019.



#277-070 (ET338 110mm faceplate)

#277-072 (ET338-104 104mm faceplate) . . . \$169.99 LIST **\$144.10** (1-3) **\$137.30** (4-UP)

ET448 Soft Dome Tweeter

- Replaceable Accuflex™ diaphragm
- Double neodymium magnet system
- Ferrofluid cooled

Specifications: • Power handling: 120 watts RMS/1,000 watts max • VCDIA: 1-1/8" • Impedance: 8 ohms • Re: 5.2 ohms • Frequency range: 2,200-20,000 Hz • Fs: 750 Hz • SPL: 92 dB 1W/1m • Dimensions: A: 2-7/8", B: 1-3/4", C: 2-5/16" • Replacement diaphragm #277-075.



#277-074 \$119.99 LIST **\$104.30** (1-3) **\$99.40** (4-UP)

EM1308 2.1" Neodymium Soft Dome Midrange

- 2.1" Accuflex™ hand coated soft dome
- Internally damped, aluminum rear chamber

Specifications: • Power-handling: 120 watts RMS/1000 watts max • VCDIA: 1-1/8" • Impedance: 8 ohms • Re: 5.2 ohms • Frequency range: 500-5,000 Hz • Fs: 320 Hz • SPL: 88 dB 1W/1m • Dimensions: A: 5-1/8", B: 3", C: 3-3/16" • Replacement diaphragm #277-075.



#287-030 \$159.99 LIST **\$139.70** (1-3) **\$133.00** (4-UP)

EM428 4" DPC Cone Midrange

- Uniflow™ steel chassis
- Neodymium magnet system
- Shallow profile DPC cone

Specifications: • Power handling: 150 watts RMS/800 watts max • VCDIA: 2.1" • Impedance: 8 ohms • Re: 5.4 ohms • Frequency range 50-5,000 Hz • Fs: 320 Hz • SPL: 87 dB 1W/1m • VAS: .12 cu. ft. • QMS: 3.03 • QES: .48 • QTS: .41 • XMAX: 3 mm • Dimensions: A: 4-2/3", B: 3-3/4", C: 2-1/4".



#287-032 \$149.99 LIST **\$126.67** (1-3) **\$120.64** (4-UP)

Speaker Building

Drivers

The Classic Advanced line is based on Morel's classic line - the renowned MW series and the famous MDT lines. The woofers feature higher power handling due to the aerodynamic Uniflow™ open chassis, a double magnet system, and lower resonance frequency.

- Uniflow™ steel chassis
- Large Hexatech aluminum voice coil
- High-flux ferrite double magnet system
- Shallow profile DPC cone
- High power handling

NEW

CAW-428 4" Woofer

Specifications: • Power handling: 150 watts RMS/800 watts max • VCDIA: 3" • Le: .32 mH • Impedance: 8 ohms • Re: 5.5 ohms • Frequency range: 45-3,000 Hz • Fs: 74 Hz • SPL: 88 dB 1W/1m • VAS: .16 cu. ft. • QMS: 2.33 • QES: .46 • QTS: .38 • XMAX: 4 mm • Dimensions: A: 4-5/8", B: 4-11/16", C: 2".



#297-080 \$119.99 LIST **\$92.21** (1-3) **\$87.82** (4-UP)

CAW-528 5" Woofer

Specifications: • Power handling: 150 watts RMS/1,000 watts max • VCDIA: 3" • Le: .47 mH • Impedance: 8 ohms • Re: 5.2 ohms • Frequency range: 35-3,500 Hz • Fs: 49 Hz • SPL: 86 dB 1W/1m • VAS: .29 cu. ft. • QMS: 1.83 • QES: .48 • QTS: .38 • XMAX: 3 mm • Dimensions: A: 5-1/16", B: 4-3/4", C: 2-9/16".



#297-082 \$129.99 LIST **\$108.98** (1-3) **\$103.79** (4-UP)

CAW-638 6" Woofer

• 3" Hexatech™ aluminum voice coil
Specifications: • Power handling: 150 watts RMS/1,000 watts max • VCDIA: 3" • Le: .63 mH • Impedance: 8 ohms • Re: 6.4 ohms • Frequency range: 30-5,000 Hz • Fs: 43 Hz • SPL: 86 dB 1W/1m • VAS: .56 cu. ft. • QMS: 2.20 • QES: .58 • QTS: .46 • XMAX: 4.25 mm • Dimensions: A: 6-5/16", B: 5-1/2", C: 2-3/4".



#297-084 \$129.99 LIST **\$117.94** (1-3) **\$112.32** (4-UP)

CAW-938 9" Woofer


Specifications: • Power handling: 150 watts RMS/1,000 watts max • VCDIA: 3" • Le: .61 mH • Impedance: 8 ohms • Re: 6.4 ohms • Frequency range: 20-3,000 Hz • Fs: 31 Hz • SPL: 87 dB 1W/1m • VAS: 2.00 cu. ft. • QMS: 2.59 • QES: .80 • QTS: .60 • XMAX: 4.25 mm • Dimensions: A: 8-3/4", B: 7-13/16", C: 3".



#297-086 \$149.99 LIST **\$131.04** (1-3) **\$124.80** (4-UP)

Speaker Sealing Caulk

Special rubber compound quickly and easily seals speakers into cabinets. Eliminates vibration and air leaks. Sold in 1/4" x 36" strips.



Strips are self-adhesive so they stick easily to speaker frame.

#269-300 **98¢** (1-9) **75¢** (10-UP)