

Size	Manufacturer	Model	Imp. Ohms	Frequency Response (Hz)	VC Dia.	Power Handling RMS (W)	SPL 1W/1m (dB)	Xmax (mm)	Fs (Hz)	Vas (cu. ft.)	Qts.	Suggested Vented Box cu. ft.	PE #	Page #
12"	Pyle Pro	PYM1255	8	35-2,500	2"	300	95.4	2.4	51.1	4.39	0.64	3.00 Sealed	292-230	WEB
12"	Pyle Pro	PYM1278	8	55-5,000	2.5"	400	96.5	1.8	62	2.11	0.48	2.5	292-232	218
12"	Pyle Pro	PYM1298	8	40-4,000	3"	600	97.8	3.2	46.9	4.02	0.28	2.5	292-234	WEB
12"	Selenium	12PW3-SLF	8	55-5,000	1.75"	200	97	1.3	50	3.42	0.69	2.75 Sealed	264-334	216
12"	Selenium	12PW5-SLF	8	50-4,000	3"	300	96	3.5	42	3.81	0.31	3	264-370	217
12"	Selenium	12WS600	8	45-3,000	4"	600	95	4.3	46	2.11	0.34	4	264-391	217
15"	B&C	15HPL76W	8	40-2,000	3"	350	97	6	38	5.5	0.41	4	294-662	WEB
15"	B&C	15NDL76	8	40-2,000	3"	500	99.5	7	37	6.8	0.22	3.5	294-683	214
15"	B&C	15PL100	8	35-2,000	4"	700	97	7	37	5.4	0.2	4	294-669	WEB
15"	B&C	15PS100	8	35-1,000	4"	700	94.5	8	33	5.3	0.31	4.5	294-673	213
15"	B&C	15PS76	8	40-2,000	3"	550	99	7.5	38	5.7	0.26	4	294-667	213
15"	B&C	15PZB100	8	40-2,000	4"	700	97	8	39	3.8	0.29	4	294-671	213
15"	B&C	15TBX100	8	35-1,500	4"	1,000	96	9	35	3.9	0.28	4.5	294-670	213
15"	Dayton	PF385-8	8	35-2,000	4"	500	97	6	36	7.04	0.37	4.75	295-080	219
15"	Electro-Voice	EVX-155	8	30-1,800	4"	1,000	98	6.4	35.4	7.77	0.21	5	294-560	214
15"	Eminence	Alpha-15A	8	46-3,500	1.5"	200	97	3.8	41	9.2	1.26	4.50 Sealed	290-407	208
15"	Eminence	Beta-15A	8	45-3,700	2"	300	98.2	4	35	11.8	0.58	4	290-410	209
15"	Eminence	Definimax 4015LF	8	35-1,200	4"	700	96	9	42	4.1	0.5	3.8	290-578	208
15"	Eminence	Delta Pro-15A	8	54-4,200	2.5"	400	101.6	4.3	42	8.6	0.4	4	290-512	209
15"	Eminence	Delta-15A	8	40-4,000	2.5"	400	100	2.7	40	9.6	0.53	5	290-418	210
15"	Eminence	Delta-15B	16	64-4,000	2.5"	400	100	1.6	45	7.2	0.61	5	290-419	210
15"	Eminence	Delta-15LFA	8	42-3,200	2.5"	500	96	4.8	41	6.6	0.58	5	290-417	210
15"	Eminence	Deltalite II 2515	8	54-3,700	2.5"	300	99.2	4.8	42	7.2	0.38	3.9	290-595	212
15"	Eminence	Gamma-15A-2	8	48-3,300	2"	300	98.6	3	33	11.1	0.3	4.5	290-454	208
15"	Eminence	Kappa Pro-15A	8	46-4,000	3"	500	101	3.2	47	5.9	0.38	4	290-422	211
15"	Eminence	Kappa Pro-15LF-2	8	38-1,800	3"	600	97.8	6.7	35	6.1	0.31	5	290-420	211
15"	Eminence	Kappa-15A	8	52-2,300	3"	450	100.5	4	33	11.35	0.32	3.5	290-458	210
15"	Eminence	Kappa-15C	4	63-2,800	3"	450	98.1	2.4	31	11.7	0.25	3.5	290-459	210
15"	Eminence	Kappa-15LFA	8	38-2,700	3"	600	99	5.5	39	5.6	0.38	3.9	290-460	210
15"	Eminence	Kappalite 3015	8	40-4,000	3"	450	100.8	5.9	45	5.4	0.34	4.8	290-597	212
15"	Eminence	Kappalite 3015LF	8	40-1,500	3"	450	99.8	9.6	42	5.6	0.39	6.1	290-598	212
15"	Eminence	Kilomax-15A	8	44-800	4"	1,250	95.5	7.9	41	5.5	0.39	6	290-436	212
15"	Eminence	Omega Pro-15A	8	51-1,700	4"	800	97.3	4.8	33	9.1	0.32	5	290-430	211
15"	Goldwood	GW-15120	8	50-2,000	4"	600	96	5.4	46	3.82	0.43	4	290-397	219
15"	Goldwood	GW-1538/PA	8	45-3,000	1.5"	140	91	3.3	41	6.36	1.36	5.00 Sealed	290-394	220
15"	Goldwood	GW-1558	8	31-2,500	2.5"	200	95.6	3.9	31	14.19	0.63	3.00 Sealed	290-384	220
15"	JBL	2226H	8	30-2,500	4"	600	97	7.6	40	6.2	0.31	5	294-470	215
15"	Peavey	15" Low Rider	8	30-1,000	4"	800	93.6	9.6	33.92	5.48	0.35	3	294-303	215
15"	Peavey	1508-8 CU BWX	8	40-2,000	4"	500	97.2	4.7	36.7	7.05	0.29	3	294-309	WEB
15"	Peavey	1508-8 CU CP Pro Rider	8	35-2,000	4"	600	97.9	4.6	34.8	7.34	0.24	3	294-305	215
15"	Peavey	1508-8 HE DWX	8	40-2,000	4"	500	100.3	1.9	51.2	6.44	0.34	4	294-311	WEB
15"	Peavey	Scorpion SP-1525	8	40-2,000	2.5"	200	98.7	3.1	50.1	4.68	0.33	4.00 Sealed	294-313	215
15"	Pyle	PPA15	8	27-4,000	2.5"	250	90.2	6	26.7	11.36	0.67	3.50 Sealed	292-218	218
15"	Pyle Pro	PYM 15128	8	40-4,000	4"	600	96.6	5.5	43.4	5.45	0.4	4.5	292-240	218
15"	Pyle Pro	PYM 1555	8	40-4,000	2"	300	95.8	4.6	41.2	9.35	0.69	5.00 Sealed	292-236	WEB
15"	Pyle Pro	PYM 1578	8	40-4,000	2.5"	400	97.5	2.7	40.3	10.35	0.49	6	292-238	218
15"	Selenium	15PW3-SLF	8	40-4,000	2.5"	250	98	3	37	9.67	0.61	6	264-338	216
15"	Selenium	15PW5-SLF	8	40-3,000	3"	350	97	5.7	40	6.71	0.4	5	264-375	217
15"	Selenium	15SWS800	8	35-1,500	4"	800	93	6.5	37	3.44	0.37	4	264-388	216
15"	Selenium	15WS600	8	40-3,500	4"	600	97	3.75	35	7.59	0.35	6	264-393	217
15"	Selenium	WPU1507QCF-SLF	8	45-3,500	4"	500	96	4.3	36	5.33	0.43	5	264-425	217
15"	Selenium	WPU1509-SLF	8	40-3,500	4"	450	97	3.75	36	5.75	0.35	5	264-345	216
18"	B&C	18PS76	8	40-2,000	3"	600	99	7	39	7.2	0.27	8	294-675	214
18"	B&C	18PZB100	8	40-2,000	4"	700	97	8	30	5.5	0.24	4.5	294-677	214
18"	B&C	18TBX100	8	35-1,000	4"	1,000	97	10	34	7.5	0.35	8	294-676	214
18"	Dayton	PF460-8	8	25-1,500	4"	500	97	6	25	16.12	0.34	7.5	295-085	219
18"	Electro-Voice	EVX-180B	8	20-2,000	4"	1,000	98	6.4	29	14.7	0.27	9	294-565	214
18"	Eminence	Definimax 4018LF	8	36-200	4"	800	95	7.9	32	8.4	0.35	6.8	290-579	208
18"	Eminence	Kilomax-18A	8	33-600	4"	1,250	95.5	9.8	33	8.5	0.56	7	290-434	212
18"	Eminence	Omega Pro-18A	8	40-800	4"	800	97	4.8	25	19.4	0.31	8	290-428	211
18"	Eminence	Omega Pro-18C	4	40-800	4"	800	96.4	4.8	23	22.6	0.28	8	290-429	211
18"	Eminence	Sigma Pro-18A-2	8	41-2,400	3"	650	99	6.1	28	15.6	0.29	8	290-427	210
18"	Goldwood	GW-18120	8	40-1,500	4"	600	95.5	5.4	38	7.67	0.57	8	290-398	219
18"	Goldwood	GW-1858	8	30-2,000	2.5"	220	94.2	3.4	30	18.5	1.07	6.00 Sealed	290-386	220
18"	JBL	2241H	8	30-3,000	4"	600	98	7.6	35	11	0.4	8	294-460	215
18"	Peavey	18" Low Rider	8	25-1,000	4"	800	97.3	9.6	28.9	14.26	0.34	6.75	294-301	215
18"	Peavey	1808 CU BWX	8	35-1,000	4"	500	97.7	4.6	35.1	11.04	0.34	5	294-307	215
18"	Pyle Pro	PYM18128	8	40-4,000	4"	600	96.7	5.5	27.4	14.9	0.28	9	292-244	218
18"	Pyle Pro	PYM1878	8	40-4,000	2.5"	400	96.3	3.7	29	20.3	0.45	8	292-242	WEB
18"	Selenium	18SWS1100	8	30-2,500	4"	1,100	97	9.3	39	7.48	0.48	5.5	264-396	WEB
18"	Selenium	18SWS800	8	30-1,500	4"	800	96	6.5	32	8.09	0.41	5	264-387	216
18"	Selenium	18WS600	8	35-3,000	4"	600	98	3.75	35	11.2	0.46	8	264-394	217
18"	Selenium	WPU1807QCF-SLF	8	45-3,500	4"	500	96	4.3	31	11.23	0.48	8	264-430	217
18"	Selenium	WPU1809-SLF	8	35-3,000	4"	450	98	3.75	33	11.58	0.45	8	264-347	216