

Pro Sound

Speakers, Drivers & Horns

Eminence Kappalite™ 450W Neodymium Woofers

- Neodymium magnet structure delivers incredible performance without the weight
- Die-cast aluminum basket/heatsink with vented core
- Copper voice coil with polyimide former
- Paper cone with solid composition paper dust cap and cloth cone edge



Kappalite™ 3015 15" Neo Woofer

Recommended for vented professional audio enclosures for full-range or as mids.

- Specifications:** • Power handling: 450 watts RMS/900 watts max • VC_{DIA}: 3" • Le: 0.64 mH • Impedance: 8 ohms • Re: 5.27 ohms • Frequency range: 40-4,000 Hz • Magnet weight: 11 oz. • Fs: 45 Hz • Sensitivity: 100.8 dB 1W/1m • V_{AS}: 5.4 cu. ft. • Q_{MS}: 6.70 • Q_{ES}: 0.36 • Q_{TS}: 0.34 • X_{MAX}: 5.9 mm • Dimensions: A: 15.32", B: 14", C: 6.8".

#290-597 \$184.99 LIST **\$179.97** EACH

Kappalite™ 3015LF 15" Neo Woofer

Recommended for professional audio and bass in a vented enclosure.

- Specifications:** • Power handling: 450 watts RMS/900 watts max • VC_{DIA}: 3" • Le: 0.92 mH • Impedance: 8 ohms • Re: 5.31 ohms • Frequency range: 40-1,500 Hz • Magnet weight: 11 oz. • Fs: 42 Hz • Sensitivity: 99.8 dB 1W/1m • V_{AS}: 5.6 cu. ft. • Q_{MS}: 6.82 • Q_{ES}: 0.41 • Q_{TS}: 0.39 • X_{MAX}: 9.6 mm • Dimensions: A: 15.32", B: 14", C: 7.25".

#290-598 \$184.99 LIST **\$179.97** EACH

Eminence Kilomax Pro Series

- Ferrite magnet
- Die-cast aluminum basket
- Paper cone
- Cloth accordion cone edge
- Kilomax alloy heatsink
- For esoteric high power bass applications



Kilomax-15A 1,250W Driver

Recommended for professional audio subwoofer and woofer applications in vented enclosures.

- Specifications:** • Power handling: 1,250 watts RMS/2,500 watts max • VC_{DIA}: 4" • Le: 1.78 mH • Impedance: 8 ohms • Re: 4.97 ohms • Frequency range: 44-800 Hz • Magnet weight: 109 oz. • Fs: 41 Hz • SPL: 95.5 dB 1W/1m • V_{AS}: 5.5 cu. ft. • Q_{MS}: 8.80 • Q_{ES}: 0.40 • Q_{TS}: 0.39 • X_{MAX}: 7.9 mm • Dimensions: A: 15.21", B: 14", C: 6.42".

#290-436 \$289.99 LIST **\$269.97** EACH

Kilomax-18A 1,250W Driver

Recommended for professional audio subwoofer and woofer applications in sealed and vented enclosures. Not for horn-loading or scoops.

- Specifications:** • Power handling: 1,250 watts RMS/2,500 watts max • VC_{DIA}: 4" • Le: 2.38 mH • Impedance: 8 ohms • Re: 5.84 ohms • Frequency range: 33-600 Hz • Magnet weight: 109 oz. • Fs: 33 Hz • SPL: 95.5 dB 1W/1m • V_{AS}: 8.5 cu. ft. • Q_{MS}: 14.24 • Q_{ES}: 0.58 • Q_{TS}: 0.56 • X_{MAX}: 9.8 mm • Dimensions: A: 18", B: 16.56", C: 8.15".

#290-434 \$329.99 LIST **\$299.97** EACH



Eminence Deltalite® II Neodymium Woofers

- Neodymium magnet structure delivers all the performance without the weight
- Die-cast aluminum basket/heatsink with vented core
- Aluminum voice coil with polyimide former
- Paper cone with solid composition paper dust cap and cloth cone edge

Recommended for professional audio as a mid/hi or full-range and monitor; also for bass guitar. Works well in sealed or vented enclosures.

Deltalite® II 2510 10" Neo Woofer

- Specifications:** • Power handling: 250 watts RMS/600 watts max • VC_{DIA}: 2.5" • Le: 0.40 mH • Impedance: 8 ohms • Re: 5.06 ohms • Frequency range: 60-4,000 Hz • Magnet weight: 7 oz. • Fs: 53 Hz • Sensitivity: 97.3 dB 1W/1m • V_{AS}: 1.9 cu. ft. • Q_{MS}: 5.76 • Q_{ES}: 0.45 • Q_{TS}: 0.42 • X_{MAX}: 4.2 mm • Dimensions: A: 10.25", B: 9.15", C: 4.9".



#290-591 \$119.99 LIST **\$109.97** EACH

Deltalite® II 2512 12" Neo Woofer

- Specifications:** • Power handling: 250 watts RMS/600 watts max • VC_{DIA}: 2.5" • Le: 0.46 mH • Impedance: 8 ohms • Re: 5.04 ohms • Frequency range: 48-4,000 Hz • Magnet weight: 7 oz. • Fs: 37 Hz • Sensitivity: 99.9 dB 1W/1m • V_{AS}: 5.2 cu. ft. • Q_{MS}: 3.13 • Q_{ES}: 0.44 • Q_{TS}: 0.39 • X_{MAX}: 4.9 mm • Dimensions: A: 12.38", B: 11.06", C: 6.06".



#290-593 \$124.99 LIST **\$119.97** EACH

Deltalite® II 2515 15" Neo Woofer

- Specifications:** • Power handling: 300 watts RMS/600 watts music program • VC_{DIA}: 2.5" • Le: 1.15 mH • Impedance: 8 ohms • Re: 5.29 ohms • Frequency range: 54-3,700 Hz • Magnet weight: 7 oz. • Fs: 42 Hz • Sensitivity: 99.2 dB 1W/1m • V_{AS}: 7.2 cu. ft. • Q_{MS}: 4.56 • Q_{ES}: 0.41 • Q_{TS}: 0.38 • X_{MAX}: 4.8 mm • Dimensions: A: 15.32" B: 14", C: 6.81".



#290-595 \$129.99 LIST **\$124.97** EACH

Eminence Line Array Series

With a truncated basket designed to minimize acoustical center spacing and modeling specific to arrays, this model will prove to be perfect for anyone interested in line array technology.

LA6-CBMR 6-1/2" Sealed Back Midrange

Recommended for professional audio midrange from 500 Hz-3 kHz. Basket is closed.

- Specifications:** • Power handling: 150 watts RMS • VC_{DIA}: 1.5" • Le: 0.33 mH • Impedance: 8 ohms • Re: 6.3 ohms • Frequency range: 500-5,400 Hz • Magnet weight: 38 oz. • Fs: 460 Hz • SPL: 97.8 dB • V_{AS}: 0.01 cu. ft. • Q_{MS}: 3.13 • Q_{ES}: 1.24 • Q_{TS}: 0.89 • X_{MAX}: 0.2 mm • Dimensions: Overall diameter: 6.59"; Width across flats: 6"; Baffle hole diameter: 5.65"; Depth: 2.77".



#290-542 \$54.99 LIST **\$49.97** EACH