

Selenium ST350 Super Tweeter

- ABS housing
- Durable phenolic diaphragm
- Well-controlled 50° conical dispersion
- High temperature adhesives and materials for increased power handling

Very efficient super tweeter designed to be used in high-frequency sound reinforcement. Recommended for large rooms, clubs, auditorium, theaters, and any other environment requiring smooth, well-controlled high frequency response.



Specifications: • Power handling: 75 watts RMS/150 watts program (above 5,000 Hz) • Dispersion: 50° H x 50° V • VC_{DIA}: 1.6" • Impedance: 8 ohms • Frequency response: 2,500-20,000 Hz • SPL: 111 dB 1W/1m • Magnet weight: 16.5 oz. • Dimensions: 5.12" H x 4.76" W x 3.86" D.

#264-362 \$40.00 LIST **\$33.60** (1-3) **\$32.00** (4-UP)
(RPST350 diaphragm)

#264-363 \$11.00 LIST **\$9.24** (1-3) **\$8.80** (4-UP)

Pyle Pro Horn Tweeters

When demands for widely dispersed, high frequency sounds are great, these horn tweeters are a superb solution. All models feature excellent transient response and are capable of handling very high SPL levels.



PH25 3" x 3" Horn Tweeter

Specifications: • Power handling: 60 watts RMS/120 watts max • VC_{DIA}: 1" • Impedance: 8 ohms • Frequency response: 1,000-15,000 Hz • Magnet weight: 15 oz. • SPL: 100 dB 1W/1m.



#272-104 ... \$12.00 LIST **\$6.50** (1-3) **\$5.85** (4-UP)

PH44 4" x 4" Horn Tweeter

Specifications: • Power handling: 100 watts RMS/200 watts max • VC_{DIA}: 1" • Impedance: 8 ohms • Frequency response: 1,000-18,000 Hz • Magnet weight: 15 oz. • SPL: 105 dB 1W/1m.



#272-102 ... \$14.00 LIST **\$9.90** (1-3) **\$9.25** (4-UP)

PDBT18 1" Bullet Horn Tweeter Pair

Pyle Pro high-dispersion bullet type speakers provide clear imaging of audio program material over a wide range of frequencies and dynamic ranges. All models feature a die-cast aluminum frame, high-temperature ferrofluid cooled voice coil and include crossover capacitor.



Specifications: • Power handling: 60 watts RMS/120 watts max • VC_{DIA}: 1" • Impedance: 4 ohms • Frequency response: 2,000-25,000 Hz • Magnet weight: 20 oz. • SPL: 93 dB 1W/1m.

#272-110 \$33.00 LIST **\$16.50** (1-3 PRS) **\$14.95** (4 PRS-UP)

PSN1165 Wide Dispersion Horn Tweeter Pair

Features an excellent transient response and low distortion.

Specifications: • Power handling: 75 watts RMS/150 watts max • Impedance: 4-8 ohms • Frequency response: 4,000-20,000 Hz • SPL: 94 dB 1W/1m • Dimensions: 4.35" square.



#272-100 \$16.00 LIST **\$9.90** (1-3 PRS) **\$8.80** (4 PRS-UP)

Pro Sound

Speakers, Drivers & Horns

Super Tweeters

Selenium has been designing and manufacturing products

SELENIUM
LOUDSPEAKERS

for the sound reinforcement and musical instrument industry since 1958. These professional super tweeters are engineered for performance, longevity, and compact size. Extremely smooth with excellent dispersion characteristics best describes the sound of these superb pro super tweeters.

DT150-OEM 1" Phenolic Horn Driver

- Ideal for compact 2-way systems
- Nomex voice coil former
- Perfect for use with HM11-25 horn
- 1-1/8"-18 TPI thread



Specifications: • Power handling: 40 watts RMS/80 watts max (xover @ 2 kHz, 12 dB/octave), 75 watts RMS/150 watts max (xover @ 4 kHz, 12 dB/octave) • Minimum recommended crossover: 4 kHz (12 dB/octave) • VC_{DIA}: 1" • Throat diameter: 1" • Impedance: 8 ohms • Frequency response: 1,500-15,000 Hz (-6 dB) • Sensitivity: 108 dB 2.83V/1m (measured on axis on HM11-25 horn, 2,000-8,000 Hz average) • Magnet weight: 10 oz. • Dimensions: Diameter: 3.23", Depth: 2.56".

#264-242 \$30.00 LIST **\$25.20** (1-3) **\$24.00** (4-UP)

#264-243 (RPDT150 diaphragm) \$8.00 LIST **\$6.72** (1-3) **\$6.40** (4-UP)

DT150 Super Tweeter With 4" x 4" Horn

This high power bullet tweeter is ideal for 2-way and 3-way monitor applications. It features a compact 4" x 4" ABS horn lens and durable phenolic diaphragm.

Specifications: • Power handling: 75 watts RMS/105 watts max (conservative, with recommended crossover at 4,000 Hz) • VC_{DIA}: 1" • Impedance: 8 ohms • Frequency response: 1,500-18,000 Hz • SPL: 107 dB 1W/1m • Dimensions: 4" W x 4" H x 4-3/4" D.



#264-240 \$37.00 LIST **\$31.08** (1-3) **\$29.60** (4-UP)

ST304 Super Tweeter

- ABS housing

Specifications: • Power handling: 40 watts RMS/55 watts max • Dispersion: 40° H x 40° V • VC_{DIA}: 1-3/4" • Impedance: 8 ohms • Frequency response: 3,500-18,000 Hz • SPL: 106 dB 1W/1m • Magnet weight: 11 oz • Dimensions: Diameter: 4-1/16", depth: 2-3/8".



#264-350 \$28.00 LIST **\$23.52** (1-3) **\$22.40** (4-UP)

#264-382 (RPST304 diaphragm) \$6.00 LIST **\$5.04** (1-3) **\$4.80** (4-UP)

ST300 Super Tweeter

- Aluminum housing

Specifications: • Power handling: 50 watts RMS/75 watts max • Dispersion: 40° H x 40° V • VC_{DIA}: 1-3/4" • Impedance: 8 ohms • Frequency response: 3,500-20,000 Hz • SPL: 108 dB 1W/1m • Magnet weight: 15 oz • Dimensions: Diameter: 4-1/4", depth: 3-9/16".



#264-355 \$45.00 LIST **\$37.80** (1-3) **\$36.00** (4-UP)

#264-380 (RPST300 diaphragm) \$7.00 LIST **\$5.88** (1-3) **\$5.60** (4-UP)

ST324 Super Tweeter

- ABS housing

Specifications: • Power handling: 40 watts RMS/55 watts max • Dispersion: 120° H x 40° V • VC_{DIA}: 1-3/4" • Impedance: 8 ohms • Frequency response: 3,500-18,000 Hz • SPL: 103 dB 1W/1m • Magnet weight: 11 oz • Dimensions: Diameter: 4", depth: 2-3/8".



#264-360 \$28.00 LIST **\$23.52** (1-3) **\$22.40** (4-UP)

#264-382 (RPST304 diaphragm) \$6.00 LIST **\$5.04** (1-3) **\$4.80** (4-UP)