

The Atlas Sound Strategy Series two-way, surface-mount loudspeaker systems are ideal for indoor and outdoor installation in conference rooms & classrooms, boutiques/shops, restaurants/cafes, decks/patios, recreation/sports centers, amusement/theme parks, and houses of worship.



**Atlas Sound Strategy Series® II Surface Mount Speaker Systems**

- Weather resistant construction for year-round indoor or outdoor use
- UV-resistant, talc impregnated, polypropylene injection molded enclosures
- Powder coated aluminum grilles
- Conforms to stringent 100HR salt spray test per the ASTM B117 standard
- Color matched heavy-duty C-shaped mounting bracket is included
- TRX Control WaveGuide high frequency director for vocal and music accuracy and clarity
- SAE 1/4"-20 brass inserts allow easy integration of "off-the-shelf" security hardware
- Available in black or white, in 70.7V and 8 ohm versions
- Five-year manufacturer's warranty

**SM42T 4" 8 Ohm/70.7V 2-Way Pair**

Includes a 70.7V/100V transformer with screwdriver adjustable tap settings from 2-16 watts for distributed sound applications and a transformer bypass setting for direct coupled 8 ohm applications.

- Specifications:** • Power rating: 30 watts RMS • Impedance: 8 ohms (xfmr. bypassed) • 70.7V Taps: 2, 4, 8, 16 watts • Frequency response: 110 Hz-20 kHz • Dimensions (less bracket): 7" H x 5" W x 5-15/16" D • Sold in pairs.



- #242-810** (Black - SM42T-B)  
**#242-812** (White - SM42T-W) . . . \$134.00 LIST **\$119.65** (1-5 PRS) **\$113.67** (6 PRS-UP)

**SM52 5-1/4" 8 Ohm 2-Way Pair**

- Specifications:** • Power rating: 100 watts RMS • Impedance: 8 ohms • Frequency response: 85 Hz-20 kHz • Dimensions (less bracket): 10-3/16" H x 6-7/8" W x 5-7/8" D • Sold in pairs.



- #242-814** (Black - SM52-B)  
**#242-816** (White - SM52-W) . . . . . **\$214.20** (1-5 PRS) **\$203.49** (6 PRS-UP)

**SM52T 5-1/4" 70.7V/100V 2-Way Pair**

- Specifications:** • Power rating: 30 watts (xfmr. limited) • 70.7V Taps: 0.94, 1.9, 3.7, 7.5, 15, 30 watts • Frequency response: 85 Hz-20 kHz • Dimensions (less bracket): 10-3/16" H x 6-7/8" W x 5-7/8" D • Sold in pairs.

- #242-818** (Black - SM52T-B)  
**#242-820** (White - SM52T-W) . . . . . **\$253.80** (1-5 PRS) **\$241.11** (6 PRS-UP)

**SM82 8" 2-Way Surface Mount Speakers**

For surface mount applications where increased output and tighter pattern control in an environment-resistant, contemporarily styled enclosure is required, the SM82 series is the perfect choice. System components consist of a highly efficient 8" HYCONE™ treated woofer and 1" exit titanium compression driver. Sold individually.



**SM82 8 Ohm Speaker**

- Specifications:** • Power rating: 150 watts RMS/225 watts max • Impedance: 8 ohms • Frequency response: 65 Hz-20 kHz • Sensitivity: 92 dB 1W/1m • Dispersion 65°H x 65°V • Dimensions: 16-1/2" H x 9-1/16" W x 8-7/16" D.

- #242-822** (Black - SM82-B)  
**#242-824** (White - SM82-W) . . . \$189.00 LIST **\$169.86** (1-5) **\$161.37** (6-UP)

**SM82T 70.7V/100V Speaker**

- Specifications:** • Power rating: 60 watts (xfmr. limited) • 70.7V Taps: 1.9, 3.8, 7.5, 15, 30, 60 watts • Frequency response: 65 Hz-20 kHz • Sensitivity: 92 dB 1W/1m • Dispersion 65°H x 65°V • Dimensions (less bracket): 16-1/2" H x 9-1/16" W x 8-7/16" D.

- #242-826** (Black - SM82T-B)  
**#242-828** (White - SM82T-W) . . . \$230.00 LIST **\$199.92** (1-5) **\$189.92** (6-UP)

**Atlas Sound Strategy Series II Ceiling Speaker Systems (UL 1480)**

- Easy installation in drop tile or sheetrock ceilings via C-ring/V-rail tile bridge (included) and "dog leg" mounting system
- Front mounted tap selector switch for easy system tuning adjustments includes transformer bypass setting for 8 ohm direct coupled operation
- Extended low frequency response from the optimally tuned and ported deep drawn galvanized steel enclosure
- 4-pole detachable "phoenix" style connector allows easy pre-wiring and is convenient for daisy chaining additional speakers
- Enhanced quality 70.7V/100V internal transformers minimize insertion loss and maintain low frequency response
- "Press fit" grilles blend better into contemporary architecture



Atlas Sound's Strategy Series® II premium ceiling speaker packages will satisfy the needs of owners, architects, contractors, and consultants by delivering true, high fidelity sound reproduction in an attractive and easy-to-install system. Each speaker system ships complete with speaker/transformer factory assembled into back can, grill, and unique C-ring/V-rail mounting hardware. Sold in pairs.

**FAP42TC Compact 4" Coaxial Speaker Pair**

With an overall depth of 4" (102 mm) the FAP42TC is the perfect choice when high fidelity audio and wide, even coverage is required but space above the plenum is limited. For wall mount applications (tanning salons or surround sound) the short 4" depth will even work in most stud wall installations.

- Specifications:** • Power rating: 16 watts (transformer limited) • 70.7V Taps: 1, 2, 4, 8, 16 watts • Frequency response: 75 Hz-20 kHz • Dispersion: 130° • Dimensions: Overall: 10-1/2" dia. x 4-1/4" H • Cutout: 9" dia.



- #242-804** . . . . . \$158.00 LIST **\$139.67** (1-5 PRS) **\$132.69** (6 PRS-UP)

**FAP62T 6" Coaxial Speaker Pair**

Compact profile enclosure and wide dispersion make the FAP62T a perfect choice for low ceilings.

- Specifications:** • Power rating: 50 watts (transformer limited) • 70.7V Taps: 2, 4, 8, 16, 32 watts • Frequency response: 63 Hz-20 kHz • Dispersion: 110° • Dimensions: Overall: 12-1/2" dia. x 8-1/2" H • Cutout: 11" dia.



- #242-806** . . . . . \$210.00 LIST **\$188.25** (1-5 PRS) **\$178.84** (6 PRS-UP)

**FAP82T 8" Coaxial Speaker Pair**

The FAP82T is perfect where high ceilings require loudspeakers with increased efficiency and tighter pattern control. Tight pattern control (not exceeding 100°) is important for high ceiling applications.

- Specifications:** • Power rating: 70 watts (at 8 ohms) • 70.7V Taps: 1.9, 3.8, 7.5, 15, 30, 60 watts • Frequency response: 65 Hz-20 kHz • Dispersion: 100° • Dimensions: Overall: 15-3/4" dia. x 12-3/4" H • Cutout: 14" dia.



- #242-808** . . . . . \$280.00 LIST **\$249.87** (1-5 PRS) **\$237.38** (6 PRS-UP)

**FAPSUB 8" Subwoofer Speaker Pair**

The FAPSUB adds impressive low frequency response to any full range distributed system. A high efficiency passive crossover network eliminates the need for a dedicated amplifier and/or active crossover, while its low crossover point greatly reduces localization.

- Specifications:** • Power rating: 100 watts/200 watts max (transformer limited) • 70.7V Taps: 1.9, 3.8, 7.5, 15, 30, 60 watts • Frequency response: 45-120 Hz (±10 dB) • Low pass filter: 120 Hz (18 dB/octave) • Dimensions: Overall: 15-3/4" dia. x 12-3/4" H • Cutout: 14" dia.



- #242-809** . . . . . \$436.00 LIST **\$392.40** (1-5 PRS) **\$372.78** (6 PRS-UP)