

Pro Sound

Amplifiers

Studio Pro's commitment to power, quality and value also extends to the world of professional audio. These amplifiers are just the ticket for just about any pro audio application. Choose from the passive cooled PA600X or the high-power PA1000X that adds an auxiliary cooling fan.



Features: Separate volume control for channels A and B • Dual RCA and dual 1/4" line inputs • LED clipping indicator • Rack-mountable with handles • Convenient 3-way binding-post connectors for 4 speakers • Channel A-B/A&B selector • Heavy duty aluminum heatsinks • The bridgeable PA1000X also features dual illuminated VU meters with meter range switch • 2-year limited manufacturer's warranty.

PA600X Power Amplifier

Specifications:

- Power output: 95 watts RMS x 2 (8 ohm load), 150 watts RMS/300 watts peak x 2 (4 ohm load)
- Frequency response: 10-50,000 Hz • Signal-to-noise ratio: 90 dB • THD: < 0.1% • Dimensions: 19" W x 4" H x 10 3/4" D • Net weight: 25 lbs.



#245-515 \$299.00 LIST **\$155.60** (1-3) **\$148.75** (4-UP)

PA1000X Power Amplifier

Specifications:

- Power output: 175 watts RMS x 2 (8 ohm load), 250 watts RMS/500 watts peak x 2 (4 ohm load)
- Bridgeable to 1000 watts peak x 1 (8 ohm load) • Frequency response: 10-50,000 Hz • Signal-to-noise ratio: 90 dB • THD: < 0.1% Dimensions: 19" W x 4-1/2" H x 12" D • Net weight: 31 lbs.



#245-525 \$399.00 LIST **\$217.80** (1-3) **\$199.90** (4-UP)

Pyle Pro Silver Face Power Amplifiers

- 2U rack mountable
- LED output level meters
- Right and left output level controls
- Heavy-duty fan-cooled design
- Signal LED
- Switched AC accessory outlet
- Dual combo XLR/1/4" jack and RCA line-level inputs
- A/B speaker selector and stereo/mono switches
- Binding post speaker outputs
- Front panel headphone jack

PT2400 Power Amplifier

Specifications:

- Power output: 80 watts RMS x 2 (8 ohms, 20-20,000 Hz), 120 watts RMS x 2 (4 ohms, 1 kHz)
- Bridged: 180 watts RMS x 1 (8 ohms, 20-20,000 Hz), 230 watts RMS x 1 (8 ohms, 1 kHz) • Frequency response: 10-50,000 Hz • S/N ratio: 90 dB • THD (at rated output power): 0.1% • Weight: 18.7 lbs. • Dimensions: 3-15/32" H x 19" W x 10-5/8" D.



#248-470 \$269.80 LIST **\$148.75** EACH

PT2800 Power Amplifier

Specifications:

- Power output: 125 watts RMS x 2 (8 ohms, 20-20,000 Hz), 190 watts RMS x 2 (4 ohms, 1 kHz)
- Bridged: 320 watts RMS x 1 (8 ohms, 20-20,000 Hz), 370 watts RMS x 1 (8 ohms, 1 kHz) • Frequency response: 10-50,000 Hz • S/N ratio: 90 dB • THD (at rated output power): 0.1% • Weight: 20.5 lbs. • Dimensions: 3-15/32" H x 19" W x 10-5/8" D.



#248-472 \$370.50 LIST **\$189.68** EACH

Pyle Pro Rack Mount Power Amplifiers



- Rack mountable
- A/B speaker selector switch
- Stereo/mono switch
- Dual combo XLR/1/4" and RCA inputs
- Binding post speaker outputs
- Right and left output level controls
- Clip & protection circuitry
- LED clip indicator
- Heavy duty fan-cooled aluminum heat sinks
- Front panel headphone jack
- Switched AC accessory outlet

PT1200 Power Amplifier

Specifications:

- Power output: 70 watts RMS x 2 (8 ohms, 20-20,000 Hz), 100 watts RMS x 2 (4 ohms, 1 kHz)
- Bridged: 150 watts RMS x 1 (8 ohms, 20-20,000 Hz), 200 watts RMS x 1 (8 ohms, 1 kHz) • Frequency response: 10-50,000 Hz • S/N ratio: 90 dB • THD (at rated output power): 0.1% • Weight: 19.8 lbs. • Dimensions: 4-3/16" H x 18-15/16" W x 10-3/4" D.



#248-435 \$307.80 LIST **\$191.42** EACH

PT1600 Power Amplifier

Specifications:

- Power output: 100 watts RMS x 2 (8 ohms, 20-20,000 Hz), 140 watts RMS x 2 (4 ohms, 1 kHz) • Bridged: 250 watts RMS x 1 (8 ohms, 20-20,000 Hz), 280 watts RMS x 1 (8 ohms, 1 kHz)
- Frequency response: 10-50,000 Hz • S/N ratio: 90 dB • THD (at rated output power): 0.1% • Weight: 24.7 lbs. • Dimensions: 4-15/32" H x 18-7/8" W x 12" D.



#248-440 \$378.10 LIST **\$234.28** EACH

PT2000 Power Amplifier

Specifications:

- Power output: 120 watts RMS x 2 (8 ohms, 20-20,000 Hz), 175 watts RMS x 2 (4 ohms, 1 kHz) • Bridged: 300 watts RMS x 1 (8 ohms, 20-20,000 Hz), 350 watts RMS x 1 (8 ohms, 1 kHz)
- Frequency response: 10-50,000 Hz • S/N ratio: 90 dB • THD (at rated output power): 0.1% • Weight: 28.2 lbs. • Dimensions: 5-1/8" H x 19" W x 12" D.



#248-445 \$435.10 LIST **\$262.85** EACH



ART SLA-1 & SLA-2 Power Amplifiers



- Efficient convection cooling combined with on-demand SmartFan design
- Perfect for professional, project, and home studios
- Rugged enough for live sound-and only one rack space high!
- Up to 560 watts bridged mono in a single rack space (SLA-2)

The SLA-1 and SLA-2 Studio Linear Amplifiers are robust yet compact power amplifiers designed for studio and even live applications. They have been designed and engineered to provide clean, quiet power and excellent sound with ultra-low noise and distortion. The SLA-1 is rated at 100 watts RMS/ch. @ 8 ohms (130 watts RMS/ch. @ 4 ohms and 260 watts RMS bridged mono @ 8 ohms), and the SLA-2 is rated at 200 watts RMS/ch. @ 8 ohms (280 watts RMS/ch. @ 4 ohms and 560 watts RMS bridged mono @ 8 ohms). Hum and noise on both amps is better than 100 dB below clipping, and they feature XLR and 1/4" inputs and ground lift switch. •Dimensions: (SLA-1): 1.75" H x 19" W x 9.5" D. •Weight: 13.2 lbs. •Dimensions: (SLA-2): 1.75" H x 19" W x 13.5" D. •Weight: 19.8 lbs.

#245-860 (SLA-1 100 watts/ch.) \$275.00 LIST **\$229.00** EACH

#245-861 (SLA-2 200 watts/ch.) \$370.00 LIST **\$289.00** EACH