



NC3MBH

3 pole male XLR receptacle, grounding: separate ground contact to mating connector shell and front panel, steel retention lug, horizontal PCB mount

Same as A series with exception of a metal mounting flange featuring continuous circumferential ground contact to chassis for best EMC practice. UL recognized component.

Features & Benefits

- Smallest XLR receptacles, highest packing density
 - Metal mounting flange featuring continuous circumferential ground contact to chassis for best EMC and RF protection
-
- Housing flammability UL94V-0

Technical Information

Product	
Title	NC3MBH
Connection Type	XLR
Gender	male

Electrical	
Capacitance between contacts	$\leq 4\text{ pF}$
Contact resistance	$\leq 6\text{ m}\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10\text{ G}\Omega$ (initial)
Rated current per contact	6 A
Rated voltage	$< 50\text{ V}$
Grounding Options	yes , separate ground contact connected to mating connector shell and front panel, no connection to Pin 1

Mechanical

Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	
Wiring	Horizontal PCB mount
Locking device	Latch lock
Mounting direction	Rear mounting
Chassis shape	B
Mounting	B-Screw

Material

Contact plating	0.2 µm AuCo over 2µm NiP15 (Tribor®)
Contacts	Brass (CuZn35Pb2)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Ck 67 steel, treated
Ring	Zinc diecast (ZnAl4Cu1), gal Ni

Environmental

Approvals	UL
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C