

Legend Guitar 10"

LEGEND 1028K

The Eminence Legend 1028K guitar speaker is a classic stage fixture. Vintage American tone with moderate, but tight, percussive lows and extended highs. Hard-working under the bright lights.



SPECIFICATION

Nominal Basket Diameter	10.0", 254 mm	Enclosure Type
Nominal Impedance*	8 Ω	Closed Back
Power Rating**	35 W	Open Back
Resonance (Fs)	95 Hz	Overall Diameter
Usable Frequency Range	100 Hz – 5.0 kHz	Baffle Hole Diameter
Sensitivity***	97.4 dB	Depth
DC Resistance (Re)	5.80 Ω	Front Sealing Gasket
Magnet Weight	6 OZ.	Rear Sealing Gasket
Gap Height	.250", 6.4 mm	Mounting Holes Diameter
Voice Coil Diameter	1.0", 25 mm	Mounting Holes B.C.D.
		Not Woight


MOUNTING INFORMATION

Enclosure Type	
Closed Back	Acceptable
Open Back	Acceptable
Overall Diameter	10.11", 256.8 mm
Baffle Hole Diameter	9.13", 231.9 mm
Depth	4.80", 121.9 mm
Front Sealing Gasket	Yes
Rear Sealing Gasket	N/A
Mounting Holes Diameter	0.22", 5.6 mm
Mounting Holes B.C.D.	9.60", 243.8 mm
Net Weight	2.90 lbs , 1.32 kg
Shipping Weight	4.00 lbs , 1.81 kg

MATERIALS OF CONSTRUCTION

Copper voice coil	
Polyimide former	3 - TAN
Alnico magnet	-
Non-vented core	
Pressed steel basket	
Paper cone	
Paper cone edge	
Solid composition felt dust cap	

FREQUENCY RESPONSE*









From design and manufacturing to the stage or studio. Once you've experienced the performance of Eminence, you'll never accept anything else.

MISSION STATEMENT

Eminence is dedicated to providing the best Quality, Value and Service to meet our customers' needs.

FOOTNOTES

- Please consult www.eminence.com for specifications of models with alternative impedances.
- ** Multiple units exceed published ratings evaluated under EIA 426A specification while tested in a free-air, non-temperature-controlled environment.
- *** The average output across the usable frequency range when applying 1W/1m into the nominal impedance. i.e: $2.83V/8\Omega$, $4V/16\Omega$. Eminence response curves are measured under the following conditions: All speakers are tested at 1W/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2 ft. x 2 ft. baffle is built into the wall with the speaker mounted flush against a steel ring for minimum diffraction | Carver PM-120 amplifier | 2700 cu. ft. chamber with fiberglass on all six surfaces (three with custommade wedges).
- **** BETA 8CX, 10CX, and 12CX are coaxial speakers with tweeter sold separately. Published usable frequency response contingent upon use of ASD:1001 HF Driver.
- ***** Multiple units exceeded published ratings evaluated under EIA-426A or AES specification while mounted on Eminence's H290, H290S, or H2EA horn in a non-temperature-controlled environment.
- ******The average on axis output across the entire usable frequency range when applying 1W/1m into the nominal impedance, i.e. $2.83V/8\Omega$, $4V/16\Omega$. Eminence response curves are measured under the following conditions: All speakers are tested at 1W/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2ft x 2ft baffle is built into the wall with horn front mounted | Carver PM-120 amplifier | 2700 cu.ft. chamber with fiberglass on all six surfaces (three with custom-made wedges).

Prices, specifications and product cosmetics are subject to change without notice.



